



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Food Plant Machine Oil

**Other means of identification**  
**Product Code** No. 73081 (Item# 1006168)

**Recommended use** Machine oil and lubricant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Canada Co.

**Address** 2-1246 Lorimar Drive  
Mississauga, Ontario L5S 1R2  
Canada

**Telephone**

**General Information** 905-670-2291

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (Canada)  
703-527-3887 (International)

**Website** www.crc-canada.ca

**E-mail** Support.CA@crcindustries.com

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 2  
Gases under pressure Compressed gas

**Health hazards** Aspiration hazard Category 1

**Environmental hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement** Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

### Precautionary statement

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

**Response** IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

**Storage** Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards** None known.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light		64742-47-8	60 - 80
white mineral oil (petroleum)		8042-47-5	15 - 40
carbon dioxide		124-38-9	1 - 5

The exact percentage (concentration) of composition has been withheld as a trade secret.  
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

---

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Get medical advice/attention if you feel unwell. Wash off with soap and water.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

---

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

---

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

---

#### 7. Handling and storage

<b>Precautions for safe handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
--------------------------------------	---

**Conditions for safe storage, including any incompatibilities**

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
white mineral oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
	TWA	30000 ppm 9000 mg/m3	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	5000 ppm 200 mg/m3	Vapor.
white mineral oil (petroleum) (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	15000 ppm	
	TWA	5000 ppm	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
white mineral oil (petroleum) (CAS 8042-47-5)	TWA	1 mg/m3	Mist.

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
white mineral oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
	TWA	30000 ppm 9000 mg/m3 5000 ppm	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	1590 mg/m3	
		400 ppm	
white mineral oil (petroleum) (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines****Canada - Alberta OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear protective gloves such as: Nitrile. Neoprene.

**Other** Wear suitable protective clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

**9. Physical and chemical properties****Appearance**

**Physical state** Liquid.

**Form** Aerosol.

**Color** Clear.

**Odor** Odorless.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -56.2 °F (-49 °C) estimated

**Initial boiling point and boiling range** 424.4 °F (218 °C) estimated

**Flash point** 200 °F (93.3 °C) Tag Closed Cup

**Evaporation rate** Very slow.

<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	0.6 % estimated
<b>Flammability limit - upper (%)</b>	5.5 % estimated
<b>Vapor pressure</b>	903 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.82 estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	419 °F (215 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Percent volatile</b>	98.4 % estimated

---

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

---

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Prolonged skin contact may cause temporary irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics**      Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

### Information on toxicological effects

**Acute toxicity**      May be fatal if swallowed and enters airways.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
white mineral oil (petroleum) (CAS 8042-47-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
* Estimates for product may be based on additional component data not shown.		
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>		
<b>ACGIH Carcinogens</b>		
white mineral oil (petroleum) (CAS 8042-47-5)	A4 Not classifiable as a human carcinogen.	
<b>Canada - Manitoba OELs: carcinogenicity</b>		
white mineral oil (petroleum) (CAS 8042-47-5)	Not classifiable as a human carcinogen.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
white mineral oil (petroleum) (CAS 8042-47-5)	3 Not classifiable as to carcinogenicity to humans.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
<b>Components</b>			
distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
white mineral oil (petroleum) (CAS 8042-47-5)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Fish	> 10000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

white mineral oil (petroleum) > 4, log Pow

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

### 13. Disposal considerations

<b>Disposal of waste from residues / unused products</b>	Contents under pressure. Do not puncture, incinerate or crush. Empty container can be recycled. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	Not regulated.
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### 14. Transport information

#### TDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	80, 107

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

#### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, LIMITED QUANTITY
<b>Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

---

### 15. Regulatory information

#### Canadian regulations

##### Controlled Drugs and Substances Act

Not regulated.

##### Export Control List (CEPA 1999, Schedule 3)

Not listed.

##### Greenhouse Gases

carbon dioxide (CAS 124-38-9)

### Precursor Control Regulations

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

carbon dioxide (CAS 124-38-9) Listed.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Not applicable.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

---

## 16. Other information

<b>Issue date</b>	09-28-2016
<b>Version #</b>	01
<b>Further information</b>	CRC # 555B-C/1002573-1002575

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..