



CHEMICAL PRODUCT SAFETY DATA SHEET

Prepared in accordance with GB/T 16483 and GB/T 17519.

Product name: Food Grade White Grease

Issue date: 11-01-2016
Revision date: 10-16-2018
Version #: 02
SDS No: -

SECTION 1 Chemical product and company identification

Product name Food Grade White Grease
Product Code No. PR03038 (Item# 1007669)
Manufactured or sold by:
Company name CRC Industries Trading (Shanghai) Co., Ltd.
Address Room 1710, No. 488 South Wuning Road
Jingan District - 200042
Shanghai, PR China
General Information +86 21 6236 6035
24-Hour Emergency +86 532 83889090
Website www.crcindustries.cn

Recommended use and Limitations on use

Recommended use Grease
Issue date 11-01-2016
Revision date 10-16-2018
Supersedes date 11-01-2016

SECTION 2 Hazards identification

Emergency overview

Aerosol. CONTENTS UNDER PRESSURE.
Pressurized container may rupture when exposed to heat or flame. May be fatal if swallowed and enters airways. May be harmful in contact with skin. May cause drowsiness and dizziness. Causes skin irritation. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses.

Hazard categories

Physical hazards	Aerosols	Category 1
Health hazards	Acute toxicity, dermal	Category 5
	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

Label elements

Pictograms



Signal word

Danger

Hazard statement

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statement**Prevention**

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapor.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P391	Collect spillage.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Physical and chemical hazards

Extremely flammable aerosol. The product is stable and non-reactive under normal conditions of use, storage and transport.

Health hazards

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May be harmful in contact with skin. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. Causes skin irritation. Direct contact with eyes may cause temporary irritation.

Environmental hazards

Very toxic to aquatic life with long lasting effects.

Supplemental information

None.

SECTION 3 Composition/information on ingredients

Substance/mixture	Mixture		
Chemical name		Concentration (%)	CAS Number
naphtha (petroleum), hydrotreated light		10 - 20	64742-49-0
white mineral oil		10 - 20	8042-47-5
n-heptane		5 - 10	142-82-5
3-methylhexane		3 - 5	589-34-4
methylcyclohexane		3 - 5	108-87-2
2-methylhexane		1 - 3	591-76-4
calcium carbonate		1 - 3	1317-65-3
zinc oxide		1 - 3	1314-13-2
2,3-dimethylpentane		< 1	565-59-3
3-ethylpentane		< 1	617-78-7
3,3-dimethylpentane		< 0.2	562-49-2

SECTION 4 First aid measures**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms and health effects	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
Personal protection for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
Notes to physician	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5 Fire-fighting measures

Extinguishing media	Water fog. Foam. Dry chemicals. Carbon dioxide (CO ₂).
Extinguishing media to avoid	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
Protection of fire-fighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
General fire hazards	Extremely flammable aerosol.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
Clean-up methods and materials and containment measures	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Prevention of secondary hazards	Not available.

SECTION 7 Handling and storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Storage	Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8 Exposure controls/personal protection

Exposure limits

China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007)

Components	Type	Value	Form
calcium carbonate (CAS 1317-65-3)	PC-TWA	8 mg/m ³	Total dust.
		4 mg/m ³	Respirable dust.
n-heptane (CAS 142-82-5)	PC-STEL	1000 mg/m ³	
	PC-TWA	500 mg/m ³	
zinc oxide (CAS 1314-13-2)	PC-STEL	5 mg/m ³	
	PC-TWA	3 mg/m ³	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Monitoring methods

Follow standard monitoring procedures.

Engineering measures

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Hand protection

Wear protective gloves such as: Nitrile.

Eye protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear appropriate chemical resistant clothing.

Hygiene measures

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9 Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol.

Color

White.

Odor

Petroleum.

pH

Not available.

Melting point/freezing point

-195.9 °F (-126.6 °C) estimated

Boiling point, initial boiling point, and boiling range

201.2 °F (94 °C) estimated

Flash point

17.6 °F (-8 °C) estimated

Flammability limit - lower (%)

1.1 % estimated

Flammability limit - upper (%)

6.7 % estimated

Explosive limit - lower (%)

1.1 % estimated

Explosive limit - upper (%)

6.7 % estimated

Vapor pressure

3440 hPa estimated

Vapor density

> 1 (air = 1)

Relative density

0.63 estimated

Density

5.29 lbs/gal estimated

Solubility(ies)

Solubility (water)

Slight.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

473 °F (245 °C) estimated

Decomposition temperature

Not available.

Evaporation rate	Moderate.
Other data	
Percent volatile	90.7 % estimated

SECTION 10 Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Oxidizing agents. Acids. Oxygen.
Hazardous decomposition products	Carbon oxides.

SECTION 11 Toxicological information

Acute toxicity	In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and central nervous system effects. May be fatal if swallowed and enters airways. May be harmful in contact with skin.
-----------------------	---

Components	Species	Test Results
3-methylhexane (CAS 589-34-4)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 hours
Oral		
LD50	Rat	> 2000 mg/kg
methylcyclohexane (CAS 108-87-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 4000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	3000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours
Oral		
LD50	Rat	25000 mg/kg
white mineral oil (CAS 8042-47-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
Inhalation		
LC50	Rat	> 5 mg/l, 4 hours
Chronic		
Oral		
LD50	Rat	> 5000 mg/kg
zinc oxide (CAS 1314-13-2)		
Acute		
Inhalation		
LC50	Rat	> 1.79 mg/l, 4 hours (no deaths occurred)
Oral		
LD50	Rat	> 5000 mg/kg
Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.	
Symptoms	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.	
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitizer	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
white mineral oil (CAS 8042-47-5)	3 Not classifiable as to carcinogenicity to humans.	
Toxic to reproduction	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity following single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity following repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	

SECTION 12 Ecological information

Ecotoxicological data

Components	Species	Test Results
zinc oxide (CAS 1314-13-2)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 0.098 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 1.1 mg/l, 96 hours
Ecotoxicity	Very toxic to aquatic life with long lasting effects.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulation		
Bioaccumulative potential		
Bioconcentration factor		
naphtha (petroleum), hydrotreated light	10 - 25000	
zinc oxide	60690	
Octanol/water partition coefficient log Kow		
methylcyclohexane	3.61	
n-heptane	4.66	
Mobility in soil	This product is miscible in water.	
Other hazardous effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

SECTION 13 Disposal considerations

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
Local disposal regulations	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14 Transport information

CNDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmentally hazardous	Yes
Special precautions for user	Not available.

IATA


UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Exempt from the regulations.
ERG Code	10L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG


UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Exempt from the regulations.
EmS	F-D, S-U
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.


CNDG; IMDG



IATA



Marine pollutant



SECTION 15 Regulatory information

Law of the People's Republic of China on Prevention and Control of Occupational Diseases

Not regulated.

Regulations on the Control over Safety of Dangerous Chemicals

Catalog of Hazardous Chemicals

2,3-DIMETHYL PENTANE (CAS 565-59-3)	2,3-DIMETHYL PENTANE
2-METHYL HEXANE (CAS 591-76-4)	2-METHYL HEXANE
3,3-DIMETHYL PENTANE (CAS 562-49-2)	3,3-DIMETHYL PENTANE
3-ETHYL PENTANE (CAS 617-78-7)	3-ETHYL PENTANE
Hexane, 3-methyl- (CAS 589-34-4)	Hexane, 3-methyl-
METHYLCYCLOHEXANE (CAS 108-87-2)	METHYLCYCLOHEXANE
NAPHTHA (CAS 64742-49-0)	NAPHTHA
N-HEPTANE (CAS 142-82-5)	N-HEPTANE

List of Priority Management of Hazardous Chemicals

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Measures for the Environmental Management Registration of Hazardous Chemicals (for Trial Implementation)

Not regulated.

Regulations on Labor Protection in Workplaces Where Toxic Substances Are Used

Regulations for Environmental Management On the First Import of Chemicals and the Import and Export of Toxic Chemicals

Provision on the Environmental Administration of New Chemical Substances

Inventory of Existing Chemical Substances in China

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Other regulations

This safety data sheet conforms to the following laws, regulations and standards:
 Regulations on the Control over Safety of Dangerous Chemicals
 Regulations on Labor Protection in Workplaces Where Toxic Products Are Used
 Measures for the Safe Use of Chemicals in Workplaces
 Safety Data Sheet for Chemical Products - Content and Order of Sections (GB/T 16483-2008)
 General Rules for Preparation of Precautionary Labels for Chemicals (GB15258-2009)
 Packing Symbol of Dangerous Goods(GB190-2009)
 Packing - Pictorial Marking for Handling of Goods (GB/T191-2009)

China. National Catalogue of Hazardous Wastes

white mineral oil (CAS 8042-47-5)
 zinc oxide (CAS 1314-13-2)

List of Priority Management of Hazardous Chemicals

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Montreal Protocol

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

SECTION 16 Other information**References**

EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Trading (Shanghai) Co., Ltd..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.