



SAFETY DATA SHEET

SECTION 1. Identification of the hazardous chemical substance or mixture and of the supplier or manufacturer

GHS product identifier	Battery Terminal Protector	
Other means of identification		
Product Code	No. MX05046 (Item# 1008059)	
Recommended use of the chemical and restrictions on use		
Recommended use	Battery terminal protector	
Recommended restrictions	None known.	
Suppliers details		
Company name	CRC Industrias de Mexico S. de R. L. de C.V.	
Address	Cerrada Canadá 201-H Fraccionamiento Industrial Martel Santa Catarina, NL 66367 Mexico	
Telephone	General Information	81-2139-0572
Website	www.crc-mexico.com	
E-mail	SoporteTecnico@crcind.com	
Emergency phone number	24-Hour Emergency	01-800-681-9531

SECTION 2: Hazard identification

Classification of the substance or mixture

Physical hazards	Aerosols	Category 1
Health hazards	Acute toxicity, dermal	Category 5
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Carcinogenicity	Category 2
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (auditory system, central nervous system, kidney, liver)
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 2

GHS label elements, including precautionary statements



Signal word Danger

Hazard statement

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

H361	Suspected of damaging fertility.
H373	May cause damage to organs (auditory system, central nervous system, kidney, liver) through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement**Prevention**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist or vapor.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P391	Collect spillage.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Other hazards which do not result in classification None known.

Supplemental information None.

SECTION 3. Composition/information on ingredients**Mixtures**

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
liquefied petroleum gas		68476-86-8	20 - 30
naphtha (petroleum), hydrotreated light		64742-49-0	20 - 30
heptane, branched, cyclic and linear		426260-76-6	10 - 20
petrolatum		8009-03-8	10 - 20
solvent naphtha (petroleum), light aliph.		64742-89-8	5 - 10
n-heptane		142-82-5	3 - 5
2-methylpentane		107-83-5	1 - 3

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
3-methylhexane		589-34-4	1 - 3
methylcyclohexane		108-87-2	1 - 3
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	1 - 3
xylene		1330-20-7	1 - 3
ethylbenzene		100-41-4	< 1
n-hexane		110-54-3	< 1

Composition comments Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4. First-aid measures

Description of necessary first-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Edema. Jaundice. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective actions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

SECTION 6. Measures that must be taken in the event of accidental spillage or an accidental leak

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
------------------------------------	---

For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

SECTION 7. Handling and storage

Precautions to ensure safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Mexico. Occupational Exposure Limit Values

Components	Type	Value
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
ethylbenzene (CAS 100-41-4)	TWA	20 ppm
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm
	STEL	500 ppm
n-heptane (CAS 142-82-5)	TWA	400 ppm
	STEL	500 ppm
n-hexane (CAS 110-54-3)	TWA	50 ppm
	TWA	5 mg/m ³
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m ³
	TWA	5 mg/m ³
petrolatum (CAS 8009-03-8)	TWA	5 mg/m ³
	TWA	5 mg/m ³
xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
3-methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	
ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-hexane (CAS 110-54-3)	TWA	50 ppm	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Biological limit values**Mexico. Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.7 g/g	Suma de ácido mandélico y ácido fenilgloxílico	Creatinine in urine	*
n-hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanodiona, Sin hidrólisis	Urine	*
xylene (CAS 1330-20-7)	1.5 g/g	Ácido metilhipúricos	Creatinine in urine	*

* - For sampling details, please see the source document.

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
n-hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*
xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**Mexico OELs: Skin designation**

n-hexane (CAS 110-54-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-hexane (CAS 110-54-3)

Can be absorbed through the skin.

Control banding approach

Not available.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Hazardous Chemicals (NOM-028-STPS-2012, System for administration of workplace safety in the process and critical equipment for handling hazardous chemicals, Appendix A, Table A.I, 9/6/2012)

ethylbenzene (CAS 100-41-4)	4600 KG
n-heptane (CAS 142-82-5)	4600 KG
n-hexane (CAS 110-54-3)	4600 KG
xylene (CAS 1330-20-7)	4600 KG

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton rubber (fluor rubber).
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Aerosol.
Color	Dark red.

Odor Petroleum.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -131.1 °F (-90.6 °C) estimated

Initial boiling point and boiling range 118.4 °F (48 °C) estimated

Flash point < 0 °F (< -17.8 °C) estimated

Evaporation rate Fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1 % estimated

Flammability limit - upper (%) 8 % estimated

Vapor pressure 1452.2 hPa estimated

Vapor density Not available.

Relative density 0.73

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 489.2 °F (254 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Molecular weight Not available.

Other information

Percent volatile 65.7 % estimated

SECTION 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Hydrogen sulfide. Mercaptans. Sulfides. Hydrocarbon fumes and smoke. Aldehydes.

SECTION 11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	May be harmful in contact with skin. Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Edema. Jaundice.

Delayed and immediate effects and also chronic effects from short and long term exposure

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. May be harmful in contact with skin.

Components	Species	Test Results
------------	---------	--------------

3-methylhexane (CAS 589-34-4)

Acute

Dermal

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

Inhalation

LC50	Rat	> 20 mg/l, 4 hours
------	-----	--------------------

Oral

LD50	Rat	> 2000 mg/kg
------	-----	--------------

ethylbenzene (CAS 100-41-4)

Acute

Dermal

LD50	Rabbit	15400 mg/kg
------	--------	-------------

Oral

LD50	Rat	3500 mg/kg
------	-----	------------

heptane, branched, cyclic and linear (CAS 426260-76-6)

Acute

Dermal

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

Inhalation

LC50	Rat	> 60 mg/l, 4 hours
------	-----	--------------------

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

methylcyclohexane (CAS 108-87-2)

Acute

Dermal

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

Components	Species	Test Results
Oral		
LD50	Rat	> 4000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	3000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours
Oral		
LD50	Rat	25000 mg/kg
n-hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 1300 mg/kg
Oral		
LD50	Rat	15840 mg/kg
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
petrolatum (CAS 8009-03-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 hours
Oral		
LD50	Rat	> 2000 mg/kg
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 3000 mg/kg

Components	Species	Test Results
xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 4300 mg/kg
Inhalation		
LC50	Rat	29 mg/l, 4 hours
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
ACGIH Carcinogens		
ethylbenzene (CAS 100-41-4)		A3 Confirmed animal carcinogen with unknown relevance to humans.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)		A4 Not classifiable as a human carcinogen.
petrolatum (CAS 8009-03-8)		A4 Not classifiable as a human carcinogen.
xylene (CAS 1330-20-7)		A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity		
ethylbenzene (CAS 100-41-4)		2B Possibly carcinogenic to humans.
xylene (CAS 1330-20-7)		3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Possible reproductive hazard. Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (auditory system, central nervous system, kidney, liver) through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Other information	Not available.	

SECTION 12. Ecotoxicological information

Ecotoxicity	Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
2-methylpentane		3.74
ethylbenzene		3.15
methylcyclohexane		3.61
n-heptane		4.66
n-hexane		3.9
xylene		3.12 - 3.2
Bioconcentration factor (BCF)		
ethylbenzene		1
naphtha (petroleum), hydrotreated light		10 - 25000
xylene		23.99
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

SECTION 13. Disposal considerations

Disposal methods

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. Transport information

SCT

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA


UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG


UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.

EmS

F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.**DOT; IMDG; SCT**

IATA



SECTION 15. Regulatory information

Safety, health and environmental regulations specific for the product in question

Mexico. Hazard identification guidance list (NOM-018-STPS)

2-methylpentane (CAS 107-83-5)	Listed.
3-methylhexane (CAS 589-34-4)	Listed.
ethylbenzene (CAS 100-41-4)	Listed.
methylcyclohexane (CAS 108-87-2)	Listed.
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
n-heptane (CAS 142-82-5)	Listed.
n-hexane (CAS 110-54-3)	Listed.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	Listed.
petrolatum (CAS 8009-03-8)	Listed.
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	Listed.
xylene (CAS 1330-20-7)	Listed.

Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)

xylene (CAS 1330-20-7)	1000 KG
	5000 KG

International regulations

Montreal Protocol

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16. Other included information relevant to the preparation and updating of safety data sheets

Issue date 10-05-2018

Version # 01

List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

SCT: Secretariat of Communications and Transportation (NOM-002-SCT/2011).

DOT: Department of Transportation (49 CFR 172.101).

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

IATA: International Air Transport Association.

IMDG Code: International Maritime Dangerous Goods Code.

MARPOL: International Convention for the Prevention of Pollution from Ships.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

References

NOM-010-STPS-2014 (second revision) – Occupational Exposure Limits – becomes effective on April 28, 2016

NOM-018-STPS-2000 – Workplace Hazardous Chemical Substances Communication and Identification Standard

NOM-028-STPS-2012 – Work-Safety Management System for Processes and Critical Equipment Handling Hazardous Chemical Substances

Workplace Threshold Quantities of Hazardous Chemicals

NOM-047-SSA1-2011 – Workplace Biological Exposure Indices (BEIs) to Chemical Substances

Further information

CRC # 597P-Q/1002627-1002629

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industrias de Mexico S. de R. L. de C.V..

Revision information

Product and Company Identification: Product Codes

Composition / Information on Ingredients: Ingredients

Physical & Chemical Properties: Multiple Properties

GHS: Classification