MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Power Lube ® Multi-Purpose Lubricant

Product Number (s): 10271

Manufactured By: CRC Industries, Inc. (215) 674-4300

885 Louis Drive, Warminster, PA 18974

24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

Component	CAS	ACGIH	OSHA	OTHER	%
	NUMBER	TLV	PEL	LIMITS	
Inhibited Paraffinic Oil	Mixture	5 mg/m3	5 mg/m3	(mist)	23-33
Isohexanes	107-83-5	500 ppm	500 ppm	NE	30-40
n-Hexane	110-54-3	50 ppm	50 ppm	NE	< 10
Methyl Salicylate	119-36-8	NE	NE	NE	< 10
Dipropylene glycol methyl ether	34590-94-8	100 ppm	100 ppm	NE	< 10
Zinc Dithiophosphate	19210-06-1	NE	NE	NE	< 10
Propane	74-98-6	NE	1000 ppm	NE	10-20
Isobutane	75-28-5	NE	NE	1000 ppm	10-20

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: An amber, opaque liquid with an oil of wintergreen odor.

Danger: Extremely Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure.

Potential Health Effects:

Inhalation: Headaches, dizziness, irritation of respiratory tract, unconsciousness, other central

nervous system effects and breathing problems.

Eyes: Irritation
Skin: Irritation
Ingestion: NA

Carcinogenicity: OSHA: No IARC: No NTP: No

Chronic Overexposure: Repeated overexposures may cause damage to nervous

system – dermatitis.

Medical Conditions Aggravated by Exposure: Pre-existing breathing problems.

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.

Eyes: Flush with large amounts of water for 15 minutes.

Skin: Remove contaminated clothing and wash area with soap and water.

Ingestion: Call a physician. Do not induce vomiting.

Section 5: Fire-Fighting Measures

Product Name: Power Lube ® Multi-Purpose Lubricant

Flashpoint: <20°F Method: TCC LEL: ND UEL: ND

Extinguishing Media: CO₂, dry chemical and foam Hazardous Combustion Products: Thermal – carbon monoxide

Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained

breathing apparatus for fire fighting. Aerosol cans may explode if heated

Product Number (s): 10271

above 120°F.

NFPA: Health: 2 Flammability: 4 Reactivity: 0

HMIS: Health: 2 Flammability: 4 Reactivity: 0 PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.

Aerosol Level: III

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State: Liquid Appearance & Odor: Amber, opaque liquid, oil of

wintergreen odor

Specific Gravity: 0.7683 Boiling Point: 138°F (initial)

Freezing Point: ND Vapor Pressure: ND Evaporation Rate: NA Vapor Density (air = 1) > air

pH: NA Solubility: Negligible in water Volatile Organic Compounds %: 68.2 g/L: 492 lbs./gal: 4.1

Section 10: Stability and Reactivity

Stability: Stable Hazardous Polymerization: No

Chemical Incompatibilities: Strong oxidizers.

Materials to Avoid: Strong oxidizers.

Hazardous Decomposition Products: None

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.

Environmental Fate: No data available for biodegradation.

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

Shipping Name: Consumer Commodity

Hazard Class: ORM-D UN Number: NA Packing Group: NA

Label: NA Placard: NA

Special Provisions: NA

•

Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.

SARA Title III: Section 311/312: Acute, Pressure Section 313*: n-Hexane

CERCLA/Superfund (RQ): Mixture Extremely Hazardous Substances: No

California Prop 65: This product contains chemicals known to the State of

California to cause cancer, birth defects and other

reproductive harm.

* See section 2 for percentage

Section 16: Additional Information

Prepared By: Adam M. Selisker Date: March 13, 2002

Technical Information: 800-521-3168 CRC# 494B

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service Not Applicable NA: Parts per Million ND: Not Determined ppm: Tag Closed Cup Not Established NE: TCC: Lower Explosive Limit LEL: g/L: grams per Liter Upper Explosive Limit pounds per gallon UEL: lbs./gal: PPE: Personal Protection Equipment RQ: Reportable Quantity

COC: Cleveland Closed Cup