

MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Fiber Optic Wire Pulling Lube
Product Number (s): 14135

Manufactured By: CRC Industries, Inc. (215) 674-4300
885 Louis Drive, Warminster, PA 18974
24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Methanol	67-56-1	200 ppm	200 ppm	NE	< 4
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm	NE	< 10
Polytetrafluoroethylene	9002-84-0	NE	NE	NE	< 10
Water	7732-18-5	NE	NE	NE	> 90

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Translucent white, gelatinous liquid.

Danger: Harmful or Fatal if Swallowed.

Potential Health Effects:

Inhalation: NA
Eyes: NA
Skin: Minor dermatitis if sensitive
Ingestion: NA

Carcinogenicity: OSHA: No IARC: No NTP: No
Chronic Overexposure: NA
Medical Conditions Aggravated by Exposure: NA

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.
Eyes: Flush with large amounts of water for 15 minutes.
Skin: Remove contaminated clothing and wash area with soap and water.
Ingestion: Note: low oral toxicity.

--

Section 5: Fire-Fighting Measures

Flashpoint: None Method: COC LEL: ND UEL: ND
Extinguishing Media: None required
Hazardous Combustion Products: Hydrogen fluoride
Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting.

NFPA: Health: 1 Flammability: 0 Reactivity: 0
HMIS: Health: 1 Flammability: 0 Reactivity: 0 PPE: B

--

Section 6: Accidental Release Measures

Spill/Leak Procedures: Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

--

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area.

--

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

--

Section 9: Physical & Chemical Properties

Physical State:	Liquid	Appearance & Odor:	Translucent white, gelatinous liquid
Specific Gravity:	0.9940	Boiling Point:	210°F
Freezing Point:	23 °F	Vapor Pressure:	ND
Evaporation Rate:	NA	Vapor Density (air = 1)	ND
pH:	7.8	Solubility:	Soluble in water
Volatile Organic Compounds %:	5.9	g/L: 58.706	lbs./gal: 0.490

Section 10: Stability and Reactivity

Stability:	Stable	Hazardous Polymerization:	No
Chemical Incompatibilities:	Strong oxidizers.		
Materials to Avoid:	NA		
Hazardous Decomposition Products:	None		

--

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

--

Section 12: Ecological Information

Ecotoxicity:	No data available.
Environmental Fate:	No data available for biodegradation.

--

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

--

Section 14: Transportation Information

Shipping Name:	Not Regulated		
Hazard Class:	NA	UN Number:	NA
Label:	NA	Placard:	NA
Special Provisions:	NA	Packing Group:	NA

--

Section 15: Regulatory Information

TSCA:	All components are either listed under TSCA or are exempt.		
SARA Title III:	Section 311/312:	Acute	Section 313*: Methanol
CERCLA/Superfund (RQ):		Mixture	
Extremely Hazardous Substances:		No	
California Prop 65:		No	

* See section 2 for percentage

--

Section 16: Additional Information

Prepared By:	Adam M. Selisker	Date:	January 21, 2003
Technical Information:	(800) 521-3168	CRC #:	455

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service
ppm: Parts per Million
TCC: Tag Closed Cup
LEL: Lower Explosive Limit
UEL: Upper Explosive Limit
PPE: Personal Protection Equipment
COC: Cleveland Closed Cup

NA: Not Applicable
ND: Not Determined
NE: Not Established
g/L: grams per Liter
lbs./gal: pounds per gallon
RQ: Reportable Quantity