



SAFETY DATA SHEET

SECTION 1. Identification of the hazardous chemical substance or mixture and of the supplier or manufacturer

GHS product identifier	Food Grade Penetrating Oil	
Other means of identification		
Product Code	Item# 1750645	
Recommended use of the chemical and restrictions on use		
Recommended use	Machine oil and lubricant	
Recommended restrictions	None known.	
Suppliers details		
Company name	CRC Industrias de Mexico S. de R. L. de C.V.	
Address	Cerrada Canadá 201-H Fraccionamiento Industrial Martel Santa Catarina, NL 66367 Mexico	
Telephone	General Information	81-2139-0572
Website	www.crc-mexico.com	
E-mail	SoporteTecnico@crcind.com	
Emergency phone number	24-Hour Emergency	01-800-681-9531

SECTION 2: Hazard identification

Classification of the substance or mixture

Physical hazards	Aerosols	Category 2
Health hazards	Acute toxicity, dermal	Category 5
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	

GHS label elements, including precautionary statements



Signal word Danger

Hazard statement

H223	Flammable aerosol.
H229	Pressurized container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.

Precautionary statement

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P312	Call a POISON CENTER/doctor if you feel unwell.

Storage

P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards which do not result in classification	None known.
Supplemental information	None.

SECTION 3. Composition/information on ingredients

Mixtures

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
white mineral oil (petroleum)		8042-47-5	30 - 40
carbon dioxide		124-38-9	1 - 3

Composition comments Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4. First-aid measures

Description of necessary first-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective actions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Flammable aerosol.

SECTION 6. Measures that must be taken in the event of accidental spillage or an accidental leak

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

SECTION 7. Handling and storage**Precautions to ensure safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8. Exposure controls/personal protection**Control parameters****Occupational exposure limits****Mexico. Occupational Exposure Limit Values**

Components	Type	Value
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	5000 ppm
	TWA	200 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
white mineral oil (petroleum) (CAS 8042-47-5)	TWA	5000 ppm	
	TWA	5 mg/m3	Inhalable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Mexico OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

Control banding approach

Not available.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Hazardous Chemicals (NOM-028-STPS-2012, System for administration of workplace safety in the process and critical equipment for handling hazardous chemicals, Appendix A, Table A.I, 9/6/2012)

distillates (petroleum), hydrotreated light (CAS 64742-47-8) 4600 KG

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear protective gloves such as: Neoprene. Nitrile.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Clear.
Odor	Odorless.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-56.2 °F (-49 °C) estimated
Initial boiling point and boiling range	424.4 °F (218 °C) estimated
Flash point	200 °F (93.3 °C) Setaflash
Evaporation rate	Very slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	5.5 % estimated
Vapor pressure	1444.8 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.83 estimated
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	428 °F (220 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Molecular weight	Not available.
Other information	
Percent volatile	97.5 % estimated

SECTION 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.

SECTION 11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May be harmful in contact with skin.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

Delayed and immediate effects and also chronic effects from short and long term exposure

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. May be harmful in contact with skin.

Product	Species	Test Results
Food Grade Penetrating Oil		

Acute

Dermal

ATEmix

2051.8292 mg/kg

Components	Species	Test Results
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Inhalation

LC50

Rat

> 20 mg/l, 4 hours

Oral

LD50

Rat

> 5000 mg/kg

white mineral oil (petroleum) (CAS 8042-47-5)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Oral

LD50

Rat

> 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

white mineral oil (petroleum) (CAS 8042-47-5)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

white mineral oil (petroleum) (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Other information	Not available.

SECTION 12. Ecotoxicological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex)
		2.7 - 5.1 mg/l, 48 hours
white mineral oil (petroleum) (CAS 8042-47-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fish
		> 10000 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
white mineral oil (petroleum)		> 4, log Pow
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

SECTION 13. Disposal considerations

Disposal methods

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. Transport information


SCT

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.


DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None

Packaging bulk	None
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.
DOT; IMDG; SCT	



IATA



SECTION 15. Regulatory information

Safety, health and environmental regulations specific for the product in question

Mexico. Hazard identification guidance list (NOM-018-STPS)

carbon dioxide (CAS 124-38-9)	Listed.
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Listed.
white mineral oil (petroleum) (CAS 8042-47-5)	Listed.

Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)

carbon dioxide (CAS 124-38-9) 100000 KG

International regulations**Montreal Protocol**

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

carbon dioxide (CAS 124-38-9) Listed.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Toxic Chemical Substances (TCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16. Other included information relevant to the preparation and updating of safety data sheets**Issue date** 06-12-2018**Version #** 01**List of abbreviations**

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 SCT: Secretariat of Communications and Transportation (NOM-002-SCT/2011).
 DOT: Department of Transportation (49 CFR 172.101).
 ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
 IATA: International Air Transport Association.
 IMDG Code: International Maritime Dangerous Goods Code.
 MARPOL: International Convention for the Prevention of Pollution from Ships.
 IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

References

NOM-010-STPS-2014 (second revision) – Occupational Exposure Limits – becomes effective on April 28, 2016
 NOM-018-STPS-2000 – Workplace Hazardous Chemical Substances Communication and Identification Standard
 NOM-028-STPS-2012 – Work-Safety Management System for Processes and Critical Equipment Handling Hazardous Chemical Substances
 Workplace Threshold Quantities of Hazardous Chemicals
 NOM-047-SSA1-2011 – Workplace Biological Exposure Indices (BEIs) to Chemical Substances

Further information

CRC # 555C/1002575

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industrias de Mexico S. de R. L. de C.V..