



# SAFETY DATA SHEET

## SECTION 1. Identification of the hazardous chemical substance or mixture and of the supplier or manufacturer

<b>Name of the hazardous chemical substance or mixture</b>	Copper Coat Gasket Compound - 118 mL	
<b>Other means of identification</b>		
Product Code	Item# 1751357	
<b>Recommended use of the hazardous chemical substance or mixture, and restrictions of use</b>		
Recommended use	Gasket compound	
Recommended restrictions	None known.	
<b>Suppliers details</b>		
Company name	CRC Industrias de Mexico S. de R. L. de C.V.	
Address	Cerrada Canadá 201-H Fraccionamiento Industrial Martel Santa Catarina, NL 66367 Mexico	
Telephone	General Information	81-2139-0572
Website	www.crc-mexico.com	
E-mail	SoporteTecnico@crcind.com	
<b>Emergency phone number</b>	24-Hour Emergency	01-800-681-9531

## SECTION 2. Hazard identification

### Classification of the substance or mixture

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Acute toxicity, dermal	Category 5
	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

### Elements of labeling, including precautionary statements and warning pictograms



**Signal word** Danger

#### Hazard statement

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Precautionary statement

##### Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.

P243	Take action to prevent static discharges.
P264	Wash thoroughly after handling.
P261	Avoid breathing vapors.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Response**

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

**Storage**

P235	Keep cool.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

**Disposal**

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Other hazards which do not result in classification** None known.

**Supplemental information** None.

**SECTION 3. Composition/information on ingredients****Mixtures**

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
naphtha (petroleum), hydrotreated light		64742-49-0	30 - 40
heptane, branched, cyclic and linear		426260-76-6	10 - 20
n-heptane		142-82-5	5 - 10
resin acids and rosin acids, hydrogenated, esters with glycerol		65997-13-9	5 - 10
solvent naphtha (petroleum), light aliph.		64742-89-8	5 - 10
2-methylhexane		591-76-4	1 - 3
3-methylhexane		589-34-4	1 - 3
copper		7440-50-8	1 - 3
methylcyclohexane		108-87-2	1 - 3
talca (not containing asbestos fibers)		14807-96-6	< 1
resin acids and rosin acids, potassium salts		61790-50-9	< 0.3

**Composition comments** Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## SECTION 4. First-aid measures

### Description of necessary first-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## SECTION 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective actions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## SECTION 6. Measures that must be taken in the event of accidental spillage or an accidental leak

### Personal precautionary measures, protective equipment and emergency procedure

<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>For emergency responders</b>	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
<b>Methods and materials for containing and cleaning up spills or releases</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

## SECTION 7. Handling and storage

**Precautions for safe handling** Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## SECTION 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

##### Mexico. Occupational Exposure Limit Values

Components	Type	Value	Form
copper (CAS 7440-50-8)	TWA	1 mg/m <sup>3</sup>	Dust and mist.
		0.2 mg/m <sup>3</sup>	Fume.
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
talca (not containing asbestos fibers) (CAS 14807-96-6)	STEL	2 mg/m <sup>3</sup>	Respirable fraction.

##### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-methylhexane (CAS 591-76-4)	STEL	500 ppm	
	TWA	400 ppm	
3-methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	
copper (CAS 7440-50-8)	TWA	1 mg/m <sup>3</sup>	Dust and mist.
		0.2 mg/m <sup>3</sup>	Fume.
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
talca (not containing asbestos fibers) (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Control banding approach** Not available.

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Hazardous Chemicals (NOM-028-STPS-2012, System for administration of workplace safety in the process and critical equipment for handling hazardous chemicals, Appendix A, Table A.I, 9/6/2012)**

n-heptane (CAS 142-82-5) 4600 KG

#### Individual protection measures, such as personal protective equipment (PPE)

**Eye/face protection** Wear safety glasses with side shields (or goggles).

<b>Skin protection</b>	
<b>Hand protection</b>	Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.
<b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## SECTION 9. Physical and chemical properties

<b>Appearance</b>	
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Copper.
<b>Odor</b>	Hydrocarbon-like.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-195.9 °F (-126.6 °C) estimated
<b>Initial boiling point and boiling range</b>	190.4 °F (88 °C) estimated
<b>Flash point</b>	30 °F (-1.1 °C) Setaflash
<b>Evaporation rate</b>	Moderate.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.1 % estimated
<b>Flammability limit - upper (%)</b>	6.7 % estimated
<b>Vapor pressure</b>	56.5 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.76
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	539.6 °F (282 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Molecular weight</b>	Not available.
<b>Other information</b>	
<b>Percent volatile</b>	74.5 % estimated

---

## SECTION 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions that must be avoided</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.

**Hazardous decomposition products** Carbon oxides. Aldehydes. Carboxylic acids. Formaldehyde. Ketones.

## SECTION 11. Toxicological information

### Information about likely routes of entry

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	May be harmful in contact with skin. Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Numerical measures of toxicity (such as acute toxicity estimates)

**Acute toxicity** May be fatal if swallowed and enters airways. In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and central nervous system effects. May be harmful in contact with skin.

Components	Species	Test Results
3-methylhexane (CAS 589-34-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
heptane, branched, cyclic and linear (CAS 426260-76-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 60 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
methylcyclohexane (CAS 108-87-2)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 4000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	61 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
n-heptane (CAS 142-82-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	3000 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	25000 mg/kg
resin acids and rosin acids, potassium salts (CAS 61790-50-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	61 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 3000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory or skin sensitization</b>		
<b>ACGIH sensitization</b>		
ROSIN CORE SOLDER THERMAL DECOMPOSITION PRODUCTS (COLOPHONY) (CAS 65997-13-9)	Dermal sensitization	Respiratory sensitization
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Not classifiable as to carcinogenicity to humans.	
<b>ACGIH Carcinogens</b>		
talca (not containing asbestos fibers) (CAS 14807-96-6)	A4	Not classifiable as a human carcinogen.
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Other information</b>	Not available.	

## SECTION 12. Ecotoxicological information

**Toxicity** Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results
copper (CAS 7440-50-8)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
		0.266 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		0.052 mg/l, 96 hours
heptane, branched, cyclic and linear (CAS 426260-76-6)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
		1.5 mg/l, 48 hours
methylcyclohexane (CAS 108-87-2)		
<b>Aquatic</b>		
Fish	LC50	Striped bass (Morone saxatilis)
		5.8 mg/l, 96 hours
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia
		1 - 10 mg/l, 48 hours
Fish	LC50	Fish
		1 - 10 mg/l, 96 hours
n-heptane (CAS 142-82-5)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
		1.5 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)
		2.1 - 2.98 mg/l, 96 hours
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
<b>Aquatic</b>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
		1.5 mg/l, 48 hours
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.	
<b>Bioaccumulative potential</b>		
<b>Partition coefficient n-octanol / water (log Kow)</b>		
methylcyclohexane		3.61
n-heptane		4.66
<b>Bioconcentration factor (BCF)</b>		
naphtha (petroleum), hydrotreated light		10 - 25000
<b>Mobility in soil</b>	No data available.	
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

## SECTION 13. Disposal considerations



### Disposal methods

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



## SECTION 14. Transport information

<b>SCT</b>	
<b>UN number</b>	UN1993
<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (heptanes, methylcyclohexane), Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Bulk special provisions</b>	274
<b>DOT</b>	
<b>UN number</b>	UN1993
<b>Proper shipping name</b>	Flammable liquids, n.o.s. (heptanes, methylcyclohexane RQ = 5370 LBS), Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	IB2, T7, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	202
<b>Packaging bulk</b>	242
<b>IATA</b>	
<b>UN number</b>	UN1993
<b>Proper shipping name</b>	Flammable liquid, n.o.s. (heptanes, methylcyclohexane), Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>ERG Code</b>	3H
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.
<b>IMDG</b>	
<b>UN number</b>	UN1993
<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (heptanes, methylcyclohexane), Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes, but exempt from the regulations.
<b>EmS</b>	F-E, S-E
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not established.

**DOT; IMDG; SCT****IATA****SECTION 15. Regulatory information****Safety, health and environmental regulations specific for the hazard chemical substance or mixture in question****Mexico. Hazard identification guidance list (NOM-018-STPS)**

2-methylhexane (CAS 591-76-4)	Listed.
3-methylhexane (CAS 589-34-4)	Listed.
copper (CAS 7440-50-8)	Listed.
methylcyclohexane (CAS 108-87-2)	Listed.
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
n-heptane (CAS 142-82-5)	Listed.
resin acids and rosin acids, hydrogenated, esters with glycerol (CAS 65997-13-9)	Listed.
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	Listed.

**Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)**

Not listed.

**Mexico. Wastewater Discharges - Maximum Limits into Coastal Waters, Dams, Rivers, Soil and Wetlands (NOM-001-ECOL)**

copper (CAS 7440-50-8)	Listed.
------------------------	---------

**International regulations****Montreal Protocol**

Not applicable.

**Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.

**Kyoto protocol**

Not applicable.

**Basel Convention**

Not applicable.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## SECTION 16. Other included information relevant to the preparation and updating of safety data sheets

**Issue date** 03-21-2019

**Version #** 01

### List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

SCT: Secretariat of Communications and Transportation (NOM-002-SCT/2011).

DOT: Department of Transportation (49 CFR 172.101).

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

IATA: International Air Transport Association.

IMDG Code: International Maritime Dangerous Goods Code.

MARPOL: International Convention for the Prevention of Pollution from Ships.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

### References

NOM-010-STPS-2014 (second revision) – Occupational Exposure Limits – becomes effective on April 28, 2016

NOM-018-STPS-2000 – Workplace Hazardous Chemical Substances Communication and Identification Standard

NOM-028-STPS-2012 – Work-Safety Management System for Processes and Critical Equipment Handling Hazardous Chemical Substances

Workplace Threshold Quantities of Hazardous Chemicals

NOM-047-SSA1-2011 – Workplace Biological Exposure Indices (BEIs) to Chemical Substances

### Further information

CRC # 915/1002905

### Disclaimer

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industrias de Mexico S. de R. L. de C.V..