#### MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

**Product Name:** Marking Paints

Product Number (s): 18202(Caution Blue), 18203(Safety Green), 18209(Pink Fluorescent),

18207 (Red Fluorescent), 18208 (Orange Fluorescent), and

18210 (Red/Orange Fluorescent)

Manufactured By: CRC Industries, Inc. (215) 674-4300

885 Louis Drive, Warminster, PA 18974

24-Hour Emergency Information: CHEMTREC (800) 424-9300

\_\_\_\_\_

# Section 2: Composition/Information on Ingredients

| Component         | CAS        | ACGIH                | OSHA                | OTHER                | %     |
|-------------------|------------|----------------------|---------------------|----------------------|-------|
|                   | NUMBER     | TLV                  | PEL                 | LIMITS               |       |
| Calcium Carbonate | 1317-65-3  | $10 \text{ mg/m}^3$  | $15 \text{ mg/m}^3$ | $10 \text{ mg/m}^3$  | 7-13  |
| Xylene            | 1330-20-7  | 100 ppm              | 100 ppm             | 100 ppm              | 1-5   |
| Propane           | 74-98-6    | NE                   | 1000 ppm            | 1000 ppm             | 7-13  |
| Ethylbenzene      | 100-41-4   | 100 ppm              | 100 ppm             | 100 ppm              | 1-5   |
| Isobutane         | 75-28-5    | NE                   | NE                  | 800 ppm              | 10-30 |
| VM&P              | 64742-89-8 | 300 ppm              | NE                  | $350 \text{ mg/m}^3$ | 7-13  |
| Toluene           | 108-88-3   | 50 ppm               | 200 ppm             | 100 ppm              | 5-10  |
| Mineral Spirits   | 64742-47-8 | $200 \text{ mg/m}^3$ | 500 ppm             | NE                   | 1-5   |
|                   |            |                      |                     |                      |       |

\_\_\_\_\_

#### Section 3: Hazards Identification

**Emergency Overview** 

Appearance & Odor: Aromatic odor.

Danger: Extremely Flammable. Eye and skin irritant. Harmful or fatal if swallowed. Vapor Harmful.

Contents under pressure.

Potential Health Effects:

Inhalation: Nasal and respiratory irritation, dizziness, fatigue, headaches, unconsciousness and

asphyxiation.

Eyes: Irritation, tearing and blurred vision.

Skin: Irritation and redness.

Ingestion: GI irritation, nausea and vomiting.

Carcinogenicity: OSHA: No IARC: Yes NTP: No

Chronic Overexposure: Reports have associated repeated and prolonged exposure

to solvents with brain and central nervous system damage.

Medical Conditions Aggravated by Exposure: Respiratory and skin conditions may be aggravated.

\_\_\_\_\_

Product Name: Marking Paints

Product Number (s): 18202(Caution Blue), 18203(Safety Green), 18209(Pink Fluorescent),

18207 (Red Fluorescent), 18208 (Orange Fluorescent), and 18210 (Red/Orange

**Fluorescent**)

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.

Eyes: Flush with large amounts of water for 15 minutes.

Skin: Remove contaminated clothing and wash area with soap and water.

Ingestion: Call a physician. Do not induce vomiting.

.....

Section 5: Fire-Fighting Measures

Flashpoint: >39°F/>4°C (concentrate) Method: TCC LEL: 0.7 UEL: 7

Extinguishing Media: CO<sub>2</sub>, alcohol foam and dry chemical

Hazardous Combustion Products: Thermal: CO, CO<sub>2</sub>, NOX and various hydrocarbons.

Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained

breathing apparatus for fire fighting. Aerosol cans may explode if heated

above 120°F.

NFPA: Health: 2 Flammability: 4 Reactivity: 0

HMIS: Health: 2 Flammability: 4 Reactivity: 0 PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

.-----

Section 7: Handling and Storage

Handling Procedures: Use in a well-ventilated area.

Storage Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans

from exploding. Keep out of reach of children!

------

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Provide local ventilation adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Product Name: Marking Paints

Product Number (s): 18202(Caution Blue), 18203(Safety Green), 18209(Pink Fluorescent),

18207 (Red Fluorescent), 18208 (Orange Fluorescent), and 18210 (Red/Orange

Fluorescent)

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State: Liquid Appearance & Odor: Aromatic odor

Specific Gravity: .985 Boiling Point: 199-313°F (93-156°C)

Freezing Point: Vapor Pressure: ND ND

Evaporation Rate: Slower than ether Vapor Density (air = 1) Heavier than air

pH: NA Solubility: Slight in water.

Volatile Organic Compounds %: 74-75 lbs./gal: g/L: ND ND

Section 10: Stability and Reactivity

Stable Stability: Hazardous Polymerization: No

Chemical Incompatibilities: Strong oxidizers.

Temperature extremes. Conditions to Avoid:

Hazardous Decomposition Products: None

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.

No data available for biodegradation. Environmental Fate:

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental

agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

Shipping Name: **Consumer Commodity** 

Hazard Class: ORM-D UN Number: NA Packing Group: NA

Label: NA Placard: NA

**Special Provisions:** NA Product Name: Marking Paints

Product Number (s): 18202(Caution Blue), 18203(Safety Green), 18209(Pink Fluorescent),

18207 (Red Fluorescent), 18208 (Orange Fluorescent), and 18210 (Red/Orange

**Fluorescent**)

\_\_\_\_\_

## Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.

SARA Title III: Section 311/312: Acute, Pressure

Section 313\*: Xylene, Ethylbenzene, Toluene

CERCLA/Superfund (RQ): Mixture Extremely Hazardous Substances: No

California Prop 65: This product contains chemicals known to the State of

California to cause cancer, birth defects and other

reproductive harm.

\_\_\_\_\_

### Section 16: Additional Information

Prepared By: Michelle Milburn Date: September 3, 2003

Technical Information: (800) 521-3168 CRC #: 18202

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by

CRC to be accurate. Before using any product, read all warnings and directions on the label.

Chemical Abstract Service CAS: NA: Not Applicable Not Determined ppm: Parts per Million ND: Not Established TCC: Tag Closed Cup NE: LEL: Lower Explosive Limit g/L: grams per Liter UEL: Upper Explosive Limit lbs./gal: pounds per gallon PPE: Personal Protection Equipment RQ: Reportable Quantity

COC: Cleveland Closed Cup

<sup>\*</sup> See section 2 for percentage