

# MATERIAL SAFETY DATA SHEET

## Section 1: Product & Company Identification

**Product Name:** Striping & Traffic Paint: White  
**Product Number (s):** 18300

Manufactured By: CRC Industries, Inc. (215) 674-4300  
885 Louis Drive, Warminster, PA 18974  
24-Hour Emergency Information: CHEMTREC (800) 424-9300

---

## Section 2: Composition/Information on Ingredients

Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Toluene	108-88-3	50 ppm	100 ppm	NE	5-13
Acetone	67-64-1	750 ppm	750 ppm	NE	15-40
Xylene	1330-20-7	100 ppm	100 ppm	NE	5-10
Propane	74-98-6	NE	1000 ppm	NE	7-13
Ethylbenzene	100-41-4	100 ppm	100 ppm	NE	1-5
Isobutane	75-28-5	NE	NE	800 ppm	5-10
TiO <sub>2</sub>	13463-67-7	NE	NE	NE	5-10
Magnesium Silicate Hydrate	14807-96-6	2 mg/m <sup>3</sup>	NE	NE	1-5

---

## Section 3: Hazards Identification

### Emergency Overview

Appearance & Odor: Ketone odor.

Danger: Extremely Flammable. Eye and skin irritant. Harmful or fatal if swallowed. Vapor Harmful. Contents under pressure.

### Potential Health Effects:

Inhalation: Nasal and respiratory irritation, dizziness, fatigue, headaches, unconsciousness and asphyxiation.  
Eyes: Irritation, tearing and blurred vision.  
Skin: Irritation and redness.  
Ingestion: GI irritation, nausea and vomiting.

Carcinogenicity: OSHA: No IARC: Yes NTP: No  
Chronic Overexposure: Reports have associated repeated and prolonged exposure to solvents with brain and central nervous system damage.  
Medical Conditions Aggravated by Exposure: Respiratory and skin conditions may be aggravated.

---

## Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.  
Eyes: Flush with large amounts of water for 15 minutes.

Skin: Remove contaminated clothing and wash area with soap and water.

Ingestion: Call a physician. Do not induce vomiting.

### Section 5: Fire-Fighting Measures

Flashpoint: -100°F Method: TCC LEL: 1.0 UEL: ND  
 Extinguishing Media: CO<sub>2</sub>, alcohol foam and dry chemical  
 Hazardous Combustion Products: Thermal: CO, CO<sub>2</sub>, NOX and various hydrocarbons.  
 Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting. Aerosol cans may explode if heated above 120°F.

NFPA:	Health:	2	Flammability:	4	Reactivity:	0
HMIS:	Health:	2	Flammability:	4	Reactivity:	0 PPE: B

### Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

### Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.

### Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

### Section 9: Physical & Chemical Properties

Physical State:	Liquid	Appearance & Odor:	Ketone odor.
Specific Gravity:	> 1 (water =1)	Boiling Point:	134°F-289°F
Freezing Point:	ND	Vapor Pressure:	ND
Evaporation Rate:	Slower than ether	Vapor Density (air = 1)	Heavier than air
pH:	NA	Solubility:	Slight in water.

  

Volatile Organic Compounds:%:	41-43	g/L:	ND	lbs./gal:	ND
-------------------------------	-------	------	----	-----------	----

### Section 10: Stability and Reactivity

Stability:	Stable	Hazardous Polymerization:	No
Chemical Incompatibilities:	Strong oxidizers.		
Materials to Avoid:	Strong oxidizers.		

Hazardous Decomposition Products: None

-----  
Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

-----  
Section 12: Ecological Information

Ecotoxicity: No data available.  
Environmental Fate: No data available for biodegradation.

-----  
Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

-----  
Section 14: Transportation Information

Shipping Name: Consumer Commodity  
Hazard Class: ORM-D UN Number: NA Packing Group: NA  
Label: NA Placard: NA  
Special Provisions: NA

-----  
Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.  
SARA Title III: Section 311/312: Acute, Pressure  
Section 313\*: Xylene, Toluene, Ethylbenzene  
CERCLA/Superfund (RQ): Mixture  
Extremely Hazardous Substances: No  
California Prop 65: This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

\* See section 2 for percentage

-----  
Section 16: Additional Information

Prepared By: Adam M. Selisker Date: June 5, 2007  
Technical Information: (800) 521-3168 CRC #: 18300

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable  
ppm: Parts per Million ND: Not Determined  
TCC: Tag Closed Cup NE: Not Established  
LEL: Lower Explosive Limit g/L: grams per Liter  
UEL: Upper Explosive Limit lbs./gal: pounds per gallon  
PPE: Personal Protection Equipment RQ: Reportable Quantity  
COC: Cleveland Closed Cup