



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Chain and Wire Rope Lubricant

**Other means of identification**

**Product code** 03052, 03053

**Recommended use** Lubricant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency** 800-424-9300 (US)

**(CHEMTREC)** 703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Serious eye damage/eye irritation	Category 2B
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe the mist or vapor. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Avoid release to the environment.

**Response**

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national regulations.

**Hazard(s) not otherwise classified (HNOC)**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information**

96.23% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**3. Composition/information on ingredients****Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), hydrotreated light		64742-49-0	80 - 90
Acrylic copolymer		Proprietary	5 - 10
n-Hexane		110-54-3	3 - 5
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		72623-86-0	1 - 3
White mineral oil		8042-47-5	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**4. First-aid measures****Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**Skin contact**

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion**

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

**Most important symptoms/effects, acute and delayed**

Exposed individuals may experience eye tearing, redness, and discomfort. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged exposure may cause chronic effects.

**Indication of immediate medical attention and special treatment needed**

Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information**

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

**5. Fire-fighting measures****Suitable extinguishing media**

Water spray. Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable extinguishing media**

Water. Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical**

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire-fighting equipment/instructions**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**General fire hazards**

Highly flammable liquid and vapor.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe the mist or vapor. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

**7. Handling and storage**

**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

For product usage instructions, please see the product label.

**Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers. Keep out of the reach of children.

**8. Exposure controls/personal protection**

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3 500 ppm	
White mineral oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
White mineral oil (CAS 8042-47-5)	STEL	50 ppm	Mist.
	TWA	10 mg/m3	Mist.
		5 mg/m3	Mist.

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton rubber (fluor rubber).

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

**Physical state** Liquid.

**Form** Liquid.

**Color** Green.

**Odor** Mild solvent.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -137.7 °F (-94.3 °C) estimated

**Initial boiling point and boiling range** 118.4 °F (48 °C) estimated

**Flash point** < 0 °F (< -17.8 °C) Tag Closed Cup

**Evaporation rate** Very fast.

**Flammability (solid, gas)** Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 1 % estimated

<b>Flammability limit - upper (%)</b>	8 % estimated
<b>Vapor pressure</b>	270.7 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.68
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	437 °F (225 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity (kinematic)</b>	Not available.
<b>Percent volatile</b>	89 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Chlorine.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	Harmful if swallowed. May be fatal if swallowed and enters airways.
<b>Inhalation</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause damage to organs by inhalation.
<b>Skin contact</b>	Prolonged skin contact may cause temporary irritation.
<b>Eye contact</b>	Causes eye irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Exposed individuals may experience eye tearing, redness, and discomfort. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Prolonged or excessive inhalation may cause respiratory tract irritation.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
Chain and Wire Rope Lubricant		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	12367.4834 mg/kg estimated
<i>Oral</i>		
LD50	Rat	1713.4238 mg/kg estimated

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Causes eye irritation.
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
White mineral oil (CAS 8042-47-5)	3 Not classifiable as to carcinogenicity to humans.
<b>Reproductive toxicity</b>	Suspected of damaging fertility.
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.

<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
Chain and Wire Rope Lubricant		
Fish	LC50	Fish
		1175.6997 mg/l, 96 hours estimated
Components	Species	Test Results
n-Hexane (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas)
		2.101 - 2.981 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**  
n-Hexane 3.9

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal of waste from residues / unused products** This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

### DOT

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	Flammable liquids, n.o.s. (Hydrotreated light naphtha, n-Hexane RQ = 5000 lbs)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	IB2, T7, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	202
<b>Packaging bulk</b>	242

### IATA

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	Flammable liquid, n.o.s. (Hydrotreated light naphtha, n-Hexane)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3H
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed.

<b>Cargo aircraft only</b>	Allowed.
<b>IMDG</b>	
<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (Hydrotreated light naphtha, n-Hexane)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-E
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

## 15. Regulatory information

<b>US federal regulations</b>	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>	Not regulated.
<b>SARA 304 Emergency release notification</b>	Not regulated.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	Not listed.
<b>US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance</b>	n-Hexane (CAS 110-54-3)
<b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>	n-Hexane (CAS 110-54-3)
<b>CERCLA Hazardous Substances: Reportable quantity</b>	n-Hexane (CAS 110-54-3) 5000 lbs
	Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.
<b>Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List</b>	n-Hexane (CAS 110-54-3)
<b>Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)</b>	Not regulated.
<b>Safe Drinking Water Act (SDWA)</b>	Not regulated.
<b>Food and Drug Administration (FDA)</b>	Not regulated.
<b>Superfund Amendments and Reauthorization Act of 1986 (SARA)</b>	
<b>Section 311/312</b>	Immediate Hazard - Yes
<b>Hazard categories</b>	Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
<b>SARA 302 Extremely hazardous substance</b>	No
<b>US state regulations</b>	
<b>US. New Jersey RTK - Substances: Listed substance</b>	n-Hexane (CAS 110-54-3)
<b>US. Massachusetts RTK - Substance List</b>	n-Hexane (CAS 110-54-3) White mineral oil (CAS 8042-47-5)
<b>US. Pennsylvania RTK - Hazardous Substances</b>	n-Hexane (CAS 110-54-3) White mineral oil (CAS 8042-47-5)
<b>US. Rhode Island RTK</b>	n-Hexane (CAS 110-54-3)
<b>US. California Proposition 65</b>	California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

## Volatile organic compounds (VOC) regulations

### EPA

**VOC content (40 CFR 51.100(s))** 89 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

### State

**Consumer products** This product is regulated as a Gear, Chain or Wire Lubricant (non-aerosol). This product is not compliant to be sold for use in California. This product is compliant in all other states.

**VOC content (CA)** 89 %

**VOC content (OTC)** 89 %

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

---

**Issue date** 12-27-2013

**Prepared by** Allison Cho

**Version #** 01

**Further information** CRC # 572B-E

**HMIS® ratings** Health: 2\*  
Flammability: 3  
Physical hazard: 0  
Personal protection: B

**NFPA ratings** Health: 2  
Flammability: 3  
Instability: 0

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.