

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Plexalube[™] Extreme Duty #2 Grease

Product Number (s): SL35354

Manufactured By:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

General Information
Technical Assistance
(800) 521-3168
Customer Service
(800) 272-8963
24-Hr Emergency (CHEMTREC)
(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Red grease, mild petroleum odor

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE: Slightly irritating.

SKIN: Repeated or prolonged contact can result in drying of the skin.

INHALATION: Heating can generate vapors that may cause respiratory irritation, nausea and

headaches. Inhalation hazard at room temperature is unlikely due to the low

volatility of this product.

INGESTION: Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into

the lungs and subsequent pneumonitis.

CHRONIC EFFECTS: None known.

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure:

None known.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Plexalube[™] Extreme Duty #2 Grease Product Number (s): SL35354

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hydrotreated heavy naphthenic distillates	64742-52-5	60 – 80
Solvent-dewaxed petroleum oils	64742-62-7 / 64742-65-0	10 – 30
Aluminum complex thickener	proprietary	5 – 10
Antimony dialkyldithiocarbamate	proprietary	0.5 – 1.5

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician

if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting! Get medical attention immediately.

Note to Physicians: None

Section 5: Fire-Fighting Measures

<u>Flammable Properties</u>: As defined by OSHA, this product is nonflammable.

Flash Point: 224 C (COC) Upper Explosive Limit: ND Autoignition Temperature: ND Lower Explosive Limit: ND

Suitable Extinguishing Media: Carbon dioxide, dry chemical, sand, dolomite, alcohol resistant foam, water spray, fog

or mist.

Products of Combustion: Acrid smoke/fumes, oxides of carbon and sulfur.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye

and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product

decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Product Name: Plexalube[™] Extreme Duty #2 Grease

Product Number (s): SL35354

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Keep sources of ignition away from spill. Ventilate the area with fresh air. If

in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into

proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from sparks and open flame. Ventilate well and avoid breathing vapors. Keep

container closed when not in use.

Storage Procedures: Store in a cool dry area out of direct sunlight. Store away from strong acids and oxidizers.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	05	SHA	AC	GIH	0	THER	
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Hydrotreated heavy naphthenic distillates	5*	NE	5*	10*	NE		mg/m ³
Solvent-dewaxed petroleum oils	5*	NE	5*	10*	NE		mg/m ³
Aluminum complex thickener	NE	NE	NE	NE	NE		
Antimony dialkyldithiocarbamate	0.5	NE	0.5	NE	NE		mg/m ³
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

^{*}exposure value for respirable oil mist

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation

of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure

guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a NIOSH-

approved cartridge respirator with organic vapor cartridge if vapors exceed exposure limits.

Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or PVC. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: grease

Color: red

Product Name: Plexalube[™] Extreme Duty #2 Grease

Odor: mild petroleum odor Specific Gravity: 0.90 Initial Boiling Point: ND Freezing Point: ND

Vapor Pressure: < 0.5 mmHg @ 20C Vapor Density: ND (air = 1) Evaporation Rate: < 0.01 (ether = 1)

Solubility: Insoluble in water

pH: NA

Volatile Organic Compounds: wt %: < 0.1% g/L: < 1 lbs./gal: < 0.01

Product Number (s): SL35354

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition.

Incompatible Materials: Acids and oxidizing substances.

Hazardous Decomposition Products: Oxides of carbon.

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

Component	<u>Test</u>	<u>Result</u>	Route	<u>Species</u>
Hydrotreated heavy naphthenic distillates	LD50	> 5000 mg/kg	Oral	Rat
Hydrotreated heavy LD50 naphthenic distillates	LD50	> 2000 mg/kg	Dermal	Rabbit

CHRONIC EFFECTS

Carcinogenicity:

Component Result

OSHA: None listed IARC: None listed NTP: None listed

Mutagenicity: No information

Other: None

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Product Name: Plexalube[™] Extreme Duty #2 Grease

Ecotoxicity: No information.

Persistence / Degradability: No information.

Bioaccumulation / Accumulation: No information.

Mobility in Environment: No information.

Section 13: Disposal Considerations

Disposal: This material is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Product Number (s): SL35354

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Not regulated

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Antimony compounds (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No

Reactive Hazard No
Release of Pressure No
Acute Health Hazard No
Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting

requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

antimony compounds (max 1.5%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Product Name: Plexalube[™] Extreme Duty #2 Grease Product Number (s): SL35354

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: NJRTK#'s 28235 & 20630 Pennsylvania: Antimony compounds

Massachusetts: None Rhode Island: None

Additional Regulatory Information: None

Section 16: Other Information

NFPA: Health: 1 Flammability: 1 Reactivity: 0

HMIS: Health: 1 Flammability: 1 Reactivity: 0 PPE: X

Prepared By: Michelle Rudnick

CRC #: SL35354 Revision Date: 3/16/2006

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable Parts per Million ND: Not Determined ppm: TCC: Tag Closed Cup NE: Not Established Pensky-Martens Closed Cup PMCC: grams per Liter g/L: PPE: Personal Protection Equipment lbs./gal: pounds per gallon

TWA: Time Weighted Average STEL: Short Term Exposure Limit OSHA: Occupational Safety and Health Administration COC: Cleveland Open Cup

ACGIH American Conference of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety & Health