



Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Mass Air Flow Sensor Cleaner (Aerosol)

Product Number (s): 05110

Manufactured By:

CRC Industries, Inc.
885 Louis Drive
Warminster, PA 18974
www.crcindustries.com

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-8963
24-Hr Emergency (CHEMTREC)	(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Clear, colorless liquid with alcohol odor

DANGER

Extremely flammable. Harmful or fatal if swallowed. Contents under pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

- EYE:** May cause mild irritation including stinging and redness, but does not injure eye.
- SKIN:** Single, brief exposures may cause mild irritation. Frequent or prolonged contact may cause more severe irritation, defatting of the skin, and dermatitis.
- INHALATION:** High vapor concentrations are irritating to the respiratory tract and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.
- INGESTION:** Low order of toxicity by ingestion. Main hazard is aspiration into the lungs during swallowing or vomiting. Small amounts aspirated into the respiratory system may cause bronchopneumonia or pulmonary edema, possibly progressing to death.
- CHRONIC EFFECTS:** Overexposure to n-hexane may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs.
- TARGET ORGANS:** central nervous system, peripheral nervous system, respiratory system

Medical Conditions Aggravated by Exposure: skin and respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hexane isomers	various	75 - 85
n-Hexane	110-54-3	6.1
COzol® 204	Proprietary	5 - 10
Carbon dioxide	124-38-9	3 - 8

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** DO NOT induce vomiting. Contact a physician immediately.
- Note to Physicians:* Treat symptomatically. Gastric lavage using a cuffed endotracheal tube may be performed at your discretion.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6)).

Flash Point:	< 0 F (TCC)	Upper Explosive Limit:	9.0
Autoignition Temperature:	489 F	Lower Explosive Limit:	1.7

Suitable Extinguishing Media: Class B fire extinguishers, dry chemical, foam or CO2

Products of Combustion: fumes, smoke and carbon monoxide

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water fog or spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Do not spray water directly on fire; product will float and could be reignited on surface of water.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Use proper grounding and bonding procedures for transferring materials. Do not use product near any source of ignition. Do not touch container to electrical sources as container will conduct electricity. Avoid contact with eyes and skin. Avoid breathing vapors.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Hexane isomers	500(v)	1000(v)	500	1000	NE		ppm
n-Hexane	500	NE	50(s)	NE	NE		ppm
COzol® 204	200	250 (v)	200	250	NE		ppm
Carbon dioxide	5000	30000(v)	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a NIOSH-approved cartridge respirator with an organic vapor cartridge if vapors exceed exposure limits. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVC or Viton. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid
Color: clear, colorless

Odor: alcohol
 Specific Gravity: 0.6699
 Initial Boiling Point: 140 F
 Freezing Point: < -76 F
 Vapor Pressure: 160 mmHg @ 68 F
 Vapor Density: > 1 (air = 1)
 Evaporation Rate: 9 (Butyl acetate = 1)
 Solubility: negligible in water
 pH: NA
 Volatile Organic Compounds: wt %: 95 g/L: 636.4 lbs./gal: 5.3

Section 10: Stability and Reactivity

Stability: Stable
 Conditions to Avoid: sources of ignition, temperature extremes
 Incompatible Materials: strong oxidizers
 Hazardous Decomposition Products: oxides of carbon
 Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
n-hexane	LD50	28710 mg/kg	Oral	Rat
n-hexane	LD50	3000 mg/kg	Dermal	Rabbit
n-hexane	LC50	48000 ppm/4H	Inhalation	Rat

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	None listed	
IARC:	None listed	
NTP:	None listed	

Mutagenicity: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	n-hexane - 48 Hr EC50 water flea: 3.87 mg/L 96 Hr LC50 Lepomis macrochirus: 4.12 mg/L
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	No information available

Section 13: Disposal Considerations

Disposal: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001 (See 40 CFR Part 261.20 – 261.33).
Aerosol containers should be emptied and depressurized before disposal. Empty containers may be recycled. Any liquid product should be managed as a hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

Section 15: Regulatory Information**U.S. Federal**Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: n-hexane (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
n-hexane (6.1%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): n-hexane

State RegulationsCalifornia Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: 75-83-2, 110-54-3, 79-29-8, 124-38-9
 Pennsylvania: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 67-56-1, 124-38-9
 Massachusetts: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 124-38-9
 Rhode Island : 110-54-3, 124-38-9

Additional Regulatory Information: None

Section 16: Other Information

NFPA:	Health: 2	Flammability: 3	Reactivity: 0	
HMIS:	Health: 2	Flammability: 3	Reactivity: 0	PPE: B

Prepared By: Michelle Rudnick
 CRC #: 599C
 Revision Date: 12/06/2007

Changes since last revision: Correction made to Evaporation Rate

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		



Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Throttle Body and Air Intake Cleaner (aerosol)

Product Number (s): 05078, 05078-6

Manufactured By:

CRC Industries, Inc.
885 Louis Drive
Warminster, PA 18974
www.crcindustries.com

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-4620
24-Hr Emergency (CHEMTREC)	(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Pale yellow to clear liquid; aromatic odor

DANGER

Extremely Flammable. Harmful or Fatal if Swallowed. Vapor Harmful. Eye and Skin Irritant.
Contents Under Pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

- EYE:** Moderate eye irritant. Exposure can cause irritation including stinging, tearing, redness, blurred vision, and swelling of the eyes.
- SKIN:** Moderate skin irritant. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of the skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.
- INHALATION:** Breathing large amounts of this material may be harmful. Symptoms include irritation of the nose and throat and central nervous system depression (dizziness, drowsiness, weakness, headache, nausea, unconsciousness).
- INGESTION:** Swallowing small amounts is not likely to cause harmful effects. Swallowing larger amounts may be harmful as this material may be aspirated into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.
- CHRONIC EFFECTS:** Unknown
- TARGET ORGANS:** liver, kidneys, blood, central nervous system
- Medical Conditions Aggravated by Exposure:** skin sensitivities, lung conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Acetone	67-64-1	50 - 60
Toluene	108-88-3	5 - 15
Xylene	1330-20-7	5 – 10
Ethylbenzene	100-41-4	2.2
Methanol	67-56-1	< 2
Diacetone alcohol	123-42-2	< 2
Liquefied petroleum gas	68476-86-8	15 - 25

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Seek medical attention. Do not induce vomiting unless instructed by medical personnel. Have victim drink a glass of water if conscious.

Note to Physicians: This material is an aspiration hazard. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Inhalation of high concentrations of this material may be associated with cardiac arrhythmias.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6)).

Flash Point:	< 0 F (TCC)	Upper Explosive Limit:	12.8
Autoignition Temperature:	869 F	Lower Explosive Limit:	2.6

Suitable Extinguishing Media: dry chemical, carbon dioxide, alcohol-resistant foam, class B extinguishers

Products of Combustion: oxides of carbon

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Vapors are heavier than air and will accumulate near the ground. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Eliminate sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use near potential sources of ignition. Do not use on energized equipment. Use with adequate ventilation. Avoid contact with skin and eyes. Avoid inhaling vapors.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Acetone	1000	NE	500	750	NE		ppm
Toluene	200	300 (c)	20	NE	NE		ppm
Xylene	100	NE	100	150	NE		ppm
Ethylbenzene	100	NE	100	125	NE		ppm
Methanol	200	NE	200	250 (s)	NE		ppm
Diacetone alcohol	50	NE	50	NE	NE		ppm
Liquefied petroleum gas	1000	NE	1000	NE	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVA, or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid

Color: pale yellow to clear

Odor: aromatic

Specific Gravity: 0.8151

Initial Boiling Point: 132 F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: > 1 (butyl acetate = 1)

Solubility: slightly soluble in water

pH: NA

Volatile Organic Compounds: wt %: 44.6 g/L: 363.5 lbs./gal: 3.03

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition; temperature extremes

Incompatible Materials: Acids, alkalis, reducing agents, strong oxidizing agents

Hazardous Decomposition Products: Oxides of carbon, various hydrocarbons

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Acetone	LD50	5800 mg/kg	Oral	Rat
Acetone	LC50	16,000 ppm/4H	Inhalation	Rat
Acetone	LD50	20,000 mg/kg	Dermal	Rabbit
Xylene	LD50	3400 mg/kg	Oral	Rat
Xylene	LC50	5000 ppm/4H	Inhalation	Rat

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	None listed	
IARC:	Ethylbenzene	Group 2B – Possibly carcinogenic to humans
NTP:	None listed	

Mutagenicity: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Acetone – 48H LC50 Daphnia: 10 mg/l
Persistence / Degradability: No information available
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Disposal: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with the following potential waste code(s): D001, F003, F005 (See 40 CFR Part 261.20 – 261.33). Aerosol containers should be fully emptied and depressurized before disposal.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Acetone (5000 lbs), Toluene (1000 lbs), Methanol (5000 lbs), Xylene (100 lbs), Ethylbenzene (1000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes
Reactive Hazard No
Release of Pressure Yes

Acute Health Hazard	Yes
Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
Toluene (10%), Methanol (< 2%), Xylene (< 10%), Ethylbenzene (2.2%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Toluene, Methanol, Xylene, Ethylbenzene

State RegulationsCalifornia Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: Toluene, Ethylbenzene

State Right to Know:

New Jersey: 67-64-1, 108-88-3, 67-56-1, 1330-20-7, 123-42-2, 100-41-4
 Pennsylvania: 67-64-1, 108-88-3, 67-56-1, 1330-20-7, 123-42-2, 100-41-4
 Massachusetts: 67-64-1, 108-88-3, 67-56-1, 1330-20-7, 123-42-2, 100-41-4
 Rhode Island : 67-64-1, 108-88-3, 67-56-1, 1330-20-7, 123-42-2, 100-41-4

Additional Regulatory Information: In states with consumer products VOC regulations, this product is compliant as a 'Fuel-injection Air Intake Cleaner'.

Section 16: Other Information

NFPA:	Health: 2	Flammability: 3	Reactivity: 0	
HMIS:	Health: 2	Flammability: 3	Reactivity: 0	PPE: B

Prepared By: Michelle Rudnick
 CRC #: 464F
 Revision Date: 12/03/2007

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		