

MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: CRC® Air Brake Anti-Freeze & Conditioner

Product Number (s): 05525, 05528, 05532, 05555

Manufactured By: CRC Industries, Inc. (215) 674-4300
885 Louis Drive, Warminster, PA 18974
24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Methanol	67-56-1	200 ppm	200 ppm	NE	> 98

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Clear liquid. Alcohol odor

Danger: Flammable. Vapor Harmful. May be fatal or cause blindness if swallowed.

Potential Health Effects:

Inhalation: Drowsiness, nausea and vomiting.
Eyes: Irritation
Skin: Burning, itching and redness.
Ingestion: Inebriation, headache, nausea, blindness and death.

Carcinogenicity: OSHA: No IARC: No NTP: No
Chronic Overexposure: NA
Medical Conditions Aggravated by Exposure: NA

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.
Eyes: Flush with large amounts of water for 15 minutes.
Skin: Remove contaminated clothing and wash area with soap and water.
Ingestion: Call a physician. Induce vomiting.

Section 5: Fire-Fighting Measures

Flashpoint: 54 °F Method: TCC LEL: 6.0 UEL: 36.5
Extinguishing Media: Carbon dioxide, dry chemical and foam.
Hazardous Combustion Products: Thermal - Carbon monoxide
Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting.

NFPA: Health: 3 Flammability: 3 Reactivity: 0
HMIS: Health: 3 Flammability: 3 Reactivity: 0 PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area.

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State: Liquid Appearance & Odor: Clear liquid. Alcohol odor.
Specific Gravity: 0.7924 Boiling Point: 148 °F
Freezing Point: ND Vapor Pressure: 96 mm
Evaporation Rate: 2 (butyl acetate=1) Vapor Density (air = 1) 1.11
pH: NA Solubility: Complete solubility in water.

Volatile Organic Compounds:%: 100.0 g/L: 792 lbs./gal: 6.6

Section 10: Stability and Reactivity

Stability: Stable Hazardous Polymerization: No
Chemical Incompatibilities: Strong oxidizers.
Materials to Avoid: Strong oxidizers.
Hazardous Decomposition Products: None

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.
Environmental Fate: No data available for biodegradation.

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

05532 – 32 fl. Oz. bottle

Shipping Name: Consumer Commodity
Hazard Class: ORM-D UN Number: NA Packing Group: NA
Label: NA Placard: NA
Special Provisions: NA

05525 – 5 gallon pail; 05528 – 1 gallon bottle; 05555 – 55 gallon drum

Shipping Name: Methanol
Hazard Class: 3 UN Number: 1230 Packing Group: II
Label: NA Placard: NA
Special Provisions: NA

Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.
SARA Title III: Section 311/312: Acute Section 313*: Methanol
CERCLA/Superfund (RQ): Mixture
Extremely Hazardous Substances: No
California Prop 65: No

* See section 2 for percentage

Section 16: Additional Information

Prepared By: Adam M. Selisker Date: April 23, 2003
Technical Information: (800) 521-3168 CRC #: 620B

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable
ppm: Parts per Million ND: Not Determined

Product Name: CRC®Air Brake Anti-Freeze & Conditioner

**Product Number (s):
05525, 05528, 05532, 05555**

TCC:	Tag Closed Cup	NE:	Not Established
LEL:	Lower Explosive Limit	g/L:	grams per Liter
UEL:	Upper Explosive Limit	lbs./gal:	pounds per gallon
PPE:	Personal Protection Equipment	RQ:	Reportable Quantity
COC:	Cleveland Closed Cup	TOC:	Tag Open Cup