

MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: CRC® Cold Flow™ Anti-Gel with Lubricity
Product Number (s): 05625, 05628, 05632, 05655

Manufactured By: CRC Industries, Inc. (215) 674-4300
885 Louis Drive, Warminster, PA 18974
24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Copolymer Resin	Proprietary	NE	NE	NE	< 10
Xylene	1330-20-7	100 ppm	100 ppm	NE	60-70
Detergent	Mixture	NE	NE	NE	< 10
Petroleum Distillate	64742-95-6	NE	400 ppm	NE	10-20
Ethylbenzene	100-41-4	100 ppm	100 ppm	NE	10-15
Trimethylbenzene (mixed isomers)	25551-13-7	25 ppm	25 ppm	NE	5-15

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Clear amber liquid, aromatic odor.

Danger: Flammable. Vapor Harmful. Harmful or Fatal if Swallowed.

Potential Health Effects:

Inhalation: Headaches, dizziness, nausea, central nervous system effects and mucous membrane irritation.
Eyes: Irritation
Skin: Dryness, dryness
Ingestion: NA

Carcinogenicity: OSHA: No IARC: Yes NTP: No
Chronic Overexposure: Dermatitis.
Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorders.

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.
Eyes: Flush with large amounts of water for 15 minutes.
Skin: Remove contaminated clothing and wash area with soap and water.
Ingestion: Call a physician. Do not induce vomiting.

Section 5: Fire-Fighting Measures

Flashpoint: 82°F Method: TCC LEL: ND UEL: ND
Extinguishing Media: CO₂, foam and dry chemical
Hazardous Combustion Products: CO, CO₂ (fire)
Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting.

NFPA: Health: 2 Flammability: 3 Reactivity: 0
HMIS: Health: 2 Flammability: 3 Reactivity: 0 PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area.

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State: Liquid Appearance & Odor: Amber liquid
Specific Gravity: 0.8823 Boiling Point: ND
Freezing Point: ND Vapor Pressure: ND
Evaporation Rate: NA Vapor Density (air = 1) > air
pH: NA Solubility: Negligible in water.

Volatile Organic Compounds:%: 99 g/L: 873 lbs./gal: 7.28

Section 10: Stability and Reactivity

Stability: Stable Hazardous Polymerization: No
Chemical Incompatibilities: Strong oxidizers.
Materials to Avoid: Strong oxidizers.
Hazardous Decomposition Products: None

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.
Environmental Fate: No data available for biodegradation.

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

Part #:	05628, 05632				
Shipping Name:	Consumer Commodity				
Hazard Class:	ORM-D	UN Number	NA	Packing Group:	NA
Label:	NA	Placard:	NA		
Special Provisions:	NA				
Part #:	05625, 05655				
Shipping Name:	Flammable Liquids, N.O.S. (Contains Xylene)				
Hazard Class:	3	UN Number:	1993	Packing Group:	III
Label:	NA	Placard:	NA		
Special Provisions:	NA				

Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.
SARA Title III: Section 311/312: NA Section 313*: Xylene, Ethylbenzene,
CERCLA/Superfund (RQ): NA Trimethylbenzene
Extremely Hazardous Substances: No
California Prop 65: This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

* See section 2 for percentage

Section 16: Additional Information

Prepared By: Michelle Milburn Date: June 17, 2003
Technical Information: (800) 521-3168 CRC #: 627F

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
LEL:	Lower Exposure Limit	g/L:	grams per Liter
UEL:	Upper Exposure Limit	lbs./gal:	pounds per gallon
PPE:	Personal Protection Equipment	RQ:	Reportable Quantity
COC:	Cleveland Closed Cup		