



# Material Safety Data Sheet

## Section 1: Product & Company Identification

**Product Name:** Spin Doctor™ Propeller Grease

**Product Number (s):** 06117

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-4620
24-Hr Emergency (CHEMTREC)	(800) 424-9300

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Off-white semi solid, mild odor

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

### Potential Health Effects:

- EYE:** May cause eye irritation in sensitive individuals.
- SKIN:** May cause skin irritation on sensitive individuals.
- INHALATION:** May cause headache, dizziness, or nausea.
- INGESTION:** May cause gastrointestinal discomfort.
- CHRONIC EFFECTS:** Prolonged or repeated contact may cause mild skin irritation and inflammation.
- TARGET ORGANS:** Skin and eyes

Medical Conditions Aggravated by Exposure:

Pre-existing skin disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

---

**Section 3: Composition/Information on Ingredients**

COMPONENT	CAS NUMBER	% by Wt.
Magnesium silicate	14807-96-6	15 - 20
Polytetrafluoroethylene (PTFE)	9002-84-0	1 - 5
Titanium Dioxide	13463-67-7	0.2 - 1.6
Additive blend	Proprietary	75 - 85

---

**Section 4: First Aid Measures**

Eye Contact:	Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
Skin Contact:	Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
Inhalation:	Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
Ingestion:	Call a physician. Do not induce vomiting. Keep person warm.
<i>Note to Physicians:</i>	Treat symptomatically.

---

**Section 5: Fire-Fighting Measures**

<u>Flammable Properties:</u>	As defined by OSHA, this product is non-flammable.		
Flash Point:	400°F (COC)	Upper Explosive Limit:	ND
Autoignition Temperature:	ND	Lower Explosive Limit:	ND
Suitable Extinguishing Media:	Carbon dioxide, water fog, foam		
Products of Combustion:	Carbon monoxide, carbon dioxide, trace metallic compounds		
Protection of Fire-Fighters:	Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Treat as an oil fire.		

---

**Section 6: Accidental Release Measures**

Personal Precautions:	Use personal protection recommended in Section 8.
Environmental Precautions:	Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

### Section 7: Handling and Storage

Handling Procedures: Spills may cause slippery floors. Proper footwear required. Remove contaminated clothing and launder before reuse. Wash hands with soap and water before eating, drinking, or smoking. Discard contaminated gloves and shoes.

Storage Procedures: Store in a cool dry area out of direct sunlight. Avoid storage near open flame or other sources of ignition. Keep containers closed when not in use.

Aerosol Storage Level: NA

### Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Magnesium Silicate	2	NE	2	NE	NE		mg/m <sup>3</sup>
PTFE	NE	NE	NE	NE	NE		
Titanium Dioxide	10	NE	10	NE	NE		mg/m <sup>3</sup>
Additive	NE	NE	NE	NE	NE		
N.E. – Not Established      (c) – ceiling      (s) – skin      (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as neoprene or nitrile. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

### Section 9: Physical and Chemical Properties

Physical State: Semi solid

Color: Off-white

Odor: Mild  
 Specific Gravity: 1.18  
 Initial Boiling Point: ND  
 Freezing Point: ND  
 Vapor Pressure: ND  
 Vapor Density: ND (air = 1)  
 Evaporation Rate: < 1 (ether = 1)  
 Solubility: Insoluble  
 pH: NA  
 Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./gal: 0

**Section 10: Stability and Reactivity**

Stability: Stable  
 Conditions to Avoid: Do not heat above flashpoint.  
 Incompatible Materials: Strong oxidizing agents, welding  
 Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, trace metallic compounds  
 Possibility of Hazardous Reactions: No

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

**ACUTE EFFECTS**

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Titanium Dioxide	TCLo	1 mg/kg	Inhalation	Rat
Titanium Dioxide	TDL0	60 mg/kg	Oral	Rat

**CHRONIC EFFECTS**

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	None listed	
IARC:	Titanium Dioxide	Group 2B (Possibly carcinogenic to humans)
NTP:	None listed	

Mutagenicity: Unknown

Other: None

**Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available

Persistence / Degradability: No information available  
Bioaccumulation / Accumulation: No information available  
Mobility in Environment: No information available

---

---

**Section 13: Disposal Considerations**

Disposal: This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

---

**Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: None

---

---

**Section 15: Regulatory Information**

**U.S. Federal**

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:

Fire Hazard	No
Reactive Hazard	No
Release of Pressure	No
Acute Health Hazard	Yes
Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

**State Regulations**

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: 14807-96-6, 13463-67-7, NJTSRN 80100362-5008P, 80100362-5012P, 80100362-5004P, 80100362-5014P, 80100362-5013P  
Pennsylvania: 14807-96-6, 9002-84-0, 13463-67-7  
Massachusetts: 14807-96-6, 13463-67-7  
Rhode Island : 14807-96-6, 9002-84-0, 13463-67-7

**Additional Regulatory Information:** None

---

**Section 16: Other Information**

NFPA: Health: 1 Flammability: 1 Reactivity: 0  
HMIS: Health: 1 Flammability: 1 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick  
CRC #: 06117  
Revision Date: 12/11/2007

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		