



SAFETY DATA SHEET

1. Identification

Product identifier Marine Fuel Stabilizer

Other means of identification
Product Code No. 06164 (Item# 1003933)

Recommended use Fuel stabilizer for gasoline

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Manufactured or sold by:

Company name CRC Industries, Inc.
Address 885 Louis Dr.
 Warminster, PA 18974 US

Telephone

General Information 215-674-4300
Technical Assistance 800-521-3168
Customer Service 800-272-4620
24-Hour Emergency 800-424-9300 (US)
(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Skin corrosion/irritation Category 1C
 Serious eye damage/eye irritation Category 1
 Sensitization, skin Category 1
 Carcinogenicity Category 2
 Reproductive toxicity (the unborn child) Category 2
 Specific target organ toxicity, single exposure Category 3 respiratory tract irritation
 Specific target organ toxicity, repeated exposure Category 2 (central nervous system, ears, kidney, liver, peripheral nervous system)
 Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2
 Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs (central nervous system, ears, kidney, liver, peripheral nervous system) through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If exposed or concerned: Get medical advice/attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	60 - 70
xylene		1330-20-7	10 - 20
ethylbenzene		100-41-4	5 - 10
hydroxyethylated aminoethylamide		Proprietary	3 - 5
distillates (petroleum), hydrotreated light		64742-47-8	1 - 3
toluene		108-88-3	1 - 3
alkarylamine		94-91-7	< 1
cumene		98-82-8	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Edema. Jaundice. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
cumene (CAS 98-82-8)	PEL	245 mg/m ³ 50 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³	
		500 ppm	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	PEL	400 mg/m ³	
ethylbenzene (CAS 100-41-4)	PEL	100 ppm	
		435 mg/m ³	
xylene (CAS 1330-20-7)	PEL	100 ppm	
		435 mg/m ³	
		100 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
cumene (CAS 98-82-8)	TWA	50 ppm	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m ³	Inhalable fraction.
ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
toluene (CAS 108-88-3)	TWA	20 ppm	
xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
cumene (CAS 98-82-8)	TWA	245 mg/m ³	
		50 ppm	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m ³	
	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m ³	
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m ³	
		125 ppm	
	TWA	435 mg/m ³	
		100 ppm	
toluene (CAS 108-88-3)	STEL	560 mg/m ³	
		150 ppm	
	TWA	375 mg/m ³	
		100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

cumene (CAS 98-82-8)

Can be absorbed through the skin.

toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

cumene (CAS 98-82-8)

Skin designation applies.

toluene (CAS 108-88-3)

Skin designation applies.

US - Tennessee OELs: Skin designation

cumene (CAS 98-82-8)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection

Wear protective gloves such as: Polyvinyl chloride (PVC). Neoprene. Nitrile.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

Yellow.

Odor

Slight. Aromatic.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-52.6 °F (-47 °C) estimated

Initial boiling point and boiling range

278.6 °F (137 °C) estimated

Flash point	114 °F (45.6 °C) Tag Closed Cup
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.5 % estimated
Flammability limit - upper (%)	6.6 % estimated
Vapor pressure	2.8 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.89
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	100 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause irritation to the respiratory system.
Skin contact	Causes severe skin burns. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Edema. Jaundice.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
Marine Fuel Stabilizer		
Acute		
Dermal		
ATEmix		2007.9515 mg/kg

Components	Species	Test Results
cumene (CAS 98-82-8)		
Acute		
Oral		
LD50	Rat	1400 mg/kg
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
ethylbenzene (CAS 100-41-4)		
Acute		
Inhalation		
LC50	Rat	17.2 mg/l, 4 hours
Oral		
LD50	Rat	3500 mg/kg
xylene (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	4300 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	3 Not classifiable as to carcinogenicity to humans.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	3 Not classifiable as to carcinogenicity to humans.
ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.
----------------------	--

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	May cause damage to organs (central nervous system, ears, kidney, liver, peripheral nervous system) through prolonged or repeated exposure.

Aspiration hazard	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
alkarylamine (CAS 94-91-7)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) > 100 mg/l, 48 hours
Fish	LC50	Zebra danio (Danio rerio) > 100 mg/l, 96 hours
cumene (CAS 98-82-8)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Brine shrimp (Artemia sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.7 mg/l, 96 hours
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) > 30000 mg/l
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.1 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 3 mg/l, 96 hours
ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Atlantic silverside (Menidia menidia) 4.4 - 5.7 mg/l, 96 hours
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 2.1 mg/l, 48 hours
toluene (CAS 108-88-3)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 6 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch) 5.5 mg/l, 96 hours
xylene (CAS 1330-20-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 9.54 - 19.2 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

cumene	3.66
ethylbenzene	3.15
toluene	2.73
xylene	3.12 - 3.2

Bioconcentration factor (BCF)

ethylbenzene	1
toluene	90
xylene	23.99

Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products	If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (xylene RQ = 621 LBS, ethylbenzene RQ = 13333 LBS), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (xylene, ethylbenzene), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (xylene, ethylbenzene), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.
-------------------------------	---

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

cumene (CAS 98-82-8)
 ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

CERCLA Hazardous Substance List (40 CFR 302.4)

cumene (CAS 98-82-8)	Listed.
ethylbenzene (CAS 100-41-4)	Listed.
toluene (CAS 108-88-3)	Listed.
xylene (CAS 1330-20-7)	Listed.

CERCLA Hazardous Substances: Reportable quantity

cumene (CAS 98-82-8)	5000 LBS
ethylbenzene (CAS 100-41-4)	1000 LBS
toluene (CAS 108-88-3)	1000 LBS
xylene (CAS 1330-20-7)	100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

toluene (CAS 108-88-3)	6594
------------------------	------

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

toluene (CAS 108-88-3)	35 %WV
------------------------	--------

DEA Exempt Chemical Mixtures Code Number

toluene (CAS 108-88-3)	594
------------------------	-----

Food and Drug Administration (FDA) Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

Section 311/312 Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance	No
---	----

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

cumene (CAS 98-82-8)
 distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
 ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

cumene (CAS 98-82-8)
 ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

cumene (CAS 98-82-8)
 distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
 ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

cumene (CAS 98-82-8)
 distillates (petroleum), hydrotreated light (CAS 64742-47-8)
 ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

US. Rhode Island RTK

cumene (CAS 98-82-8)
 distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
 ethylbenzene (CAS 100-41-4)
 toluene (CAS 108-88-3)
 xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

benzene (CAS 71-43-2)	Listed: February 27, 1987
cumene (CAS 98-82-8)	Listed: April 6, 2010
ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
naphthalene (CAS 91-20-3)	Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2)	Listed: December 26, 1997
toluene (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

Volatile organic compounds (VOC) regulations**EPA**

VOC content (40 CFR 51.100(s))	96.1 %
Consumer products (40 CFR 59, Subpt. C)	Not regulated

State

Consumer products	Not regulated
VOC content (CA)	27.6 %
VOC content (OTC)	27.6 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-29-2017
Prepared by	Allison Yoon
Version #	01
Further information	CRC # 899A/1002888
HMIS® ratings	Health: 3* Flammability: 2 Physical hazard: 0 Personal protection: D
NFPA ratings	Health: 3 Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..