MATERIAL SAFETY DATA SHEET

| | I J J | | | | | | |
|--|--|---------------------|-------------------|---------------|----------------|-------|--|
| Product Name: M Product Number (s): M | · | Reel Lubricant | | | | | |
| Manufactured By: Cl | RC Industr | ies, Inc. | | (21 | 5) 674-4300 | | |
| | 885 Louis Drive, Warminster, PA 18974 24-Hour Emergency Information: CHEMTREC | | | | (800) 424-9300 | | |
| Section 2: Composition/ | Information | n on Ingredients | | | | | |
| Component | | CAS | ACGIH | OSHA | OTHER | % | |
| - | | NUMBER | TLV | PEL | LIMITS | | |
| Polytetrafluoroethylene (PTFE*) | | 9002-84-0 | NE | NE | 10 mg/m3 | 70-95 | |
| Perfluoroalkyether | . , | 60164-51-4 | NE | NE | NE | 5-30 | |
| Perfluorocarboxylic Acid 51798-33-5 | | | NE | NE | NE | 2-5 | |
| *Not a hazardous materi | al under no | ormal usage, but PT | FE can produce to | oxic fumes if | pyrolized. | | |
| Section 3: Hazards Ident | ification | | | | | | |
| | | Emergen | cy Overview | | | | |

| Appearance & Odor: Smooth, white grease with no odor. |
|---|
| DANGER: May irritate eyes and skin. Thermal decomposition of PTFE releases hazardous fumes that may cause polymer fume fever. |
| |

Potential Health Effects:

Section 1: Product & Company Identification

| i otominar mountin Em | | | | | | | |
|-----------------------|--|---|---------------------|--|------|----|--|
| Inhalation: | Oil mist and vapors at high temperatures may irritate respiratory passages. Inhalation of decomposition products of PTFE (over 290°C) may cause polymer fume fever, a temporary flu-like illness accompanied by fever, chills, and sometimes cough, of approximately 24 hours duration. Inhalation of fluorine compounds as decomposition products of PTFE (over 290°C) may cause lung irritation and pulmonary edema. | | | | | | |
| | · · · · | / | 5 0 | 1 | 2 | l. | |
| Eyes: | Irritation w | ith discomfort | , tearing or blu | rring of visio | n. | | |
| Skin: | of PTFE (o | Repeated or prolonged skin contact may cause irritation or rash. Thermal decomposition of PTFE (over 290°C) will generate hydrogen fluoride, which is corrosive, causing burns on contact with skin and other tissue. | | | | | |
| Ingestion: | May cause gastrointestinal irritation. | | | | | | |
| Carcinogenicity: | OSHA: | No | IARC: | No | NTP: | No | |
| Chronic Overexposure: | | | Repeated of damage. | Repeated episodes of polymer fume fever may cause lung damage. | | | |
| Medical Conditions | have incre | Individuals with pre-existing diseases of the lungs may have increased susceptibility to the toxicity of excessive | | | | | |

Section 4: First Aid Measures

exposures from thermal decomposition products.

| Product Name: Marykate® Reel Lubricant P | | | | Product Number (s): MK80005 | | | |
|--|-------------|---|--|-----------------------------|---------------------------------------|--|--|
| Inhalation: | R | Remove to fresh air. Give artificial respiration if necessary. Get medical attention. | | | | | |
| Eyes: | | Flush with large amounts of water for at least 15 minutes. Get immediate medical attention. | | | | | |
| Skin: | R | lemove cont | aminated clothing | and wash are | ea with soap and water. | | |
| Ingestion: | C | Call a physic | ian. Do not induce | vomiting. I | f conscious, give 2 glasses of water. | | |
| Note to Physician: Activated charcoal mixture may be administered. Suspend 50 grams activated charcoal in 400 mL water and mix thoroughly. Administer 5 mL/kg, or 350 mL for an average adult. | | | | | | | |
| Section 5: Fire-Fighting Measures | | | | | | | |
| Flashpoint: | Ν | lone | Method: PI | МСС | LEL: ND UEL: ND | | |
| Extinguishing Media: | | | As appropriate for | or combustibl | les in area. | | |
| Hazardous Combustion Products: Hydrogen fluoride, carbonyl fluoride, carbon monoxide and small amount of other toxic fumes. | | | | | | | |
| Fire-fighting | Instruction | 15: | Wear a NIOSH approved positive pressure self-contained breathing apparatus with full protective clothing. Do not release runoff from | | | | |
| | | | fire control methods to sewers or waterways. | | | | |
| NFPA: | Health: | 1 | Flammability: | 0 | Reactivity: 0 | | |
| HMIS: | Health: | 1 | Flammability: | 0 | Reactivity: 0 PPE: B | | |

Section 6: Accidental Release Measures

Spill/Leak Procedures: Area should be ventilated. Remove sources of heat and flame. Absorbent should be used to pick up any liquid material. Wipe or scrape up grease and place it in a proper container for disposal. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Wash hands after use. Avoid contact with eyes and skin. Do not use near heat or flames.

Storage Procedures: Store in a cool, dry area. Do not store in open or unlabeled containers. Store away from incompatibles. Keep out of reach of children!

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Provide ventilation adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Product Name: Marykate® Reel Lubricant Section 9: Physical & Chemical Properties

| Physical State: Specific Gravity: Freezing Point: Evaporation Rate: pH: | Grease 1.89-1.93 (@^ ND ND Neutral | 75F) | Appearance & Boiling Point: Vapor Pressur Vapor Density Solubility: | e: | Smooth white Not volatile Negligible ND Negligible in v | grease, no odor water |
|--|--|------------------------------|---|-----------------|---|--------------------------|
| Volatile Organic Compound | s:%: ND | | g/L: | ND | lbs./gal: | ND |
| Section 10: Stability and Rea | nctivity | | | | | |
| Stability: Chemical Incompatibilities: Conditions to Avoid: Hazardous Decomposition P | roducts: | Pyrolys Therma carbony | al oxidative de | | lymerization: In produce hydr as well as smal | |
| Section 11: Toxicological In | formation | | | | | |
| Long-term toxicological stud The following data is availab | | | | product. | | |
| Perfluoroalkylether: | Inhalation 4 hr ALC:19.54 mg/L (rat)Skin absorption ALD:>17,000 mg/kg (rabbit)Oral ALD:>25,000 mg/kg (rat) | | | it) | | |
| Perfluorocarboxylic Acid: | Oral ALD: | | >25,00 | 00 mg/kg (rat) | | |
| Section 12: Ecological Inform | nation | | | | | |
| Ecotoxicity: Environmental Fate: | No data availa No data availa | | biodegradation | | | |
| Section 13: Disposal Conside | erations | | | | | |
| Disposal: This material if dis activities must comply with agency for specific rules. Do | federal, state an | d local r | regulations. Co | ontact your loc | al or state envir | |
| Section 14: Transportation In | | | | | | |
| Shipping Name: Hazard Class: Label: Special Provisions: | Not Regulated NA NA NA | | UN Number: Placard: | NA NA | Packing Grou | p: NA |

Section 15: Regulatory Information

| TSCA: | All components are either listed under TSCA or are exempt. | | | | |
|---------------------------------|--|-------|--|--|--|
| SARA Title III: | Section 311/312: | Acute | | | |
| | Section 313*: | NA | | | |
| CERCLA/Superfund (RQ): | | NA | | | |
| Extremely Hazardous Substances: | | No | | | |
| California Prop 65: | | No | | | |
| * See section 2 for percentage | | | | | |
| | | | | | |

Section 16: Additional Information

| Prepared By: | Michelle Milburn | Date: | July 9, 2003 | | | |
|--|------------------|--------|--------------|--|--|--|
| Technical Information: | (800) 521-3168 | CRC #: | MK80005 | | | |
| This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by | | | | | | |
| CRC to be accurate. Before using any product, read all warnings and directions on the label. | | | | | | |

| CAS: | Chemical Abstract Service | NA: | Not Applicable |
|------|-------------------------------|-----------|---------------------|
| ppm: | Parts per Million | ND: | Not Determined |
| TCC: | Tag Closed Cup | NE: | Not Established |
| LEL: | Lower Explosive Limit | g/L: | grams per Liter |
| UEL: | Upper Explosive Limit | lbs./gal: | pounds per gallon |
| PPE: | Personal Protection Equipment | RQ: | Reportable Quantity |
| COC: | Cleveland Closed Cup | | |