



Section 1: Product & Company Identification

Product Name: SP-350™ Corrosion Inhibitor (bulk)

Product Number (s): 03268

Product Use: Lubricant & Corrosion Inhibitor

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Eye and Skin Irritant. Harmful or Fatal if Swallowed.

Appearance & Odor: Tan creamy liquid, petroleum solvent odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause eye irritation. Symptoms include stinging, tearing and redness.

SKIN: Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying, and cracking of the skin.

INHALATION: Expected to have a low degree of toxicity by inhalation. Breathing concentrated vapors may be harmful. Symptoms of overexposure include irritation of the nose and throat, headache, dizziness, drowsiness, loss of coordination and other signs of central nervous system depression.

INGESTION: Low degree of toxicity by ingestion. May cause irritation of digestive tract, nausea and vomiting. Main hazard is aspiration of material into lungs during swallowing or vomiting. This can lead to lung inflammation and damage.

CHRONIC EFFECTS: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TARGET ORGANS: Kidneys, central nervous system

Medical Conditions Aggravated by Exposure: skin disorders, respiratory disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: SP-350™ Corrosion Inhibitor (bulk)

Product Number (s): 03268

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hydrotreated light distillates	64742-47-8	50 – 60
Solvent refined heavy paraffinic distillates	64741-88-4	20 – 30
Oil soluble calcium sulfonates	Proprietary blend	15 – 20
Fatty acids, tall oil, monoesters with sorbitan	61791-48-8	1 – 3

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do not induce vomiting. Contact a physician immediately. If victim is drowsy or unconscious, place individual on the left side with head down.

Note to Physicians: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is a Class IIIA Combustible Liquid

Flash Point: 190°F (87.8°C) TCC Upper Explosive Limit: 6.0 (estimate)
Autoignition Temperature: 410°F (210°C) Lower Explosive Limit: 0.6 (estimate)

Fire and Explosion Data:

Suitable Extinguishing Media: Foam, carbon dioxide, dry chemical; Class B fire extinguishers

Products of Combustion: Oxides of carbon, sulfur

Explosion Hazards: Closed containers of chemicals, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Product Name: SP-350™ Corrosion Inhibitor (bulk)

Product Number (s): 03268

Methods for Containment & Clean-up: Dike area to contain spill. Remove sources of ignition. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use near sources of ignition. Do not use on energized equipment. Use with proper ventilation. Wash hands after use and before handling food. Use proper grounding and bonding procedures when transferring material between metal containers. For product use instructions, please see product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Keep containers closed when not in use.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Hydrotreated light distillates	NE	NE	NE	NE	NE		
Solvent refined heavy paraffinic distillates	NE	NE	NE	NE	NE		
Oil soluble calcium sulfonates	NE	NE	NE	NE	NE		
Fatty acids, tall oil, monoesters with sorbitan	NE	NE	NE	NE	NE		
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Product Name: SP-350™ Corrosion Inhibitor (bulk)

Product Number (s): 03268

Section 9: Physical and Chemical Properties

Physical State: liquid

Color: tan, creamy

Odor: petroleum solvent

Odor Threshold: ND

Specific Gravity: 0.86

Initial Boiling Point: > 392 °F (> 200 °C)

Freezing Point: -72.4 °F (-58 °C)

Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: slow

Solubility: insoluble in water

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 5.9 g/L: 50.6 lbs./gal: 0.42

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition; temperature extremes

Incompatible Materials: Strong oxidizing agents

Hazardous Decomposition Products: oxides of carbon, sulfur and calcium

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Hydrotreated light distillates	> 5 g/kg	> 2 g/kg	> 5 mg/L/4H
Solvent refined heavy paraffinic distillates	No data	No data	No data
Oil soluble calcium sulfonates	No data	No data	No data
Fatty acids, tall oil, monoesters with sorbitan	No data	No data	No data

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Hydrotreated light distillates	No	No	No	None	Unknown
Solvent refined heavy paraffinic distillates	No	No	No	None	Unknown
Oil soluble calcium sulfonates	No	No	No	eye, skin	Unknown
Fatty acids, tall oil, monoesters with sorbitan	No	No	No	Unknown	Unknown

Product Name: SP-350™ Corrosion Inhibitor (bulk)

Product Number (s): 03268

Release of Pressure No
Acute Health Hazard Yes
Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Canadian Regulations:

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

WHMIS Hazard Class: B3, D2B


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	1
Flammability:	2
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: 540F/G
Revision Date: 03/29/2017

Changes since last revision: Part number removed

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

Product Name: SP-350™ Corrosion Inhibitor (bulk)

Product Number (s): 03268

ACGIH: American Conference of Governmental Industrial Hygienists	NA: Not Applicable
CAS: Chemical Abstract Service	ND: Not Determined
CFR: Code of Federal Regulations	NIOSH: National Institute of Occupational Safety & Health
DOT: Department of Transportation	NFPA: National Fire Protection Association
DSL: Domestic Substance List	NTP: National Toxicology Program
g/L: grams per Liter	OSHA: Occupational Safety and Health Administration
HMIS: Hazardous Materials Identification System	PMCC: Pensky-Martens Closed Cup
IARC: International Agency for Research on Cancer	PPE: Personal Protection Equipment
IATA: International Air Transport Association	ppm: Parts per Million
ICAO: International Civil Aviation Organization	RoHS: Restriction of Hazardous Substances
IMDG: International Maritime Dangerous Goods	STEL: Short Term Exposure Limit
IMO: International Maritime Organization	TCC: Tag Closed Cup
lbs./gal: pounds per gallon	TWA: Time Weighted Average
LC: Lethal Concentration	WHMIS: Workplace Hazardous Materials Information System
LD: Lethal Dose	