



MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Inner Slide Lube
Product Number (s): 05305
Product Use: Lubricant for inner slides of fork lifts

Manufacturer / Supplier Contact Information:

In United States:
CRC Industries, Inc.
885 Louis Drive
Warminster, PA 18974
www.crcindustries.com
1-215-674-4300 (General)
(800) 521-3168 (Technical)
(800) 272-4620 (Customer Service)

In Canada:
CRC Canada Co.
2-1246 Lorimar Drive
Mississauga, Ontario L5S 1R2
www.crc-canada.ca
1-905-670-2291

In Mexico:
CRC Industries Mexico
Av. Benito Juárez 4055 G
Colonia Orquídea
San Luís Potosí, SLP CP 78394
www.crc-mexico.com
52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely flammable. Harmful or Fatal if Swallowed. May Irritate Skin.
Contents under pressure.
Appearance & Odor: Black liquid with solvent odor.

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause eye irritation and moderate corneal injury. Vapors may irritate eyes.

SKIN: Prolonged contact may cause irritation and defatting of skin.

INHALATION: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Prolonged overexposure to solvent will result in permanent brain and nervous system damage.

INGESTION: If aspirated, it may be absorbed through lungs and result in injury to body. May cause gastro-intestinal distress.

CHRONIC EFFECTS: Repeated and prolonged overexposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are signs that solvent levels are too high.

TARGET ORGANS: central nervous system

Medical Conditions Aggravated by Exposure: ND

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Inner Slide Lube

Product Number (s): 05305

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Heptane	142-82-5	30 - 40
Hydrotreated Heavy Naphthenic	64742-65-0	20 - 30
Liquefied Petroleum Gas	68476-85-7	20 - 30
Petroleum Oil Mixture	Proprietary	3 - 10
Molybdenum Disulfide	1317-33-5	<1
Antimony Diamyldithiocarbamate	15890-25-2	<0.50

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do not induce vomiting. Call a physician immediately.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6)).

Flash Point: 20°F / -7 °C (TCC)

Upper Explosive Limit: ~6.7

Autoignition Temperature: ND

Lower Explosive Limit: ~1.2

Fire and Explosion Data:

Suitable Extinguishing Media: Carbon dioxide, foam, or dry chemical

Products of Combustion: oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors can accumulate and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Product Name: Inner Slide Lube

Product Number (s): 05305

Methods for Containment & Clean-up: Shut off all ignition sources. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers. Evacuate area if spill is large.

Section 7: Handling and Storage

Handling Procedures: Do not use near open flames, heat or any sources of ignition. Avoid breathing vapors. Vapors are heavier than air and will collect in low areas. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Heptane	500	NE	400	500	NE	NE	ppm
Hydrotreated Heavy Naphthenic	5*	NE	5*	NE	NE	NE	mg/m ³
Liquefied Petroleum Gas	1000	NE	1000	NE	NE	NE	ppm
Petroleum Oil Mixture	5*	NE	5*	NE	NE	NE	mg/m ³
Molybdenum Disulfide	5	NE	0.5	NE	NE	NE	mg/m ³
Antimony Diamyldithiocarbamate	0.5	NE	0.5	NE	NE	NE	mg/m ³
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated * - oil mist							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective, solvent resistant gloves such as nitrile or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Product Name: Inner Slide Lube

Product Number (s): 05305

Section 9: Physical and Chemical Properties

Physical State: Liquid

Color: Black

Odor: Solvent

Odor Threshold: NA

Specific Gravity: 0.70

Initial Boiling Point: 175°F / 79°C

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: >1 (air = 1)

Evaporation Rate: fast

Solubility: Slightly soluble in water

Coefficient of water/oil distribution: NA

pH: NA

Volatile Organic Compounds: wt %: 61.4 g/L: 428 lbs./gal: 3.56

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Avoid ignition sources and excessive heat.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Heptane	NE	NE	103 g/m ³ /4H
Hydrotreated Heavy Naphthenic	>5000 mg/kg	>5000 mg/kg	NE
Liquefied Petroleum Gas	NE	NE	NE
Petroleum Oil Mixture	NE	NE	NE
Molybdenum Disulfide	>2 g/kg	>2 g/kg	>2820 mg/m ³ /4H
Antimony Diamyldithiocarbamate	>16400 mg/kg	>16000 mg/kg	NE

Product Name: Inner Slide Lube

Product Number (s): 05305

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u> S (moderate) / E (mild)	<u>Sensitizer</u>
Heptane	No	No	No		Unknown
Hydrotreated Heavy Naphthenic	No	No	No	E & S (mild)	Unknown
Liquefied Petroleum Gas	No	No	No	No	No
Petroleum Oil Mixture	No	No	No	No	Unknown
Molybdenum Disulfide	No	No	No	E & S (mild)	Unknown
Antimony Diamyldithiocarbamate	No	No	No	Unknown	Unknown

E – Eye S – Skin R - Respiratory

Reproductive Toxicity: No data available
Teratogenicity: No data available
Mutagenicity: Molybdenum Disulfide: cell transformation seen in mammalian cells.
Synergistic Effects: No data available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Heptane: EC50 = 1500ul/g, 8H/NR (algae)
Persistence / Degradability: No data available
Bioaccumulation / Accumulation: No data available
Mobility in Environment: No data available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitibility with the following potential waste codes: D001. (See 40 CFR Part 261.20 – 261.33)
Aerosol containers should be fully emptied and depressurized before disposal. Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity
ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, Limited Quantity
IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity
Special Provisions: No

Section 15: Regulatory Information

Product Name: Inner Slide Lube

Product Number (s): 05305

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): No

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

Consumer Products VOC Regulations: This product is not regulated

State Right to Know:

New Jersey: 142-82-5, 1317-33-5, 68476-85-7

Pennsylvania: 142-82-5, 68476-85-7

Massachusetts: 142-82-5

Rhode Island : 142-82-5, 68476-85-7

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulation and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

Product Name: Inner Slide Lube

Product Number (s): 05305


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: none

Section 16: Other Information

HMIS® (II)	
Health:	2
Flammability:	4
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: 05305
Revision Date: 02/06/2015

Changes since last revision: Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List
g/L: grams per Liter
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization
lbs./gal: pounds per gallon
LC: Lethal Concentration
LD: Lethal Dose

NA: Not Applicable
ND: Not Determined
NIOSH: National Institute of Occupational Safety & Health
NFPA: National Fire Protection Association
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PMCC: Pensky-Martens Closed Cup
PPE: Personal Protection Equipment
ppm: Parts per Million
RoHS: Restriction of Hazardous Substances
STEL: Short Term Exposure Limit
TCC: Tag Closed Cup
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Information System