



SAFETY DATA SHEET

1. Identification

Product identifier	PhaseGuard4® Stor & Go™ Stabilizer & Ethanol Fuel Treatment	
Other means of identification		
Product code	74142	
Recommended use	Fuel treatment and stabilizer	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufactured or sold by:		
Company name	CRC Canada Co.	
Address	2-1246 Lorimar Dr. Mississauga, Ontario L5S 1R2 Canada	
Telephone	905-670-2291	
Website	www.crc-canada.ca	
E-mail	Support.CA@crcindustries.com	
Emergency phone number	24-Hour Emergency (CHEMTREC)	800-424-9300 (Canada) 703-527-3887 (International)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1B
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2

Label elements

**Signal word**

Danger

Hazard statement

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of causing cancer. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use non-sparking tools. Take action to prevent static discharges. Use explosion-proof electrical/ventilating/lighting equipment. Avoid breathing mist or vapor. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment.

Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire. Collect spillage.
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light		64742-47-8	40 - 50
naphtha (petroleum), hydrotreated heavy		64742-48-9	30 - 40
dibutylphenol		128-39-2	3 - 5
distillates (petroleum), hydrotreated middle		64742-46-7	3 - 5
hydrocarbyl amine		Proprietary	3 - 5
solvent naphtha (petroleum), heavy arom.		64742-94-5	1 - 3
naphthalene		91-20-3	< 0.3
diphenylamine		122-39-4	< 0.2
toluene		108-88-3	< 0.2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
diphenylamine (CAS 122-39-4)	TWA	10 mg/m3	
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
naphthalene (CAS 91-20-3)	TWA	10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.
toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
diphenylamine (CAS 122-39-4)	TWA	10 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m ³	Vapor.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m ³	Mist.
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	5 mg/m ³	Mist.
	TWA	1590 mg/m ³	
naphthalene (CAS 91-20-3)	STEL	400 ppm 79 mg/m ³	
	TWA	15 ppm 52 mg/m ³	
toluene (CAS 108-88-3)	TWA	10 ppm 188 mg/m ³ 50 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
diphenylamine (CAS 122-39-4)	TWA	10 mg/m ³	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m ³	Non-aerosol.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	0.2 mg/m ³	Mist.
naphthalene (CAS 91-20-3)	STEL	15 ppm	
	TWA	10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	200 mg/m ³	Non-aerosol.
toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
diphenylamine (CAS 122-39-4)	TWA	10 mg/m ³	
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m ³	Inhalable fraction.
naphthalene (CAS 91-20-3)	TWA	10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	200 mg/m ³	Non-aerosol.
toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
diphenylamine (CAS 122-39-4)	TWA	10 mg/m ³
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	525 mg/m ³
naphthalene (CAS 91-20-3)	STEL	15 ppm
	TWA	10 ppm
toluene (CAS 108-88-3)	TWA	20 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
diphenylamine (CAS 122-39-4)	TWA	10 mg/m3	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	1590 mg/m3	
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	400 ppm 10 mg/m3	Mist.
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	5 mg/m3	Mist.
naphthalene (CAS 91-20-3)	TWA	1590 mg/m3	
	STEL	400 ppm 79 mg/m3	
	TWA	15 ppm 52 mg/m3	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	10 ppm 1590 mg/m3	
toluene (CAS 108-88-3)	TWA	400 ppm 188 mg/m3 50 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Can be absorbed through the skin.
naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	Can be absorbed through the skin.
toluene (CAS 108-88-3)	Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Can be absorbed through the skin.
naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

toluene (CAS 108-88-3)	Can be absorbed through the skin.
------------------------	-----------------------------------

Canada - Saskatchewan OELs: Skin designation

distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Can be absorbed through the skin.
--	-----------------------------------

naphthalene (CAS 91-20-3)
solvent naphtha (petroleum), heavy arom. (CAS
64742-94-5)
toluene (CAS 108-88-3)

Can be absorbed through the skin.
Can be absorbed through the skin.
Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

naphthalene (CAS 91-20-3)
solvent naphtha (petroleum), heavy arom. (CAS
64742-94-5)

Can be absorbed through the skin.
Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene. Polyvinyl chloride (PVC).

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Amber.

Odor Amine-like.

Odor threshold Not available.

pH Not available.

Melting point/freezing point 98.6 °F (37 °C) estimated

Initial boiling point and boiling range 315 °F (157.2 °C) estimated

Flash point 120 °F (48.9 °C) Tag Closed Cup

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0.5 % estimated

Flammability limit - upper (%) 6 % estimated

Vapor pressure 0.6 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.82

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 410 °F (210 °C) estimated

Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Percent volatile	73.3 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Nitrogen oxides (NOx).

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
---	--

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
-----------------------	---

Components	Species	Test Results
diphenylamine (CAS 122-39-4)		
Acute		
Oral		
LD50	Rat	2 g/kg
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5.2 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg, 2.5 hours
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)		
Acute		
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours

Components	Species	Test Results
Oral LD50	Rat	> 5000 mg/kg
naphthalene (CAS 91-20-3)		
Acute Dermal LD50	Rabbit	> 20 g/kg
Oral LD50	Rat	490 mg/kg
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)		
Acute Dermal LD50	Rabbit	> 2000 mg/kg
Inhalation <i>Vapor</i> LC50	Rat	> 22 mg/l, 4 hours
Oral LD50	Rat	> 5000 mg/kg
toluene (CAS 108-88-3)		
Acute Dermal LD50	Rabbit	> 5000 mg/kg
Inhalation LC50	Rat	7585 ppm, 4 hours
Oral LD50	Rat	5580 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

ACGIH Carcinogens

diphenylamine (CAS 122-39-4)	A4 Not classifiable as a human carcinogen.
naphthalene (CAS 91-20-3)	A3 Confirmed animal carcinogen with unknown relevance to humans.
toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

diphenylamine (CAS 122-39-4)	Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	Not classifiable as a human carcinogen.
naphthalene (CAS 91-20-3)	Confirmed animal carcinogen with unknown relevance to humans.
toluene (CAS 108-88-3)	Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.
toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.
---------------------------	--

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
dibutylphenol (CAS 128-39-2)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	0.45 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	1.4 mg/l, 96 hours
diphenylamine (CAS 122-39-4)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	0.27 - 0.36 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	3.471 - 4.141 mg/l, 96 hours
distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1.1 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	3 mg/l, 96 hours
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
hydrocarbyl amine			
<i>Acute</i>			
Other	EC50	Activated sludge, industrial	> 1000 mg/l, 2.4 hours
Aquatic			
<i>Acute</i>			
Algae	EC50	Green algae (Selenastrum capricornutum)	> 450 mg/l, 96 hours
Crustacea	EC50	Water flea (Daphnia magna)	> 100 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	31 mg/l, 96 hours
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
naphthalene (CAS 91-20-3)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	1.6 mg/l, 96 hours

Components	Species		Test Results
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
toluene (CAS 108-88-3)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	6 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	5.5 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

dibutylphenol	4.92
naphthalene	3.3
toluene	2.73

Bioconcentration factor (BCF)

toluene	90
---------	----

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number	UN1268
UN proper shipping name	PETROLEUM PRODUCTS, N.O.S., Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	91, 92

IATA

UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s., Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1268
UN proper shipping name PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S., Limited Quantity
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information**Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

naphthalene (CAS 91-20-3)

toluene (CAS 108-88-3)

Precursor Control Regulations

toluene (CAS 108-88-3)

Class B

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

naphthalene (CAS 91-20-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	04-19-2017
Version #	01
Further information	CRC # 923A
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..