



SAFETY DATA SHEET

1. Identification

| | | |
|---|--|---|
| Product identifier | Power Lube Multi-Purpose Lubricant | |
| Other means of identification | | |
| Product code | 75007 | |
| Recommended use | Multi-purpose lubricant | |
| Recommended restrictions | None known. | |
| Manufacturer/Importer/Supplier/Distributor information | | |
| Manufactured or sold by: | | |
| Company name | CRC Canada Co. | |
| Address | 2-1246 Lorimar Dr. Mississauga, Ontario L5S 1R2 Canada | |
| Telephone | 905-670-2291 | |
| Website | www.crc-canada.ca | |
| E-mail | Support.CA@crcindustries.com | |
| Emergency phone number | 24-Hour Emergency (CHEMTREC) | 800-424-9300 (Canada) 703-527-3887 (International) |

2. Hazard(s) identification

| | | |
|------------------------------|--|------------|
| Physical hazards | Flammable liquids | Category 4 |
| Health hazards | Aspiration hazard | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 3 |

Label elements



| | |
|--------------------------------|---|
| Signal word | Danger |
| Hazard statement | Combustible liquid. May be fatal if swallowed and enters airways. Harmful to aquatic life. |
| Precautionary statement | |
| Prevention | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. |
| Response | IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire. |
| Storage | Store in a well-ventilated place. Store locked up. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Other hazards | None known. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|---------------------------------|-------------------|----------|
| distillates (petroleum), hydrotreated light | | 64742-47-8 | 60 - 70 |
| paraffin oils (petroleum), catalytic dewaxed heavy | | 64742-70-7 | 10 - 20 |
| paraffin oils (petroleum), catalytic dewaxed light | | 64742-71-8 | 5 - 10 |
| butyl stearate | | 123-95-5 | 3 - 5 |

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|-------|
| dipropylene glycol monomethyl ether acetate | | 88917-22-0 | 3 - 5 |
| methyl salicylate | | 119-36-8 | 1 - 3 |
| petrolatum | | 8009-03-8 | 1 - 3 |
| sorbitan monotallate | | 61791-48-8 | 1 - 3 |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

| | |
|---|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Combustible liquid. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination. |
| Environmental precautions | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|----------------------|---------------------|
| butyl stearate (CAS 123-95-5) | TWA | 10 mg/m ³ | |
| paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) | TWA | 5 mg/m ³ | Inhalable fraction. |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | TWA | 5 mg/m ³ | Inhalable fraction. |
| petrolatum (CAS 8009-03-8) | TWA | 5 mg/m ³ | Inhalable fraction. |

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components | Type | Value | Form |
|---|------|-----------------------|--------|
| butyl stearate (CAS 123-95-5) | TWA | 10 mg/m ³ | |
| distillates (petroleum), hydrotreated light (CAS 64742-47-8) | TWA | 200 mg/m ³ | Vapor. |
| paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) | STEL | 10 mg/m ³ | Mist. |
| | TWA | 5 mg/m ³ | Mist. |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | STEL | 10 mg/m ³ | Mist. |
| | TWA | 5 mg/m ³ | Mist. |
| petrolatum (CAS 8009-03-8) | STEL | 10 mg/m ³ | Mist. |
| | TWA | 5 mg/m ³ | Mist. |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Type | Value | Form |
|---|------|-----------------------|--------------|
| butyl stearate (CAS 123-95-5) | TWA | 10 mg/m ³ | |
| distillates (petroleum), hydrotreated light (CAS 64742-47-8) | TWA | 200 mg/m ³ | Non-aerosol. |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | TWA | 1 mg/m ³ | Mist. |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Type | Value | Form |
|---|------|----------------------|---------------------|
| butyl stearate (CAS 123-95-5) | TWA | 10 mg/m ³ | |
| paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) | TWA | 5 mg/m ³ | Inhalable fraction. |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | TWA | 5 mg/m ³ | Inhalable fraction. |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Type | Value | Form |
|----------------------------|------|---------|---------------------|
| petrolatum (CAS 8009-03-8) | TWA | 5 mg/m3 | Inhalable fraction. |

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

| Components | Type | Value | Form |
|--|------|---------------------------------|------|
| butyl stearate (CAS 123-95-5) | TWA | 10 mg/m3 | |
| dipropylene glycol monomethyl ether acetate (CAS 88917-22-0) | STEL | 1164 mg/m3 | |
| | TWA | 150 ppm 776 mg/m3 100 ppm | |

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value | Form |
|---|------|---------------------|-------|
| distillates (petroleum), hydrotreated light (CAS 64742-47-8) | TWA | 1590 mg/m3 | |
| paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) | STEL | 400 ppm 10 mg/m3 | Mist. |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | TWA | 5 mg/m3 | Mist. |
| | STEL | 10 mg/m3 | Mist. |
| petrolatum (CAS 8009-03-8) | TWA | 5 mg/m3 | Mist. |
| | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Canada - Alberta OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Neoprene. Nitrile.

Other Wear suitable protective clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

| | |
|----------------|---------|
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Amber. |

Odor Mint.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -56.2 °F (-49 °C) estimated

Initial boiling point and boiling range 212 °F (100 °C) estimated

Flash point 196 °F (91.1 °C) Tag Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0.6 % estimated

Flammability limit - upper (%) 5.5 % estimated

Vapor pressure 0.2 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.83

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 428 °F (220 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Percent volatile 77.6 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

Information on toxicological effects**Acute toxicity** May be fatal if swallowed and enters airways.

| Product | Species | Test Results |
|---|----------------|----------------------------|
| Power Lube Multi-Purpose Lubricant | | |
| <u>Acute</u> | | |
| Dermal | | |
| ATEmix | | 2105.8395 mg/kg |
| Components | Species | Test Results |
| butyl stearate (CAS 123-95-5) | | |
| <u>Acute</u> | | |
| Oral | | |
| LD50 | Rat | 32 g/kg |
| dipropylene glycol monomethyl ether acetate (CAS 88917-22-0) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 20 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| distillates (petroleum), hydrotreated light (CAS 64742-47-8) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 20 mg/l, 4 hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg > 25 ml/kg |
| methyl salicylate (CAS 119-36-8) | | |
| <u>Acute</u> | | |
| Oral | | |
| LD50 | Rat | 887 mg/kg |
| paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| petrolatum (CAS 8009-03-8) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 20 mg/l, 4 hours |

| Components | Species | Test Results |
|---------------------------------------|---------|--------------------|
| Oral | | |
| LD50 | Rat | > 2000 mg/kg |
| sorbitan monotallate (CAS 61791-48-8) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 20 mg/l, 4 hours |
| Oral | | |
| LD50 | Rat | 39800 mg/kg |

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

butyl stearate (CAS 123-95-5) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

butyl stearate (CAS 123-95-5) A4 Not classifiable as a human carcinogen.

paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) A4 Not classifiable as a human carcinogen.

paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) A4 Not classifiable as a human carcinogen.

petrolatum (CAS 8009-03-8) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

butyl stearate (CAS 123-95-5) Not classifiable as a human carcinogen.

paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) Not classifiable as a human carcinogen.

paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) Not classifiable as a human carcinogen.

petrolatum (CAS 8009-03-8) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

| Components | Species | Test Results |
|---|---------|---|
| dipropylene glycol monomethyl ether acetate (CAS 88917-22-0) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | LC50 | Water flea (Daphnia magna) 2701 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 151 mg/l, 96 hours |
| | | Rainbow trout, donaldson trout (Oncorhynchus mykiss) 111 mg/l, 96 hours |
| paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | EC50 | Daphnia > 100 mg/l, 48 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|---|---------------|
| dipropylene glycol monomethyl ether acetate | 0.61 OECD 107 |
| methyl salicylate | 2.55 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|-------------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

| | |
|----------------------------|--|
| Issue date | 12-20-2016 |
| Version # | 01 |
| Further information | CRC # 462F |
| Disclaimer | The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.. |