



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>GDI IVD™ Intake Valve &amp; Turbo Cleaner</b>	
<b>Other means of identification</b>		
<b>Product code</b>	75320	
<b>Recommended use</b>	Cleaner for gasoline direct injection intake valves	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Manufactured or sold by:</b>		
<b>Company name</b>	CRC Canada Co.	
<b>Address</b>	2-1246 Lorimar Dr. Mississauga, Ontario L5S 1R2 Canada	
<b>Telephone</b>	905-670-2291	
<b>Website</b>	www.crc-canada.ca	
<b>E-mail</b>	Support.CA@crcindustries.com	
<b>Emergency phone number</b>	24-Hour Emergency (CHEMTREC)	800-424-9300 (Canada) 703-527-3887 (International)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 2
	Carcinogenicity	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3

### Label elements

**Signal word**

Danger

**Hazard statement**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

**Precautionary statement****Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

<b>Response</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
<b>Storage</b>	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national regulations.
<b>Other hazards</b>	None known.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
liquefied petroleum gas		68476-86-8	30 - 40
distillates (petroleum), hydrodesulfurized middle	Diesel Fuel No. 2	64742-80-9	20 - 30
distillates (petroleum), hydrotreated light		64742-47-8	10 - 20
polyether amine		9835*	10 - 20
distillates (petroleum), hydrotreated middle		64742-46-7	5 - 10
hydrocarbyl amine		9835*	3 - 5
solvent naphtha (petroleum), heavy arom.		64742-94-5	1 - 3
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	< 1
distillates (petroleum), hydrotreated light paraffinic		64742-55-8	< 1
naphthalene		91-20-3	< 0.2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Exact concentrations are withheld in accordance with HMIRA RN 10439, date filed/granted: 10/12/2016

\*CAS numbers are withheld in accordance with HMIRA RN 9835 [other supplier], date filed/granted: 02/10/2016

### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.
<b>Conditions for safe storage, including any incompatibilities</b>	Level 3 Aerosol.  Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### ACGIH

#### Components

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

#### Type

TWA

#### Value

5 mg/m3

#### Form

Inhalable fraction

#### US. ACGIH Threshold Limit Values

#### Components

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

#### Type

TWA

#### Value

5 mg/m3

#### Form

Inhalable fraction.

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

TWA

5 mg/m3

Inhalable fraction.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
naphthalene (CAS 91-20-3)	TWA	10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value	Form
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m <sup>3</sup>	Vapor.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
naphthalene (CAS 91-20-3)	STEL	79 mg/m <sup>3</sup> 15 ppm	
	TWA	52 mg/m <sup>3</sup> 10 ppm	

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m <sup>3</sup>	Mist.
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	0.2 mg/m <sup>3</sup>	Mist.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	0.2 mg/m <sup>3</sup>	Mist.
naphthalene (CAS 91-20-3)	STEL	15 ppm	
	TWA	10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
naphthalene (CAS 91-20-3)	TWA	10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.

**Canada - Ontario**

Components	Type	Value	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	
	TWA	5 mg/m3	

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
naphthalene (CAS 91-20-3)	STEL	15 ppm	
	TWA	10 ppm	

**Canada - Quebec**

Components	Type	Value	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	
	TWA	5 mg/m3	

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value	Form
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
naphthalene (CAS 91-20-3)	STEL	79 mg/m3	
		15 ppm	
	TWA	52 mg/m3	
		10 ppm	
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	1590 mg/m3	
		400 ppm	

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

**Canada - Alberta OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Can be absorbed through the skin.
naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Can be absorbed through the skin.
--	-----------------------------------

naphthalene (CAS 91-20-3)  
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

naphthalene (CAS 91-20-3)  
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

naphthalene (CAS 91-20-3)  
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
naphthalene (CAS 91-20-3)  
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

Can be absorbed through the skin.  
Can be absorbed through the skin.  
Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

naphthalene (CAS 91-20-3)  
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Wear protective gloves such as: Nitrile. Neoprene. Polyvinyl chloride (PVC).

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## 9. Physical and chemical properties

**Appearance**

**Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Amber.

**Odor**

Petroleum.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

320 °F (160 °C) estimated

**Flash point**

187 °F (86.1 °C) Tag Closed Cup

**Evaporation rate**

Moderate.

**Flammability (solid, gas)**

Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 0.5 % estimated

<b>Flammability limit - upper (%)</b>	7.5 % estimated
<b>Vapor pressure</b>	1448.1 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.87 estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	410 °F (210 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Percent volatile</b>	100 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Nitrogen oxides (NOx). Aldehydes. Ammonia. Hydrocarbon fumes and smoke.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
---	--

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways.
-----------------------	---

Components	Species	Test Results
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	1.78 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 5000 mg/kg
<b>Oral</b>		
LD50	Rat	> 15000 mg/kg

Components	Species	Test Results
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 5.2 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg, 2.5 hours
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 5 mg/l
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
naphthalene (CAS 91-20-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 20 g/kg
<b>Oral</b>		
LD50	Rat	490 mg/kg
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 22 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	Suspected of causing genetic defects.
<b>Carcinogenicity</b>	Suspected of causing cancer.

#### ACGIH Carcinogens

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	A2 Suspected human carcinogen.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	A4 Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	A4 Not classifiable as a human carcinogen.
naphthalene (CAS 91-20-3)	A3 Confirmed animal carcinogen with unknown relevance to humans.

#### Canada - Manitoba OELs: carcinogenicity

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	Suspected human carcinogen.
--	-----------------------------



distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	Not classifiable as a human carcinogen.
naphthalene (CAS 91-20-3)	Confirmed animal carcinogen with unknown relevance to humans.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	3 Not classifiable as to carcinogenicity to humans.
naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.

#### US. National Toxicology Program (NTP) Report on Carcinogens

naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.
---------------------------	--

<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
<b>Chronic effects</b>	Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) 45 mg/l, 96 hours
hydrocarbyl amine		
<i>Acute</i>		
Other	EC50	Activated sludge, industrial > 1000 mg/l, 2.4 hours
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Green algae (Selenastrum capricornutum) > 450 mg/l, 96 hours
Crustacea	EC50	Water flea (Daphnia magna) > 100 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 31 mg/l, 96 hours
naphthalene (CAS 91-20-3)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 1.6 mg/l, 96 hours
solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours

Components	Species	Test Results
		8.8 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Partition coefficient n-octanol / water (log Kow)</b>	
naphthalene	3.3
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential.

### 13. Disposal considerations

<b>Disposal of waste from residues / unused products</b>	Contents under pressure. Do not puncture, incinerate or crush. Empty container can be recycled. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

#### TDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	Not available.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	80

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, limited quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

#### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, LIMITED QUANTITY
<b>Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	Not available.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not established.

---

## 15. Regulatory information

### Canadian regulations

#### Controlled Drugs and Substances Act

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

naphthalene (CAS 91-20-3)

#### Precursor Control Regulations

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

Not applicable.

#### Montreal Protocol

Not applicable.

#### Basel Convention

naphthalene (CAS 91-20-3)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

---

## 16. Other information

**Issue date** 10-20-2016

**Version #** 01

**Further information** CRC # 883A

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..