

## Section 1: Product & Company Identification

Product Name: White Lithium Grease (aerosol)

Product Number (s): 76037

Product Use: Iubricating grease

### Manufacturer / Supplier Contact Information:

In United States:In Canada:CRC Industries, Inc.CRC Canada Co.885 Louis Drive2-1246 Lorimar DriveWarminster, PA 18974Mississauga, Ontario L5S 1R2www.crcindustries.comwww.crc-canada.ca1-215-674-4300(General)1-905-670-2291(800) 521-3168 (Technical)1905-670-2291

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

### Section 2: Hazards Identification

### Emergency Overview

**DANGER:** Extremely Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure. Appearance & Odor: Off-white, viscous grease with solvent odor

### **Potential Health Effects:**

ACUTE EFFECTS:

- EYE: May cause mild irritation including stinging and redness, but does not injure eye.
- SKIN: Single, brief exposures may cause mild irritation. Frequent or prolonged contact may cause more severe irritation, defatting of the skin, and dermatitis.
- INHALATION: High vapor concentrations are irritating to the respiratory tract and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage. Heating the dispensed grease may generate irritating vapors.
- INGESTION: Low order of toxicity by ingestion. Main hazard is aspiration into the lungs during swallowing or vomiting. Small amounts aspirated into the respiratory system may cause bronchopneumonia or pulmonary adema, possible progressing to death.
- CHRONIC EFFECTS: Overexposure to n-hexane may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs.
- TARGET ORGANS: central nervous system, peripheral nervous system, respiratory system

Medical Conditions Aggravated by Exposure: skin and respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

## Section 3: Composition/Information on Ingredients

| COMPONENT                              | CAS NUMBER            | % by Wt. |
|----------------------------------------|-----------------------|----------|
| Hexane isomers                         | 64742-49-0 / 107-83-5 | 40 - 50  |
| n-Hexane                               | 110-54-3              | 3.2      |
| Heavy naphthenic petroleum distillates | 64742-52-5            | 10 - 20  |
| Liquefied petroleum gas                | 68476-86-8            | 35 - 45  |

## Section 4: First Aid Measures

| Eye Contact:        | Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Skin Contact:       | Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use. |
| Inhalation:         | Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.         |
| Ingestion:          | Do NOT induce vomiting. Contact a physician immediately.                                                                                                      |
| Note to Physicians: | Treat symptomatically. Gastric lavage using a cuffed endotracheal tube may be performed at your discretion.                                                   |

## **Section 5: Fire-Fighting Measures**

 
 Flammable Properties:
 This product is extremely flammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)).

 Flash Point:
 < 20°F / -6°C (TCC)</td>
 Upper Explosive Limit:
 9.0

 Autoignition Temperature:
 489°F / 254°C
 Lower Explosive Limit:
 1.7

### Fire and Explosion Data:

Suitable Extinguishing Media: Class B fire extinguishers, dry chemical, foam or CO<sub>2</sub>

Products of Combustion: Fumes, smoke and carbon monoxide

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Do not spray water directly on fire; product will float and could be reignited on surface of water.

### Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

### Product Name: White Lithium Grease (aerosol) Product Number (s): 76037

Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

### Section 7: Handling and Storage

Handling Procedures: Use proper grounding and bonding procedures for transferring materials. Do not use product near any source of ignition. Avoid contact with eyes and skin. Avoid breathing vapors. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing.

Aerosol Storage Level: III

## Section 8: Exposure Controls/Personal Protection

#### Exposure Guidelines:

|                                                               | OS     | SHA     | AC    | GIH  | 0   | THER   |                   |
|---------------------------------------------------------------|--------|---------|-------|------|-----|--------|-------------------|
| COMPONENT                                                     | TWA    | STEL    | TWA   | STEL | TWA | SOURCE | UNIT              |
|                                                               |        |         |       |      |     |        |                   |
| Hexane isomers                                                | 500(v) | 1000(v) | 500   | 1000 | NE  |        | ppm               |
| n-Hexane                                                      | 500    | NE      | 50(s) | NE   | NE  |        | ppm               |
| Heavy naphthenic petroleum distillates                        | 5      | NE      | NE    | NE   | NE  |        | mg/m <sup>3</sup> |
| Liquefied petroleum gas                                       | 1000   | NE      | 1000  | NE   | NE  |        | ppm               |
| N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated |        |         |       |      |     |        |                   |

### Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVC or Viton®. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

# **Section 9: Physical and Chemical Properties**

| Physical State: semi-solid / grease          |                                          |
|----------------------------------------------|------------------------------------------|
| Color: off-white                             |                                          |
| Odor: solvent                                |                                          |
| Odor Threshold: ND                           |                                          |
| Specific Gravity: 0.6257                     |                                          |
| Initial Boiling Point: 140°F / 60°C          |                                          |
| Freezing Point: < -50°F / -45°C              |                                          |
| Vapor Pressure: ND                           |                                          |
| Vapor Density: > 1 (air = 1)                 |                                          |
| Evaporation Rate: fast                       |                                          |
| Solubility: not soluble in water             |                                          |
| Coefficient of water/oil distribution: ND    |                                          |
| pH: NA                                       |                                          |
| Volatile Organic Compounds: <u>wt %</u> : 85 | <u>g/L</u> : 531.8 <u>lbs./gal:</u> 4.43 |

# Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition, temperature extremes

Incompatible Materials: Strong oxidizers

Hazardous Decomposition Products: Oxides of carbon

Possibility of Hazardous Reactions: No

# Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

#### Acute Toxicity:

| <u>Component</u><br>Hexane isomers     | <u>Oral LD50</u> (rat)<br>> 5000 mg/kg | Dermal LD50 (rabbit) > 2000 mg/kg | Inhalation LC50 (rat) |
|----------------------------------------|----------------------------------------|-----------------------------------|-----------------------|
| n-Hexane                               | 28,710 mg/kg                           | > 3000 mg/kg                      | 48,000 ppm/4H         |
| Heavy naphthenic petroleum distillates | No data                                | No data                           | No data               |
| Liquefied petroleum gas                | No data                                | No data                           | No data               |

#### **Chronic Toxicity:**

|                                           | OSHA       | IARC       | NTP               |          |                   |
|-------------------------------------------|------------|------------|-------------------|----------|-------------------|
| <u>Component</u>                          | Carcinogen | Carcinogen | <u>Carcinogen</u> | Irritant | <u>Sensitizer</u> |
| Hexane isomers                            | No         | No         | No                | No       | Unknown           |
| n-Hexane                                  | No         | No         | No                | Skin     | No                |
| Heavy naphthenic petroleum<br>distillates | No         | No         | No                | Eye      | Unknown           |
| Liquefied petroleum gas                   | No         | No         | No                | No       | No                |

| Reproductive Toxicity: | No information available |
|------------------------|--------------------------|
| Teratogenicity:        | No information available |
| Mutagenicity:          | No information available |
| Synergistic Effects:   | No information available |

## Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

| Ecotoxicity:        | n-hexane - 48 l | Hr EC50 water flea: 3.87 mg/L          |
|---------------------|-----------------|----------------------------------------|
|                     | 96 H            | Hr LC50 Lepomis macrochirus: 4.12 mg/L |
| Persistence / Deg   | radability:     | No information available               |
| Bioaccumulation /   | Accumulation:   | No information available               |
| Mobility in Enviror | iment:          | No information available               |

## **Section 13: Disposal Considerations**

<u>Waste Classification</u>: The packaged liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001. The dispensed grease is not a hazardous waste. (See 40 CFR Part 261.20 – 261.33). Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

### Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity\*\*

ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: \*\*This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic ground shipping until December 31, 2020. If shipping as limited quantity by ground, note that shipping papers are not required.

# Section 15: Regulatory Information

### U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): Reportable Quantities (RQ's) exist for the following ingredients: n-hexane (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III: Section 302 Extremely Hazardous Substances (EHS): None

| Section 311/312 Hazard Categories: | Fire Hazard           | Yes |
|------------------------------------|-----------------------|-----|
| -                                  | Reactive Hazard       | No  |
|                                    | Release of Pressure   | Yes |
|                                    | Acute Health Hazard   | Yes |
|                                    | Chronic Health Hazard | No  |

### Product Name: White Lithium Grease (aerosol) Product Number (s): 76037

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: n-hexane (3.2%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): n-hexane

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

#### Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2A, D2B


Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

#### **European Union Regulations:**

<u>RoHS Compliance</u>: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

### Section 16: Other Information



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By:Michelle RudnickCRC #:568GRevision Date:04/13/2015

Changes since last revision: Removed product number Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

- ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstract Service
- CFR: Code of Federal Regulations
- DOT: Department of Transportation
- DSL: Domestic Substance List
- g/L: grams per Liter
- HMIS: Hazardous Materials Identification System
- IARC: International Agency for Research on Cancer
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organization
- IMDG: International Maritime Dangerous Goods
- IMO: International Maritime Organization
- lbs./gal: pounds per gallon
- LC: Lethal Concentration
- LD: Lethal Dose

- NA: Not Applicable
- ND: Not Determined
- NIOSH: National Institute of Occupational Safety & Health
- NFPA: National Fire Protection Association
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PMCC: Pensky-Martens Closed Cup
- PPE: Personal Protection Equipment
- ppm: Parts per Million
- RoHS: Restriction of Hazardous Substances
- STEL: Short Term Exposure Limit
- TCC: Tag Closed Cup
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Information System