

MATERIAL SAFETY DATA SHEET

FICHE SIGNALÉTIQUE

CRC CANADA INC.

1246 LORIMAR DRIVE UNIT #2, MISSISSAUGA, ONT. (905) 670-2291 FAX (905) 670-5941

PRODUCT IDENTIFIER: Trewax® Boat Wax

PART NO: 76666

PRODUCT USE: Polishing wax

PROPER SHIPPING NAME: N.ap

UN NUMBER: N.ap

TDG CLASS: N.ap

WHMIS CLASS: D2B

MANUFACTURED BY: CRC INDUSTRIES INC.

885 LOUIS DRIVE

WARMINSTER, PA. 18974

USA

EMERGENCY PHONE NUMBER: (613) 996-6666

PAGE 1 OF 2

SECTION 2 - HAZARDOUS INGREDIENTS

| HAZARDOUS INGREDIENTS | % | CAS NUMBER | LD 50 OF INGREDIENT (SPECIES & ROUTE) | LC 50 OF INGREDIENT (SPECIES & ROUTE) |
|-----------------------|-------|------------|---------------------------------------|---------------------------------------|
| Mineral Spirits | 40-90 | 64742-88-7 | N.av | N.av |
| Petroleum Distilate | 20-40 | 64742-47-8 | N.av | N.av |
| Dimethylpolysiloxanes | 10-20 | 63148-62-9 | N.av | N.av |
| Diatomaceous earth | 10-20 | 61790-53-2 | N.av | N.av |
| Montan wax acids | 1-10 | 68476-03-9 | N.av | N.av |
| Carnauba wax | 1-10 | 8015-86-9 | N.av | N.av |

SECTION 3 - PHYSICAL DATA

PHYSICAL STATE: Paste

BOILING POINT: 193-204°C

VAPOUR PRESSURE: 0.5 mm Hg

EVAPOURATION RATE: >1

ODOUR & APPEARANCE: Tan paste, solvent odour.

COEFF. WATER / OIL DIST.: Insoluble

SPECIFIC GRAVITY: N.av

FREEZING POINT: N.av

VAPOUR DENSITY (AIR=1): 5.4

PH: N.av

SECTION 4 - FIRE & EXPLOSION DATA

FLAMMABILITY: No.

MEANS OF EXTINCTION: Carbon dioxide, dry chemical, foam.

FLASH POINT (°C): None.

FLAMMABILITY LIMITS (% BY VOLUME)

AUTOIGNITION TEMP.: N.av

SENSITIVITY TO STATIC DISCHARGE: N.av

HAZARDOUS COMBUSTION PRODUCTS : Closed containers exposed to high temperatures such as fire conditions may rupture.

UNDER WHAT CONDITIONS:

METHOD: N.ap

UPPER: N.av **LOWER:** N.av

SENSITIVITY TO IMPACT: N.av

SECTION 5 - REACTIVITY DATA

CHEMICAL STABILITY: Stable

INCOMPATIBILITY WITH OTHER SUBSTANCES: Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: See HAZARDOUS COMBUSTION PRODUCTS.

REACTIVITY AND UNDER WHAT CONDITIONS: N.av

PRODUCT IDENTIFIER: Trewax® Boat Wax

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: Inhalation, eyes, skin, ingestion.

EFFECTS OF ACUTE EXPOSURE: Inhalation - vapour may irritate the respiratory tract. Eyes - contact with eyes can cause irritation. Skin - contact with skin can cause irritation, dryness, de-fattening. Ingestion - may be harmful or fatal if swallowed.

EFFECTS OF CHRONIC EXPOSURE: Overexposure to this material may cause severe eye and skin irritation. May effect the central nervous system and liver.

EXPOSURE LIMITS: N.av

CARCINOGENICITY: None known

TERATOGENICITY: None known

MUTANOGENICITY: None known

IRRITANCY OF PRODUCT: Eyes, skin

SYNERGISTIC PRODUCTS: None known

REPRODUCTIVE TOXICITY: None known

SENSITIZATION TO PRODUCT: None known

SECTION 7 - PREVENTATIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

GLOVES: Solvent resistant

FOOTWEAR: No

RESPIRATOR: Self contained above TLV.

ENGINEERING CONTROLS: Use mechanical means to keep concentration below TLV.

LEAK & SPILL PROCEDURE: Remove sources of ignition, ventilate, absorb with absorbent, place in closed container.

WASTE DISPOSAL: Dispose of in accordance with Local, Provincial, and Federal Regulations.

HANDLING PROCEDURES & EQUIPMENT: N.ap

STORAGE REQUIREMENTS: Cool dry area

SPECIAL SHIPPING INFORMATION: Consumer Commodity.

EYES (SPECIFY): Safety glasses

CLOTHING: No

SECTION 8 - FIRST AID MEASURES

1. INHALATION : Remove to fresh air, apply artificial respiration if necessary.

2. EYE : Flush for 15 minutes with large amounts of water.

3. SKIN : Wash affected area with soap and water.

4. INGESTION : **DO NOT INDUCE VOMITING.** Call physician or poison control centre.

SECTION 9 - PREPARATION DATE OF MSDS

PREPARED BY: Michelle Rudnick

PHONE NUMBER: (905) 670-2291

DATE: June 3, 2006

FAX NUMBER: (905) 670-5941