



SAFETY DATA SHEET

1. Identification

Product identifier	Wizard Heavy Duty Silicone	
Other means of identification		
Product code	79827	
Recommended use	Multi-purpose lubricant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufactured or sold by:		
Company name	CRC Canada Co.	
Address	2-1246 Lorimar Dr. Mississauga, Ontario L5S 1R2 Canada	
Telephone	905-670-2291	
Website	www.crc-canada.ca	
E-mail	Support.CA@crcindustries.com	
Emergency phone number	24-Hour Emergency (CHEMTREC)	800-424-9300 (Canada) 703-527-3887 (International)

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wear protective gloves. Wash thoroughly after handling. Avoid release to the environment.
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.
Storage	Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
liquefied petroleum gas		68476-86-8	20 - 30
n-heptane		142-82-5	20 - 30
3-methylhexane		589-34-4	10 - 20
2-methylhexane		591-76-4	5 - 10
heptane, branched, cyclic and linear		426260-76-6	5 - 10
methylcyclohexane		108-87-2	5 - 10
naphtha (petroleum), hydrotreated light		64742-49-0	5 - 10
solvent naphtha (petroleum), light aliph.		64742-89-8	5 - 10
polydimethylsiloxane		63148-62-9	3 - 5
3-ethylpentane		617-78-7	1 - 3
3,3-dimethylpentane		562-49-2	< 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm
3,3-dimethylpentane (CAS 562-49-2)	STEL	500 ppm
	TWA	400 ppm
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
methylcyclohexane (CAS 108-87-2)	STEL	500 ppm
	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
2-methylhexane (CAS 591-76-4)	STEL	2050 mg/m ³
	TWA	500 ppm 1640 mg/m ³

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
3,3-dimethylpentane (CAS 562-49-2)	STEL	400 ppm 2050 mg/m3
	TWA	500 ppm 1640 mg/m3
3-ethylpentane (CAS 617-78-7)	STEL	400 ppm 2050 mg/m3
	TWA	500 ppm 1640 mg/m3
3-methylhexane (CAS 589-34-4)	STEL	400 ppm 2050 mg/m3
	TWA	500 ppm 1640 mg/m3
methylcyclohexane (CAS 108-87-2)	STEL	400 ppm 2050 mg/m3
	TWA	500 ppm 1610 mg/m3
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 ppm 1590 mg/m3
	STEL	400 ppm 2050 mg/m3
n-heptane (CAS 142-82-5)	TWA	500 ppm 1640 mg/m3
	STEL	400 ppm 2050 mg/m3
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 ppm 1590 mg/m3
	STEL	400 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm
3,3-dimethylpentane (CAS 562-49-2)	STEL	500 ppm
	TWA	400 ppm
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
methylcyclohexane (CAS 108-87-2)	STEL	500 ppm
	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
3,3-dimethylpentane (CAS 562-49-2)	STEL	500 ppm
	TWA	400 ppm
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
methylcyclohexane (CAS 108-87-2)	STEL	500 ppm
	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm
3,3-dimethylpentane (CAS 562-49-2)	STEL	500 ppm
	TWA	400 ppm
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
methylcyclohexane (CAS 108-87-2)	STEL	500 ppm
	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
methylcyclohexane (CAS 108-87-2)	TWA	1610 mg/m3
		400 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3
		400 ppm
n-heptane (CAS 142-82-5)	STEL	2050 mg/m3
		500 ppm
	TWA	1640 mg/m3
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		400 ppm
	TWA	1590 mg/m3
		400 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Viton®. Polyvinyl alcohol (PVA).
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Clear.
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-195.9 °F (-126.6 °C) estimated
Initial boiling point and boiling range	149 °F (65 °C) estimated
Flash point	< 0 °F (< -17.8 °C) Tag Closed Cup
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 % estimated
Flammability limit - upper (%)	6.7 % estimated
Vapor pressure	1457 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.66 estimated
Solubility(ies)	
Solubility (water)	Slightly soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	539.6 °F (282 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Percent volatile	96.4 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
---------	---------	--------------

Wizard Heavy Duty Silicone

Acute

Dermal

ATEmix

3502.7497 mg/kg

Components	Species	Test Results
------------	---------	--------------

3-methylhexane (CAS 589-34-4)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Inhalation

LC50

Rat

> 20 mg/l, 4 hours

Oral

LD50

Rat

> 2000 mg/kg

heptane, branched, cyclic and linear (CAS 426260-76-6)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Inhalation

LC50

Rat

> 60 mg/l, 4 hours

Oral

LD50

Rat

> 5000 mg/kg

methylcyclohexane (CAS 108-87-2)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Oral

LD50

Rat

> 4000 mg/kg

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Inhalation

LC50

Rat

61 mg/l, 4 Hours

Oral

LD50

Rat

> 5000 mg/kg

Components	Species	Test Results
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	3000 mg/kg
Inhalation		
LC50	Rat	48000 ppm, 4 hours
Oral		
LD50	Rat	25000 mg/kg
polydimethylsiloxane (CAS 63148-62-9)		
Acute		
Dermal		
LD50	Rabbit	> 2006 mg/kg
Oral		
LD50	Rat	4996 mg/kg
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	3400 ppm, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Product	Species	Test Results
Wizard Heavy Duty Silicone		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia
		1.6895 mg/l, 48 hours estimated
Fish	LC50	Fish
		8.9976 mg/l, 96 hours estimated

Components	Species	Test Results
heptane, branched, cyclic and linear (CAS 426260-76-6)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.5 mg/l, 48 hours
methylcyclohexane (CAS 108-87-2)		
Aquatic		
Fish	LC50	Striped bass (Morone saxatilis) 5.8 mg/l, 96 hours
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia 1 - 10 mg/l, 48 hours
Fish	LC50	Fish 1 - 10 mg/l, 96 hours
n-heptane (CAS 142-82-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.5 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 2.1 - 2.98 mg/l, 96 hours
polydimethylsiloxane (CAS 63148-62-9)		
Aquatic		
Fish	LC50	Channel catfish (Ictalurus punctatus) 2.36 - 4.15 mg/l, 96 hours
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.5 mg/l, 48 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

methylcyclohexane	3.61
n-heptane	4.66

Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light	10 - 25000
---	------------

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products Contents under pressure. Do not puncture, incinerate or crush. Empty container can be recycled. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable, Limited Quantity

Transport hazard class(es)**Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**Environmental hazards** D**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Special provisions** 80**IATA****UN number** UN1950**UN proper shipping name** Aerosols, flammable, Limited Quantity**Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**Environmental hazards** No.**ERG Code** 10L**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Other information****Passenger and cargo aircraft** Allowed with restrictions.**Cargo aircraft only** Allowed with restrictions.**IMDG****UN number** UN1950**UN proper shipping name** AEROSOLS, Limited Quantity**Transport hazard class(es)****Class** 2**Subsidiary risk** -**Packing group** Not applicable.**Environmental hazards****Marine pollutant** No.**EmS** Not available.**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

15. Regulatory information

Canadian regulations**Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	02-03-2017
Version #	01
Further information	CRC # 519B
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..