



MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: CRC® Motor Treatment

Product Number (s): 85316AZ

Product Use: fuel system cleaner

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

In Mexico:

CRC Industries Mexico

Av. Benito Juárez 4055 G

Colonia Orquídea

San Luís Potosí, SLP CP 78394

www.crc-mexico.com

52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Combustible. Harmful or Fatal if Swallowed.

Appearance & Odor: Clear liquid, petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Contact with liquid or vapor may cause mild to moderate irritation, including redness, tearing and stinging. Extensive exposure may cause moderate corneal injury.

SKIN: May cause skin irritation with prolonged or repeated contact. Practically non-toxic if absorbed following a single exposure.

INHALATION: Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure and death.

INGESTION: Moderate toxicity if swallowed. Ingestion may cause gastrointestinal disturbance, including irritation, nausea, vomiting and diarrhea. The major health threat of ingestion occurs from the danger of aspiration of liquid drop into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage and even death.

CHRONIC EFFECTS: In animals, effects have been reported on the blood (hemolysis) and secondary effects on the kidney and liver.

TARGET ORGANS: Central nervous system, kidneys, lungs, liver, blood

Medical Conditions Aggravated by Exposure: Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hydrotreated heavy paraffinic distillate	64742-54-7	45 – 55
Mineral spirits	8052-41-3	30 – 40
2-Butoxy ethanol	111-76-2	10 - 20

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Mouth can be rinsed to dissipate the taste.
- Note to Physicians:* Massive ingestion of 2-butoxyethanol may produce metabolic acidosis and subsequent secondary effects such as hemolysis, central nervous system and kidney effects. Due to structural analogy and clinical data, 2-butoxyethanol may have a mechanism of intoxication similar to ethylene glycol. On that basis, treatment similar to ethylene glycol intoxication may be of benefit.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is a Class II Combustible Liquid.

Flash Point: 117°F / 47°C (TCC)	Upper Explosive Limit: 7.0
Autoignition Temperature: 435°F / 224°C	Lower Explosive Limit: 0.9

Fire and Explosion Data:

- Suitable Extinguishing Media:** Use extinguishers rated for Class B fires, such as dry chemical, fire fighting foam or CO₂.
- Products of Combustion:** Oxides of carbon
- Explosion Hazards:** Containers, when exposed to heat from fire, may build pressure and rupture.
- Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

- Personal Precautions:** Use personal protection recommended in Section 8.
- Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Remove all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from heat, sparks and open flame. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion. Provide adequate ventilation during use. Do not breathe vapors. Avoid contact with skin, eyes and clothing. Wash hands after use. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Containers should be tightly closed while in storage. Store in a well ventilated area. Keep out of reach of children.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Hydrotreated heavy paraffinic distillate	5	NE	5	10	NE		mg/m ³
Mineral spirits	500	NE	100	NE	NE		ppm
2-Butoxy Ethanol	50 (s)	NE	20	NE	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as butyl rubber, nitrile, neoprene or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid
 Color: clear
 Odor: petroleum
 Odor Threshold: ND

Specific Gravity: 0.82
 Initial Boiling Point: 314°F / 157°C
 Freezing Point: ND
 Vapor Pressure: ND
 Vapor Density: 4.7 (air = 1)
 Evaporation Rate: slow
 Solubility: negligible in water
 Coefficient of water/oil distribution: ND
 pH: NA
 Volatile Organic Compounds: wt %: 50 g/L: 410 lbs./gal: 3.4

Section 10: Stability and Reactivity

Stability: Stable
 Conditions to Avoid: Temperature extremes, sources of ignition
 Incompatible Materials: Strong oxidizers, strong acids
 Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, non-combusted hydrocarbons (smoke)
 Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Hydrotreated heavy paraffinic distillate	> 5 g/kg	> 5 g/kg	> 5 mg/L
Mineral spirits	> 5 g/kg	> 3160 mg/kg	No data
2-Butoxy Ethanol	470 mg/kg	220 mg/kg	450 ppm/4H

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Hydrotreated heavy paraffinic distillate	No	No	No	No	No
Mineral spirits	No	No	No	E & S (mild)	Unknown
2-Butoxy Ethanol	No	No	No	E (severe) / S & R (mild)	No

E – Eye S – Skin R - Respiratory

Reproductive Toxicity: No information available
Teratogenicity: No information available
Mutagenicity: Petroleum Distillate: This material has been positive in a mutagenicity study.
Synergistic Effects: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: 2-Butoxy Ethanol - 24 Hr LC50 water flea: 1720 mg/L
 Persistence / Degradability: No information available
 Bioaccumulation / Accumulation: No information available
 Mobility in Environment: Spills may penetrate the soil causing groundwater contamination. This material may accumulate in sediments.

Section 13: Disposal Considerations

Waste Classification: This product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001. (See 40 CFR Part 261.20 – 261.33)
 Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1993, Flammable liquids, N.O.S. (Petroleum distillates & 2-butoxyethanol), 3, PGIII, Limited Quantity**

ICAO/IATA (air): UN1993, Flammable liquids, N.O.S. (Petroleum distillates & 2-butoxyethanol), 3, PGIII, Limited Quantity

IMO/IMDG (water): UN1993, Flammable liquids, N.O.S. (Petroleum distillates & 2-butoxyethanol), 3, PGIII, Limited Quantity

Special Provisions: **This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic ground shipping until December 31, 2014.
 If shipping as limited quantity by ground, note that shipping papers are not required.

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:
Glycol ethers (15%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

Ethylbenzene (< 0.1%)
Naphthalene (< 0.02%)

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: 111-76-2, 64742-54-7
Pennsylvania: 111-76-2
Massachusetts: 111-76-2
Rhode Island : 111-76-2

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: B3, D1A, D1B, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: This fuel additive is registered with the EPA and complies with all standards related to the use in gas or diesel engines.

Section 16: Other Information

HMIS® (II)	
Health:	2
Flammability:	2
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
 CRC #: 864
 Revision Date: 05/29/2015

Changes since last revision: Removed Product Number
 Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists
 CAS: Chemical Abstract Service
 CFR: Code of Federal Regulations
 DOT: Department of Transportation
 DSL: Domestic Substance List
 g/L: grams per Liter
 HMIS: Hazardous Materials Identification System
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 IMO: International Maritime Organization
 lbs./gal: pounds per gallon
 LC: Lethal Concentration
 LD: Lethal Dose

NA: Not Applicable
 ND: Not Determined
 NIOSH: National Institute of Occupational Safety & Health
 NFPA: National Fire Protection Association
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PMCC: Pensky-Martens Closed Cup
 PPE: Personal Protection Equipment
 ppm: Parts per Million
 RoHS: Restriction of Hazardous Substances
 STEL: Short Term Exposure Limit
 TCC: Tag Closed Cup
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Information System