

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

Product Use: Prevents spatter from adhering to surrounding metal surfaces during welding

Manufactured For:

The Easthill Group
Dba The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
www.Eastwood.com

USA & Canada
Outside USA

1-800-345-1178
(610) 323-2200

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

WARNING: Contents Under Pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Appearance & Odor: Milky white emulsion, mild petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Contact may cause mild irritation including stinging, redness and tearing.

SKIN: Contact may cause mild irritation including redness and itching. Prolonged exposure can cause drying or cracking of skin.

INHALATION: Inhalation of small amounts of vapor is not expected to cause health effects. Prolonged or concentrated exposure may lead to irritation of the nose and throat.

INGESTION: Ingestion of small amounts is not expected to cause health effects. Ingestion of larger amounts may lead to stomach ache or nausea.

CHRONIC EFFECTS: None known

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure: pre-existing skin conditions or sensitivities

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Water	7732-18-5	55 - 65
Mixed glycerides	73398-61-5 / 68990-54-5	10 - 15
White mineral oil	8042-47-5	1 - 3
Dimethyl ether	115-10-6	20 - 30

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Call a doctor or poison control center. Keep victim calm.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is nonflammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)).

Flash Point: None
Autoignition Temperature: ND

Upper Explosive Limit: ND
Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: Use Class B extinguishers or an extinguishing agent appropriate for the surrounding fire.

Products of Combustion: Oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Wash hands after using and before consuming food. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing. Store out of reach of children.

Aerosol Storage Level: I

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Water	NE	NE	NE	NE	NE		
White mineral oil	5	NE	5	10	NE		mg/m ³
Mixed glycerides	NE	NE	NE	NE	NE		
Dimethyl ether	NE	NE	NE	NE	1000	AIHA	ppm

N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid emulsion

Color: milky white

Odor: mild petroleum

Odor Threshold: ND

Specific Gravity: 0.8874

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

Initial Boiling Point: ~212°F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: ND (air = 1)

Evaporation Rate: slow

Solubility: soluble in water

Coefficient of water/oil distribution: ND

pH: 7.0 – 8.0

Volatile Organic Compounds: wt %: 25.3 g/L: 224.5 lbs./gal: 1.87

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: None known

Incompatible Materials: Strong oxidizers

Hazardous Decomposition Products: Oxides of carbon

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Water	90 mL/kg	No data	No data
White mineral oil	> 5 g/kg	> 2 g/kg	No data
Mixed glycerides	No data	No data	No data
Dimethyl ether	No data	No data	309 g/m ³ /4H

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Water	No	No	No	No	No
White mineral oil	No	No	No	No	Unknown
Mixed glycerides	No	No	No	No	Unknown
Dimethyl ether	No	No	No	No	Unknown

E – Eye S – Skin R - Respiratory

Reproductive Toxicity: No information available

Teratogenicity: No information available

Mutagenicity: No information available

Synergistic Effects: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

Ecotoxicity: No information available
Persistence / Degradability: Not evaluated.
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is not a RCRA hazardous waste. Pressurized containers may be a D003 reactive waste. (See 40 CFR Part 261.20 – 261.33)
Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Consumer Commodity, ORM-D
ICAO/IATA (air): Consumer Commodity, ID8000, 9
IMO/IMDG (water): Aerosols, UN1950, 2.2, Limited Quantity
Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: 8042-47-5, 141-43-5, 115-10-6
Pennsylvania: 8001-29-4, 8042-47-5, 141-43-5, 115-10-6
Massachusetts: 8042-47-5, 141-43-5, 115-10-6
Rhode Island : 8001-29-4, 8042-47-5, 141-43-5, 115-10-6

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	1
Flammability:	1
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Revision Date: 02/25/2011

Changes since last revision: New product

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of our knowledge or obtained from sources believed to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor or a health & safety professional.

Product Name: Eastwood® Welder's Anti-Spatter (aerosol)

Product Number (s): 12938Z

ACGIH: American Conference of Governmental Industrial Hygienists	NA: Not Applicable
CAS: Chemical Abstract Service	ND: Not Determined
CFR: Code of Federal Regulations	NIOSH: National Institute of Occupational Safety & Health
DOT: Department of Transportation	NFPA: National Fire Protection Association
DSL: Domestic Substance List	NTP: National Toxicology Program
g/L: grams per Liter	OSHA: Occupational Safety and Health Administration
HMIS: Hazardous Materials Identification System	PMCC: Pensky-Martens Closed Cup
IARC: International Agency for Research on Cancer	PPE: Personal Protection Equipment
IATA: International Air Transport Association	ppm: Parts per Million
ICAO: International Civil Aviation Organization	RoHS: Restriction of Hazardous Substances
IMDG: International Maritime Dangerous Goods	STEL: Short Term Exposure Limit
IMO: International Maritime Organization	TCC: Tag Closed Cup
lbs./gal: pounds per gallon	TWA: Time Weighted Average
LC: Lethal Concentration	WHMIS: Workplace Hazardous Materials Information System
LD: Lethal Dose	