



# Material Safety Data Sheet

## Section 1: Product & Company Identification

**Product Name:** NAPA/CRC® Guaranteed To Pass® Emissions Test Formula

**Product Number (s):** 091836

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

|                            |                |
|----------------------------|----------------|
| General Information        | (215) 674-4300 |
| Technical Assistance       | (800) 521-3168 |
| Customer Service           | (800) 272-8963 |
| 24-Hr Emergency (CHEMTREC) | (800) 424-9300 |

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Light amber liquid, petroleum odor

### DANGER

Combustible. Harmful or Fatal if Swallowed.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

### Potential Health Effects:

- EYE:** Contact with liquid or vapor may cause mild to moderate irritation.
- SKIN:** May cause skin irritation with prolonged or repeated contact. Practically non-toxic if absorbed following a single exposure.
- INHALATION:** Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure and death.
- INGESTION:** Ingestion may cause gastrointestinal disturbance, including irritation, nausea, vomiting and diarrhea. The major health threat of ingestions occurs from the danger of aspiration of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage and even death.
- CHRONIC EFFECTS:** Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly exposed.
- TARGET ORGANS:** Central nervous system

### Medical Conditions Aggravated by Exposure:

Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

---

### **Section 3: Composition/Information on Ingredients**

| <b>COMPONENT</b>                      | <b>CAS NUMBER</b> | <b>% by Wt.</b> |
|---------------------------------------|-------------------|-----------------|
| Petroleum Distillate                  | 68476-34-6        | 25 - 35         |
| Sweetened middle petroleum distillate | 64741-86-2        | 25 - 35         |
| Polyether amine                       | Proprietary       | 25 - 35         |
| Solvent naphtha                       | 64742-94-5        | < 5             |
| Naphthalene                           | 91-20-3           | < 1             |

---

### **Section 4: First Aid Measures**

**Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

**Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

**Ingestion:** Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Mouth can be rinsed to dissipate the taste.

*Note to Physicians:* Treat symptomatically.

---

### **Section 5: Fire-Fighting Measures**

**Flammable Properties:** In accordance with OSHA definitions, this product is a combustible liquid.

|                           |             |                        |     |
|---------------------------|-------------|------------------------|-----|
| Flash Point:              | 187 F (TCC) | Upper Explosive Limit: | 7.5 |
| Autoignition Temperature: | 494 F       | Lower Explosive Limit: | 0.6 |

**Suitable Extinguishing Media:** Use extinguishers rated for Class B fires, such as dry chemical, Halon, fire fighting foam or CO2.

**Products of Combustion:** Oxides of carbon

**Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

**Section 6: Accidental Release Measures**

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Remove all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

**Section 7: Handling and Storage**

Handling Procedures: Keep away from heat, sparks and open flame. Open container in a well-ventilated area and provide adequate ventilation during use. Do not breathe vapors. Keep container closed when not in use. Wash hands after use.

Storage Procedures: Store in a cool dry area out of direct sunlight. Store in a well ventilated area. Keep out of reach of children.

Aerosol Storage Level: NA

**Section 8: Exposure Controls/Personal Protection**

Exposure Guidelines:

| COMPONENT  | OSHA |       | ACGIH   |      | OTHER |        | UNIT              |
|--|------|-------|---------|------|-------|--------|-------------------|
|  | TWA  | STEL  | TWA     | STEL | TWA   | SOURCE |                   |
| Petroleum distillate   | 5    | NE    | 100 (s) | NE   | NE    |        | mg/m <sup>3</sup> |
| Sweetened middle petroleum distillate  | NE   | NE    | NE      | NE   | NE    |        |                   |
| Polyether amine  | NE   | NE    | NE      | NE   | NE    |        |                   |
| Solvent naphtha  | NE   | NE    | NE      | NE   | NE    |        |                   |
| Naphthalene  | 10   | 15(v) | 10      | 15   | NE    |        | ppm               |
| N.E. – Not Established      (c) – ceiling      (s) – skin      (v) – vacated |      |       |         |      |       |        |                   |

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use NIOSH-approved cartridge respirators with organic vapor cartridge if vapors exceed exposure limits. Use self-contained breathing apparatus for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, neoprene or PVC. Also , use full protective clothing if

**Product Name: NAPA/CRC® Guaranteed to Pass® Emissions Test Formula**

**Product Number (s): 091836**

there is prolonged or repeated contact of liquid with skin.

---

**Section 9: Physical and Chemical Properties**

Physical State: liquid

Color: Light amber

Odor: Petroleum

Specific Gravity: 0.87

Initial Boiling Point: 320 F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: < 1 (ether = 1)

Solubility: Negligible in water

pH: NA

Volatile Organic Compounds:     wt %:   47                     g/L:   408.9                     lbs./gal:   3.41

---

**Section 10: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: temperature extremes, sources of ignition

Incompatible Materials: Strong oxidizers, Viton®, Fluorel®, strong acids

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, non-combusted hydrocarbons (smoke). Propylamine, polyalkylglycols, and aliphatic alcohols may also be released.

Possibility of Hazardous Reactions: No

---

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

**ACUTE EFFECTS**

| <u>Component</u>            | <u>Test</u> | <u>Result</u> | <u>Route</u> | <u>Species</u> |
|-----------------------------|-------------|---------------|--------------|----------------|
| Petroleum Distillate        | LD50        | 9 ml/kg       | Oral         | Rat            |
| Sweetened middle distillate | LC50        | 4.6 mg/L/4H   | Inhalation   | Rat            |
| Sweetened middle distillate | LD50        | > 2000 mg/kg  | Dermal       | Rabbit         |

**CHRONIC EFFECTS**

Carcinogenicity:

|       | <u>Component</u> | <u>Result</u>                             |
|-------|------------------|---|
| OSHA: | Naphthalene      | Hazard communication carcinogen           |
| IARC: | Naphthalene      | 2B – Possibly carcinogenic                |
| NTP:  | Naphthalene      | Reasonably anticipated to be a carcinogen |

Mutagenicity: Petroleum Distillate This material has been positive in a mutagenicity study.

---

## **Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

|                                 |   |
|---------------------------------|---|
| Ecotoxicity:                    | Naphthalene -- 48 Hr EC50 water flea: 2.16 mg/L   |
| Persistence / Degradability:    | No information available  |
| Bioaccumulation / Accumulation: | Some ingredients of this product have the potential for Bioconcentration.                                   |
| Mobility in Environment:        | Spills may penetrate the soil causing groundwater contamination. This material may accumulate in sediments. |

---

## **Section 13: Disposal Considerations**

Disposal: This product is a RCRA hazardous waste for the toxicity characteristic: D018 (1.4 mg/L Benzene).  
(See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

## **Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: None

---

## **Section 15: Regulatory Information**

### **U.S. Federal**

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Naphthalene (100 lbs)

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

|                                    |                       |     |
|------------------------------------|-----------------------|-----|
| Section 311/312 Hazard Categories: | Fire Hazard           | Yes |
|                                    | Reactive Hazard       | No  |
|                                    | Release of Pressure   | No  |
|                                    | Acute Health Hazard   | Yes |
|                                    | Chronic Health Hazard | Yes |

**Product Name: NAPA/CRC® Guaranteed to Pass® Emissions Test Formula**  
**Product Number (s): 091836**

---

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
Naphthalene (0.2%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Naphthalene

**State Regulations**

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: Naphthalene (0.2%), Benzene (1.4 ppm)

State Right to Know:

New Jersey: 91-20-3, 800967-5491P, 800967-5502P, 800967-5485P  
Pennsylvania: 91-20-3  
Massachusetts: 91-20-3  
Rhode Island : 91-20-3

**Additional Regulatory Information:** None

---

**Section 16: Other Information**

|       |           |                 |               |        |
|-------|-----------|-----------------|---------------|--------|
| NFPA: | Health: 2 | Flammability: 2 | Reactivity: 0 |        |
| HMIS: | Health: 2 | Flammability: 2 | Reactivity: 0 | PPE: B |

Prepared By: Michelle Rudnick  
CRC #: 425F  
Revision Date: 10/13/2005

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

|       |  |           |                           |
|-------|--|-----------|---------------------------|
| CAS:  | Chemical Abstract Service                                  | NA:       | Not Applicable            |
| ppm:  | Parts per Million  | ND:       | Not Determined            |
| TCC:  | Tag Closed Cup   | NE:       | Not Established           |
| PMCC: | Pensky-Martens Closed Cup                                  | g/L:      | grams per Liter           |
| PPE:  | Personal Protection Equipment                              | lbs./gal: | pounds per gallon         |
| TWA:  | Time Weighted Average                                      | STEL:     | Short Term Exposure Limit |
| OSHA: | Occupational Safety and Health Administration              |           |                           |
| ACGIH | American Association of Governmental Industrial Hygienists |           |                           |
| NIOSH | National Institute of Occupational Safety & Health         |           |                           |