CRC

SAFETY DATA SHEET

1. Identification

Product identifier BMW Non-Chlorinated Brake Parts Cleaner

Other means of identification

Product Code No. 09554 (Item# 1004595)

Recommended use Brake cleaner Recommended restrictionsNone known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard

Category 1

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Category 1

Hazardous to the aquatic environment,

long-term hazard

Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting

effects.

Precautionary statement Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves and eye/face protection. Avoid release to the environment.

Material name: BMW Non-Chlorinated Brake Parts Cleaner
No. 09554 (Item# 1004595) Version #: 03 Revision date: 12-29-2017 Issue date: 05-07-2015

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention. Collect spillage.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	40 - 50
n-heptane		142-82-5	10 - 20
3-methylhexane		589-34-4	5 - 10
carbon dioxide		124-38-9	5 - 10
2-methylhexane		591-76-4	3 - 5
heptane, branched, cyclic and linear		426260-76-6	3 - 5
methylcyclohexane		108-87-2	3 - 5
naphtha (petroleum), hydrotreated light		64742-49-0	3 - 5
solvent naphtha (petroleum), light aliph.		64742-89-8	3 - 5
3-ethylpentane		617-78-7	1 - 3
3,3-dimethylpentane		562-49-2	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

cymptome may be acayear

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam

Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide,

sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Material name: BMW Non-Chlorinated Brake Parts Cleaner

No. 09554 (Item# 1004595) Version #: 03 Revision date: 12-29-2017 Issue date: 05-07-2015 2 / 12

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Many vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m3	

Material name: BMW Non-Chlorinated Brake Parts Cleaner

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
		500 ppm	
naphtha (petroleum),	PEL	400 mg/m3	
nydrotreated light (CAS	I LL	400 mg/m3	
34742-49-0)			
14742-49-0)		100 nnm	
	DE:	100 ppm	
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
solvent naphtha	PEL	400 mg/m3	
petroleum), light aliph.		3	
CAS 64742-89-8)			
•		100 ppm	
JS. ACGIH Threshold Limit Values			
Components	Туре	Value	
2-methylhexane (CAS	STEL	500 ppm	
591-76-4)	OTEL	300 ррш	
79 1-7 0 -4)	TWA	400 ppm	
0.0.1			
3,3-dimethylpentane (CAS	STEL	500 ppm	
562-49-2)	T14/4	400	
	TWA	400 ppm	
3-ethylpentane (CAS	STEL	500 ppm	
617-78-7)			
	TWA	400 ppm	
3-methylhexane (CAS	STEL	500 ppm	
589-34-4)		Pro-	
,	TWA	400 ppm	
acetona (CAS 67 64 1)	STEL		
acetone (CAS 67-64-1)		500 ppm	
	TWA	250 ppm	
carbon dioxide (CAS	STEL	30000 ppm	
124-38-9)			
	TWA	5000 ppm	
nethylcyclohexane (CAS	STEL	500 ppm	
108-87-2)		Pro-	
	TWA	400 ppm	
hontono (CAS 142 92 5)	STEL	500 ppm	
n-heptane (CAS 142-82-5)			
	TWA	400 ppm	
JS. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Type	Value	
•			
acetone (CAS 67-64-1)	TWA	590 mg/m3	
acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm	
		250 ppm	
carbon dioxide (CAS	TWA STEL	-	
carbon dioxide (CAS		250 ppm 54000 mg/m3	
carbon dioxide (CAS	STEL	250 ppm 54000 mg/m3 30000 ppm	
carbon dioxide (CAS		250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3	
carbon dioxide (CAS 124-38-9)	STEL	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm	
carbon dioxide (CAS 24-38-9) nethylcyclohexane (CAS	STEL	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS	STEL	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS	STEL	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2)	STEL	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2) naphtha (petroleum),	STEL TWA TWA	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2) naphtha (petroleum), nydrotreated light (CAS	STEL TWA TWA	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2) naphtha (petroleum), nydrotreated light (CAS	STEL TWA TWA	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3 400 ppm 400 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2) maphtha (petroleum), nydrotreated light (CAS 134742-49-0)	STEL TWA TWA TWA	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3 400 ppm 400 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2) naphtha (petroleum), nydrotreated light (CAS 64742-49-0)	STEL TWA TWA	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3 400 ppm 400 mg/m3	
methylcyclohexane (CAS 108-87-2) maphtha (petroleum), mydrotreated light (CAS 142-82-5)	STEL TWA TWA TWA Ceiling	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3 400 ppm 400 mg/m3	
carbon dioxide (CAS 124-38-9) methylcyclohexane (CAS 108-87-2) naphtha (petroleum), nydrotreated light (CAS 64742-49-0)	STEL TWA TWA TWA	250 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 1600 mg/m3 400 ppm 400 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

ComponentsTypeValuesolvent naphthaTWA400 mg/m3

(petroleum), light aliph. (CAS 64742-89-8)

100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.

Other Wear appropriate chemical resistant clothing.

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormAerosol.

Color Clear. Colorless.

Odor Solvent.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -195.9 °F (-126.6 °C) estimated Initial boiling point and boiling 132.9 °F (56.1 °C) estimated

range

Flash point < 0 °F (< -17.8 °C) Tag Closed Cup

Evaporation rate Fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 1.1 % estimated

(%)

Flammability limit - upper 12.8 % estimated

(%)

Vapor pressure 4832.3 hPa estimated

Vapor density 2 (air = 1)

Relative density 0.8 estimated

Solubility(ies)

Solubility (water) Slightly soluble.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

539.6 °F (282 °C) estimated

Decomposition temperature Not available. **Percent volatile** 91.4 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Aldehydes. Alkalies. Amines. Ammonia. Halogens. Peroxides. Reducing agents. Strong

acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
0		

3-methylhexane (CAS 589-34-4)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 2000 mg/kg

acetone (CAS 67-64-1)

Acute

Dermal

LD50 Rabbit 20000 mg/kg

Oral

LD50 Rat 5800 mg/kg

heptane, branched, cyclic and linear (CAS 426260-76-6)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 60 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Material name: BMW Non-Chlorinated Brake Parts Cleaner

SDS US

No. 09554 (Item# 1004595) Version #: 03 Revision date: 12-29-2017 Issue date: 05-07-2015

Species Components **Test Results**

methylcyclohexane (CAS 108-87-2)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

n-heptane (CAS 142-82-5)

Acute **Dermal**

LD50 Rabbit 3000 mg/kg

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

a

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting,

may cause chemical pneumonia, pulmonary injury or death.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects. C

Components		Species	Test Results
acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

Material name: BMW Non-Chlorinated Brake Parts Cleaner

7 / 12 No. 09554 (Item# 1004595) Version #: 03 Revision date: 12-29-2017 Issue date: 05-07-2015

^{*} Estimates for product may be based on additional component data not shown.

Components **Test Results Species**

heptane, branched, cyclic and linear (CAS 426260-76-6)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

methylcyclohexane (CAS 108-87-2)

Aquatic

Fish LC50 Striped bass (Morone saxatilis) 5.8 mg/l, 96 hours

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Aquatic

Acute

Crustacea EC50 Daphnia 1 - 10 mg/l, 48 hours LC50 Fish Fish 1 - 10 mg/l, 96 hours

n-heptane (CAS 142-82-5)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 2.1 - 2.98 mg/l, 96 hours

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Aquatic

Fish LC50 Rainbow trout.donaldson trout 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

-0.24acetone 3.61 methylcyclohexane n-heptane 4.66

Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light 10 - 25000

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This material and its container must be disposed of as hazardous waste. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not

puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

D001: Waste Flammable material with a flash point <140 F Hazardous waste code

F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN1950 **UN number**

UN proper shipping name

Aerosols, flammable, Limited Quantity

Transport hazard class(es)

2.1 Class Subsidiary risk

^{*} Estimates for product may be based on additional component data not shown.

Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulk304Packaging bulkNone

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Allowed with restrictions.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

aft

Cargo aircraft only IMDG

UN number UN1950

UN proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

Class 2

Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Marine pollutant No. S F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

3,3-dimethylpentane (CAS 562-49-2) Listed. acetone (CAS 67-64-1) Listed.

CERCLA Hazardous Substances: Reportable quantity

3,3-dimethylpentane (CAS 562-49-2) 100 LBS acetone (CAS 67-64-1) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Material name: BMW Non-Chlorinated Brake Parts Cleaner

SDS US

Safe Drinking Water Act Not regulated. (SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority

Not regulated. Food and Drug

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Gas under pressure categories Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. Massachusetts RTK - Substance List

2-methylhexane (CAS 591-76-4)

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. Pennsylvania Worker and Community Right-to-Know Law

2-methylhexane (CAS 591-76-4)

3,3-dimethylpentane (CAS 562-49-2)

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. Rhode Island RTK

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

SDS US



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0)
Listed: April 1, 1988
benzene (CAS 71-43-2)
Listed: February 27, 1987
cumene (CAS 98-82-8)
Listed: April 6, 2010
ethylbenzene (CAS 100-41-4)
naphthalene (CAS 91-20-3)
Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

acetone (CAS 67-64-1)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Inventory name

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 44.9 %

51.100(s))

Consumer products

Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products This product is regulated as a Brake Cleaner. This product is not compliant to be sold for use in

California, Delaware, Maryland, New Hampshire, and the following counties in Utah: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber. This product is compliant in all other states.

VOC content (CA) 44.9 % **VOC content (OTC)** 44.9 %

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Toxic Chemical Substances (TCS)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

country(s).

16. Other information, including date of preparation or last revision

Issue date05-07-2015Revision date12-29-2017Prepared byAllison Yoon

On inventory (yes/no)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Version # 03

Further information CRC # 920/1002913

HMIS® ratings Health: 2

Flammability: 4 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 4 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information

Product and Company Identification: Product Codes

Hazard(s) identification: Prevention Hazard(s) identification: Response

Composition/information on ingredients: Component information

Handling and storage: Precautions for safe handling Exposure controls/personal protection: Hand protection Physical and chemical properties: Oxidizing properties Physical and chemical properties: Explosive properties

Transport Information: Agency Name, Packaging Type, and Transport Mode Selection

Regulatory information: California Prop 65 Regulatory information: Consumer products

Other information, including date of preparation or last revision: Further information

Material name: BMW Non-Chlorinated Brake Parts Cleaner

No. 09554 (Item# 1004595) Version #: 03 Revision date: 12-29-2017 Issue date: 05-07-2015 12 / 12