



Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Webseal 36 (bulk)

Product Number (s): 09704

Manufactured By:

CRC Industries, Inc.
885 Louis Drive
Warminster, PA 18974
www.crcindustries.com

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-4620
24-Hr Emergency (CHEMTREC)	(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Red, slightly viscous liquid, petroleum odor

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

- EYE:** Contact may cause mild irritation including stinging, watering and redness.
- SKIN:** Contact may cause redness, itching, burning and skin damage. Prolonged or repeated contact can worsen irritation and lead to dermatitis. No harmful effects from skin absorption are expected.
- INHALATION:** Expected to have a low degree of toxicity by inhalation. High concentrations of vapors may be irritating to the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, and other central nervous system effects.
- INGESTION:** Ingestion may cause gastrointestinal discomfort. Although unlikely due to the viscosity, small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
- CHRONIC EFFECTS:** None known
- TARGET ORGANS:** None known

Medical Conditions Aggravated by Exposure:

pre-existing dermatitis

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Solvent-refined heavy paraffinic distillates	64741-88-4	85 - 95
Fatty acids, tall oil, monoesters with sorbitan	61791-48-8	2 - 5
n-Butyl stearate	123-95-5	2 - 5
Inhibitor blend	proprietary	2 - 5

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** If swallowed, do NOT induce vomiting. Keep at rest. Get prompt medical attention.
- Note to Physicians:** This product may cause an aspiration hazard. Careful gastric lavage or emesis may be considered to evacuate large quantities of this material. Subcutaneous or intramuscular injection requires prompt surgical debridement.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is a Class IIIB combustible liquid (not regulated).

Flash Point:	350 F (COC)	Upper Explosive Limit:	ND
Autoignition Temperature:	ND	Lower Explosive Limit:	ND

Suitable Extinguishing Media: Foam, dry chemical, carbon dioxide or water spray.

Products of Combustion: Oxides of carbon

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Remove sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Avoid water contamination to minimize product degradation. Wash hands after use and before handling food. Keep containers closed when not in use.

Storage Procedures: Store in a cool dry area out of direct sunlight. Keep containers properly closed while in storage. Keep out of reach of children.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Solvent-refined heavy paraffinic distillates	5*	NE	5*	10*	NE		mg/m ³
Fatty acids, tall oil, monoesters with sorbitan	NE	NE	NE	NE	NE		
n-Butyl stearate	NE	NE	NE	NE	NE		
Inhibitor blend	NE	NE	NE	NE	NE		
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated *- oil mist							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: Liquid
Color: Red
Odor: Petroleum
Specific Gravity: 0.866
Initial Boiling Point: > 600 F
Freezing Point: ND
Vapor Pressure: < 0.1 mmHg @ 68 F
Vapor Density: > 1 (air = 1)
Evaporation Rate: ND (butyl acetate = 1)
Solubility: negligible in water
pH: NA
Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./gal: 0

Section 10: Stability and Reactivity

Stability: Stable
Conditions to Avoid: Temperature extremes, sources of ignition
Incompatible Materials: Strong oxidizing agents
Hazardous Decomposition Products: Oxides of carbon, oxides of sulfur, hydrocarbons
Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Heavy paraffinic distillate	LD50	> 5 g/kg	Oral	Rat
Heavy paraffinic distillate	LD50	> 2 g/kg	Dermal	Rabbit
Heavy paraffinic distillate	LC50	2.18 mg/L/4H	Inhalation	Rat

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	None listed	
IARC:	None listed	
NTP:	None listed	

Other: Paraffinic distillates Product testing using IP 346 shows a DMSO PAH content of < 3% by weight.

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available
Persistence / Degradability: No information available
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Disposal: This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: None
Pennsylvania: None
Massachusetts: None
Rhode Island : None

Additional Regulatory Information: None

Section 16: Other Information

NFPA: Health: 1 Flammability: 1 Reactivity: 0
HMIS: Health: 1 Flammability: 1 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick
CRC #: 539B
Revision Date: 02/14/2007

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		