



SAFETY DATA SHEET

1. Identification

| | |
|---|---|
| Product identifier | Acura Glass Cleaner |
| Other means of identification | |
| Product code | 08700-9217A (CRC# 09987) |
| Recommended use | Glass cleaner |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Company name | CRC Industries, Inc. |
| Address | 885 Louis Dr. Warminster, PA 18974 US |
| Telephone | |
| General Information | 215-674-4300 |
| Technical Assistance | 800-521-3168 |
| Customer Service | 800-272-4620 |
| 24-Hour Emergency (CHEMTREC) | 800-424-9300 (US) 703-527-3887 (International) |
| Website | www.crcindustries.com |

2. Hazard(s) identification

| | | |
|------------------------------|--|---------------|
| Physical hazards | Gases under pressure | Liquefied gas |
| Health hazards | Not classified. | |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 3 |
| | Hazardous to the aquatic environment, long-term hazard | Category 3 |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



| | |
|--|---|
| Signal word | Warning |
| Hazard statement | Contains gas under pressure; may explode if heated. Harmful to aquatic life with long lasting effects. |
| Precautionary statement | |
| Prevention | Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. Avoid release to the environment. |
| Response | Wash hands after handling. |
| Storage | Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. |
| Disposal | Dispose of contents/container in accordance with local/regional/national regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|----------------------|---------------------------------|-------------------|----------|
| water | | 7732-18-5 | 80 - 90 |

| Chemical name | Common name and synonyms | CAS number | % |
|-------------------------|--------------------------|------------|--------|
| liquefied petroleum gas | | 68476-86-8 | 5 - 10 |
| 2-butoxyethanol | | 111-76-2 | 1 - 3 |
| ethanol | | 64-17-5 | 1 - 3 |
| ammonia | | 7664-41-7 | < 1 |
| methanol | | 67-56-1 | < 0.2 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Call a POISON CENTER or doctor/physician. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire-fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. |
| General fire hazards | Contents under pressure. Pressurized container may rupture when exposed to heat or flame. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|--------------------------------------|--|
| Precautions for safe handling | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label. |
|--------------------------------------|--|

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|--------------------------------|------|------------|
| 2-butoxyethanol (CAS 111-76-2) | PEL | 240 mg/m3 |
| | | 50 ppm |
| ammonia (CAS 7664-41-7) | PEL | 35 mg/m3 |
| | | 50 ppm |
| ethanol (CAS 64-17-5) | PEL | 1900 mg/m3 |
| | | 1000 ppm |
| methanol (CAS 67-56-1) | PEL | 260 mg/m3 |
| | | 200 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|--------------------------------|------|----------|
| 2-butoxyethanol (CAS 111-76-2) | TWA | 20 ppm |
| ammonia (CAS 7664-41-7) | STEL | 35 ppm |
| | TWA | 25 ppm |
| ethanol (CAS 64-17-5) | STEL | 1000 ppm |
| methanol (CAS 67-56-1) | STEL | 250 ppm |
| | TWA | 200 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|--------------------------------|------|------------|
| 2-butoxyethanol (CAS 111-76-2) | TWA | 24 mg/m3 |
| | | 5 ppm |
| ammonia (CAS 7664-41-7) | STEL | 27 mg/m3 |
| | | 35 ppm |
| | TWA | 18 mg/m3 |
| | | 25 ppm |
| ethanol (CAS 64-17-5) | TWA | 1900 mg/m3 |
| | | 1000 ppm |
| methanol (CAS 67-56-1) | STEL | 325 mg/m3 |
| | | 250 ppm |
| | TWA | 260 mg/m3 |
| | | 200 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|--------------------------------|----------|--|---------------------|---------------|
| 2-butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |
| methanol (CAS 67-56-1) | 15 mg/l | Methanol | Urine | * |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

2-butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.
 methanol (CAS 67-56-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-butoxyethanol (CAS 111-76-2)
 methanol (CAS 67-56-1)

Skin designation applies.
 Skin designation applies.

US - Tennessee OELs: Skin designation

2-butoxyethanol (CAS 111-76-2)
 methanol (CAS 67-56-1)

Can be absorbed through the skin.
 Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

methanol (CAS 67-56-1)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-butoxyethanol (CAS 111-76-2)
 methanol (CAS 67-56-1)

Can be absorbed through the skin.
 Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Wear protective gloves such as: Nitrile. Rubber.

Other

Wear suitable protective clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Aerosol.

Color

Clear.

Odor

Ammoniacal.

Odor threshold

Not available.

pH

10.5

Melting point/freezing point

Not available.

Initial boiling point and boiling range

212 °F (100 °C) estimated

Flash point

None.

Evaporation rate

Slow.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

1.3 % estimated

Flammability limit - upper (%)

25 % estimated

Vapor pressure

280.3 hPa estimated

Vapor density

> 1 (air = 1)

Relative density

0.97 estimated

Solubility (water)

Soluble.

| | |
|--|---------------------------|
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 446 °F (230 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity (kinematic) | Not available. |
| Percent volatile | 99.6 % estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Heat, flames and sparks. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | Carbon oxides. Aldehydes. Ketones. Organic acids. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Expected to be a low ingestion hazard. |

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

| Components | Species | Test Results |
|-------------------|----------------|---------------------|
|-------------------|----------------|---------------------|

2-butoxyethanol (CAS 111-76-2)

Acute

Dermal

| | | |
|------|--------|--------------|
| LD50 | Rabbit | > 2000 mg/kg |
|------|--------|--------------|

Oral

| | | |
|------|-----|------------|
| LD50 | Rat | 1300 mg/kg |
|------|-----|------------|

ammonia (CAS 7664-41-7)

Acute

Inhalation

| | | |
|------|-----|-------------------|
| LC50 | Rat | 2000 ppm, 4 Hours |
|------|-----|-------------------|

Oral

| | | |
|------|-----|-----------|
| LD50 | Rat | 350 mg/kg |
|------|-----|-----------|

ethanol (CAS 64-17-5)

Acute

Dermal

| | | |
|------|--------|---------|
| LD50 | Rabbit | 20 g/kg |
|------|--------|---------|

Inhalation

| | | |
|------|-----|--------------------|
| LC50 | Rat | 8000 mg/l, 4 hours |
|------|-----|--------------------|

Oral

| | | |
|------|-----|----------|
| LD50 | Rat | 6.2 g/kg |
|------|-----|----------|

| Components | Species | Test Results |
|------------------------|---------|--------------------|
| methanol (CAS 67-56-1) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 12800 mg/kg |
| Inhalation | | |
| LC50 | Rat | 64000 ppm, 4 hours |
| Oral | | |
| LD50 | Rat | 5628 mg/kg |

* Estimates for product may be based on additional component data not shown.

| | |
|---|--|
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | Not classifiable as to carcinogenicity to humans. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | |
| 2-butoxyethanol (CAS 111-76-2) | 3 Not classifiable as to carcinogenicity to humans. |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | |
| Not regulated. | |
| US. National Toxicology Program (NTP) Report on Carcinogens | |
| Not listed. | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not classified. |
| Chronic effects | May be harmful if absorbed through skin. Prolonged inhalation may be harmful. |
| | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

| Components | Species | Test Results |
|--------------------------------|---------|--|
| 2-butoxyethanol (CAS 111-76-2) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) |
| | | 1550 mg/l, 48 hours |
| | | >= 1000 mg/l, 96 hours |
| ammonia (CAS 7664-41-7) | | |
| Aquatic | | |
| Fish | LC50 | Chinook salmon (Oncorhynchus tshawytscha) |
| | | 0.43 - 0.47 mg/l, 96 hours |
| ethanol (CAS 64-17-5) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| | | 7.7 - 11.2 mg/l, 48 hours |

| Components | Species | Test Results |
|--------------------------------|---------|---|
| Fish methanol (CAS 67-56-1) | LC50 | Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) > 10000 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|-----------------|---------------|
| 2-butoxyethanol | 0.81, log Pow |
| ethanol | -0.31 |
| methanol | -0.77 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, non-flammable, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.2 |
| Subsidiary risk | - |
| Label(s) | 2.2 |
| Packing group | Not applicable. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

IATA

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, non-flammable, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.2 |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| ERG Code | 2L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed with restrictions. |
| Cargo aircraft only | Allowed with restrictions. |

IMDG

| | |
|--------------------------------|----------------------------|
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS, LIMITED QUANTITY |

| | |
|-------------------------------------|---|
| Transport hazard class(es) | |
| Class | 2 |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | Not available. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

15. Regulatory information

| | | |
|--|--|--------------|
| US federal regulations | All components are on the U.S. EPA TSCA Inventory List. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. | |
| TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) | Not regulated. | |
| US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | Not listed. | |
| SARA 304 Emergency release notification | Not regulated. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | Not regulated. | |
| US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance | 2-butoxyethanol (CAS 111-76-2) | |
| CERCLA Hazardous Substance List (40 CFR 302.4) | 2-butoxyethanol (CAS 111-76-2) | Listed. |
| CERCLA Hazardous Substances: Reportable quantity | Not listed. Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee. | |
| Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List | Not regulated. | |
| Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) | Not regulated. | |
| Safe Drinking Water Act (SDWA) | Not regulated. | |
| FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace | ethanol (CAS 64-17-5) | Low priority |
| Food and Drug Administration (FDA) | Not regulated. | |
| Superfund Amendments and Reauthorization Act of 1986 (SARA) | | |
| Section 311/312 | Immediate Hazard - No | |
| Hazard categories | Delayed Hazard - No Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No | |
| SARA 302 Extremely hazardous substance | No | |
| US state regulations | | |
| US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) | 2-butoxyethanol (CAS 111-76-2) ammonia (CAS 7664-41-7) liquefied petroleum gas (CAS 68476-86-8) methanol (CAS 67-56-1) | |
| US. New Jersey Worker and Community Right-to-Know Act | 2-butoxyethanol (CAS 111-76-2) ammonia (CAS 7664-41-7) | |

ethanol (CAS 64-17-5)
methanol (CAS 67-56-1)

US. Massachusetts RTK - Substance List

2-butoxyethanol (CAS 111-76-2)
ammonia (CAS 7664-41-7)
ethanol (CAS 64-17-5)
methanol (CAS 67-56-1)

US. Pennsylvania Worker and Community Right-to-Know Law

2-butoxyethanol (CAS 111-76-2)
ammonia (CAS 7664-41-7)
ethanol (CAS 64-17-5)
methanol (CAS 67-56-1)

US. Rhode Island RTK

2-butoxyethanol (CAS 111-76-2)
ammonia (CAS 7664-41-7)
ethanol (CAS 64-17-5)
methanol (CAS 67-56-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

methyl isobutyl ketone (CAS 108-10-1) Listed: November 4, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

methanol (CAS 67-56-1) Listed: March 16, 2012

methyl isobutyl ketone (CAS 108-10-1) Listed: March 28, 2014

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) 9.6 %

Consumer products (40 CFR 59, Subpt. C) Compliant

State

Consumer products This product is regulated as a Glass Cleaner (aerosol). This product is compliant for use in all 50 states.

VOC content (CA) 9.6 %

VOC content (OTC) 9.6 %

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-24-2014

Revision date 05-11-2017
Prepared by Allison Cho
Version # 02
Further information CRC # 411A
HMIS® ratings Health: 1
Flammability: 0
Physical hazard: 0
Personal protection: B
NFPA ratings Health: 1
Flammability: 0
Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision Information

This document has undergone significant changes and should be reviewed in its entirety.