



# CHEMICAL PRODUCT SAFETY DATA SHEET

Prepared in accordance with GB/T 16483 and GB/T 17519.

Company name: CRC Industries Trading (Shanghai) Co., Ltd. Product name: Power Lube High Performance Lubricant w/PTFE

Issue date: 03-10-2017

Version #: 01

SDS No: -

## 1. Chemical product and company identification

<b>Product name</b>	<b>Power Lube High Performance Lubricant w/PTFE</b>
<b>Product code</b>	PR03045
<b>Company name</b>	CRC Industries Trading (Shanghai) Co., Ltd.
<b>Address</b>	Room 2408, No. 488 South Wuning Road Jingan District - 200042 Shanghai, PR China
<b>General Information</b>	+86 (0) 21 6236 6035
<b>24-Hour Emergency</b>	+86 532 83889090
<b>Website</b>	www.crcindustries.cn

### Recommended use and Limitations on use

<b>Recommended use</b>	Multi-purpose lubricant
<b>Issue date</b>	03-10-2017

## 2. Hazards identification

### Emergency overview

Aerosol. CONTENTS UNDER PRESSURE.  
Pressurized container may rupture when exposed to heat or flame. May be fatal if swallowed and enters airways. May be harmful in contact with skin. Causes serious eye irritation. Causes mild skin irritation. Possible reproductive hazard. Dangerous for the environment if discharged into watercourses.

### GHS-classification

<b>Physical hazards</b>	Aerosols	Category 1
<b>Health hazards</b>	Acute toxicity, dermal	Category 5
	Skin corrosion/irritation	Category 3
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (fertility)	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>Other hazards which do not result in classification</b>	Not classified.	

### Label elements

#### Pictograms



### GHS-labeling

#### Signal word

Danger

#### Hazard statement

Extremely flammable aerosol. Pressurized container: May burst if heated. May be fatal if swallowed and enters airways. May be harmful in contact with skin. Causes mild skin irritation. Causes serious eye irritation. Suspected of damaging fertility. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment.
<b>Response</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
<b>Storage</b>	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Physical and chemical hazards</b>	Extremely flammable aerosol. The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Health hazards</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May be harmful in contact with skin. No adverse effects due to inhalation are expected. Prolonged inhalation may be harmful. Causes serious eye irritation.
<b>Environmental hazards</b>	Harmful to aquatic life with long lasting effects.

**3. Composition/information on ingredients**

Substance/mixture	Mixture	Concentration (%)	CAS Number
distillates (petroleum), hydrotreated light		30 - 40	64742-47-8
liquefied petroleum gas		10 - 20	68476-86-8
paraffin oils (petroleum), catalytic dewaxed heavy		10 - 20	64742-70-7
methyl salicylate		3 - 5	119-36-8
paraffin oils (petroleum), catalytic dewaxed light		3 - 5	64742-71-8
sorbitan monooleate		3 - 5	1338-43-8
sorbitan monotallate		3 - 5	61791-48-8
2-methylpentane		1 - 3	107-83-5
fatty acids, C18-unsatd., dimers		1 - 3	61788-89-4
naphtha (petroleum), hydrotreated light		1 - 3	64742-49-0
petrolatum		1 - 3	8009-03-8
sodium petroleum sulfonate		1 - 3	68608-26-4
distillates (petroleum), hydrotreated heavy naphthenic		< 1	64742-52-5
distillates (petroleum), solvent-refined heavy paraffinic		< 1	64741-88-4
n-hexane		< 0.3	110-54-3

**4. First aid measures**

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms and health effects</b>	Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Mild skin irritation.
<b>Expected acute symptoms and delayed symptoms</b>	Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Mild skin irritation.
<b>Personal protection for first-aid responders</b>	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

**Notes to physician** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire-fighting measures

**Extinguishing media** Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO<sub>2</sub>).

**Extinguishing media to avoid** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards** Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

**Special fire fighting procedures** Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.

**Protection of fire-fighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**General fire hazards** Extremely flammable aerosol.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**For emergency responders** Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**Clean-up methods and materials and containment measures** Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Prevention of secondary hazards** Not available.

## 7. Handling and storage

**Handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

**Storage** Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Exposure limits

**China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007)**

Components	Type	Value
n-hexane (CAS 110-54-3)	PC-STEL	180 mg/m <sup>3</sup>
	PC-TWA	100 mg/m <sup>3</sup>

**Biological limit values**

**China. Biological limit values for occupational exposure (WS/T 110 to 115, 239 to 243, and 264 to 267)**

Components	Value	Determinant	Specimen	Sampling Time
n-hexane (CAS 110-54-3)	4 mg/l	2,5-Hexanedione	Urine	*
	35 mmol/l	2,5-Hexanedione	Urine	*

\* - For sampling details, please see the source document.

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
n-hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007): Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Control parameters** Follow standard monitoring procedures.

**Engineering measures** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

**Personal protective equipment**

**Respiratory protection** If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Hand protection** Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).

**Eye protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear appropriate chemical resistant clothing.

**Hygiene measures** Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

**Appearance**

**Physical state** Liquid.  
**Form** Aerosol.  
**Color** Amber. White precipitate.

**Odor** Wintergreen.

**pH** Not available.

**Melting point/freezing point** -112 °F (-80 °C) estimated

**Boiling point, initial boiling point, and boiling range** 118.4 °F (48 °C) estimated

**Flash point** < 20 °F (< -6.7 °C) Tag Closed Cup

**Flammability limit - lower (%)** 0.6 % estimated

**Flammability limit - upper (%)** 14 % estimated

**Explosive limit - lower (%)** 0.6 %

**Explosive limit - upper (%)** 14 %

**Vapor pressure** 1078.2 hPa estimated

<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.8 estimated
<b>Density</b>	6.7 lbs/gal estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	404.6 °F (207 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Evaporation rate</b>	Fast.
<b>Other data</b>	
<b>Percent volatile</b>	86.9 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Aldehydes. Ketones. Organic acids.

## 11. Toxicological information

**Acute toxicity** May be fatal if swallowed and enters airways. May be harmful in contact with skin.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg > 25 ml/kg
distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	7.6 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
fatty acids, C18-unsatd., dimers (CAS 61788-89-4)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
methyl salicylate (CAS 119-36-8)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	887 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	61 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
n-hexane (CAS 110-54-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 1300 mg/kg
<b>Inhalation</b>		
LC50	Rat	< 48000 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	15840 mg/kg
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
petrolatum (CAS 8009-03-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
sodium petroleum sulfonate (CAS 68608-26-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
sorbitan monooleate (CAS 1338-43-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	39800 mg/kg
sorbitan monotallate (CAS 61791-48-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	39800 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Symptoms</b>	Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Mild skin irritation.
<b>Skin corrosion/irritation</b>	Causes mild skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	3 Not classifiable as to carcinogenicity to humans.
polytetrafluoroethylene (CAS 9002-84-0)	3 Not classifiable as to carcinogenicity to humans.
<b>Toxic to reproduction</b>	Suspected of damaging fertility.
<b>Specific target organ toxicity following single exposure</b>	Not classified.
<b>Specific target organ toxicity following repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.

## 12. Ecological information

Ecotoxicological data Components	Species	Test Results
2-methylpentane (CAS 107-83-5)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50 Daphnia	1 - 10 mg/l, 48 hours
Fish	LC50 Fish	1 - 10 mg/l, 96 hours
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia magna)	1000 mg/l, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	5000 mg/l, 96 hours
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours

Components	Species	Test Results
fatty acids, C18-unsatd., dimers (CAS 61788-89-4)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Carp (Cyprinus carpio) > 350 mg/l, 96 hours
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia 1 - 10 mg/l, 48 hours
Fish	LC50	Fish 1 - 10 mg/l, 96 hours
n-hexane (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia > 100 mg/l, 48 hours
sorbitan monooleate (CAS 1338-43-8)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) > 1000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Ecotoxicity** Harmful to aquatic life with long lasting effects.  
**Persistence and degradability** No data is available on the degradability of this product.  
**Bioaccumulation**

Bioaccumulative potential	
<b>Bioconcentration factor</b>	
naphtha (petroleum), hydrotreated light	10 - 25000
<b>Octanol/water partition coefficient log Kow</b>	
2-methylpentane	3.74
methyl salicylate	2.55
n-hexane	3.9

**Mobility in soil** No data available for this product.  
**Other hazardous effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

### 13. Disposal considerations

**Residual waste** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.  
**Local disposal regulations** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

### 14. Transport information

**CNDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.



**IATA**


**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards** No.  
**ERG Code** 10L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-D, S-U  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**CNDG; IMDG**



**IATA**



**15. Regulatory information**

**Inventory of Existing Chemical Substances in China**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## Applicable regulations

This safety data sheet conforms to the following laws, regulations and standards:  
Regulations on the Control over Safety of Dangerous Chemicals  
Regulations on Labor Protection in Workplaces Where Toxic Products Are Used  
Measures for the Safe Use of Chemicals in Workplaces  
Safety Data Sheet for Chemical Products - Content and Order of Sections (GB/T 16483-2008)  
General Rules for Preparation of Precautionary Labels for Chemicals (GB15258-2009 )  
Packing Symbol of Dangerous Goods(GB190-2009)  
Packing - Pictorial Marking for Handling of Goods (GB/T191-2009)

## General Rule For Classification and Hazard Communication of Chemicals (GB 13690-2009) and Catalog of Hazardous Chemicals

2-methylpentane (CAS 107-83-5)  
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-hexane (CAS 110-54-3)

## Occupational exposure limits for hazardous agents in the workplace (GBZ 2.1-2007)

n-hexane (CAS 110-54-3)

## National Catalogue of Hazardous Wastes

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)  
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)  
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)  
petrolatum (CAS 8009-03-8)

## Restricted Import/Export Toxic Chemical List (MEP and GCA Announcement No. 2008-66, Dec. 1, 2008, amended through MEP and Customs Notice No. 2013-85, December 30, 2013)

Not regulated.

## Identification of Major Hazard Installations for Hazardous Chemicals (GB18218-2009)

n-hexane (CAS 110-54-3)

## List Of Priority Management of Hazardous Chemicals

distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

## Classification and code of dangerous goods (GB 6944-2012)

Regulated.

## List of Dangerous Goods (GB 12268-2005)

Regulated.

## The Principle of Classification of Transport Packaging Groups of Dangerous Goods (GB/T15098-2008)

Regulated.

## General Specifications for Transport Packages of Dangerous Goods (GB 12463-2009)

Regulated.

## Regulations on Road Transport of Dangerous Goods

Regulated.

## Regulations on Rail Road Transport of Dangerous Goods

Regulated.

## UN Recommendations on the Transport of Dangerous Goods (UN RTDG)

Regulated.

---

## 16. Other information

### References

EPA: AQUIRE database  
NLM: Hazardous Substances Data Base  
US. IARC Monographs on Occupational Exposures to Chemical Agents

### Further information

CRC # 494K-L

### Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Trading (Shanghai) Co., Ltd..