



CHEMICAL PRODUCT SAFETY DATA SHEET

Prepared in accordance with GB/T 16483 and GB/T 17519.

Product name: Dielectric Grease

Issue date: 12-20-2016
Revision date: 08-29-2017
Version #: 02
SDS No: -

SECTION 1 Chemical product and company identification

Product name	Dielectric Grease
Product code	No. PR03082 (Item# 1007690)
Manufactured or sold by:	
Company name	CRC Industries Trading (Shanghai) Co., Ltd.
Address	Room 1710, No. 488 South Wuning Road Jingan District - 200042 Shanghai, PR China
General Information	+86 21 6236 6035
24-Hour Emergency	+86 532 83889090
Website	www.crcindustries.cn
Recommended use and Limitations on use	
Recommended use	Lubricating and insulating electrical components
Issue date	12-20-2016
Revision date	08-29-2017
Supersedes date	12-20-2016

SECTION 2 Hazards identification

Emergency overview	Aerosol. CONTENTS UNDER PRESSURE. Pressurized container may rupture when exposed to heat or flame. May be fatal if swallowed and enters airways. May be harmful in contact with skin. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness and dizziness. Causes eye irritation. Causes skin irritation. Possible reproductive hazard. Dangerous for the environment if discharged into watercourses.
---------------------------	---

GHS-classification		
Physical hazards	Aerosols	Category 1
Health hazards	Acute toxicity, dermal	Category 5
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
Other hazards which do not result in classification	Not classified.	

Label elements

Pictograms



GHS-labeling

Signal word Danger

Hazard statement

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statement**Prevention**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist or vapor.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P391	Collect spillage.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Physical and chemical hazards

Extremely flammable aerosol. The product is stable and non-reactive under normal conditions of use, storage and transport.

Health hazards

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May be harmful in contact with skin. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Causes skin irritation. Causes eye irritation.

Environmental hazards

Very toxic to aquatic life with long lasting effects.

SECTION 3 Composition/information on ingredients

Substance/mixture	Mixture	
Chemical name	Concentration (%)	CAS Number
liquefied petroleum gas	20 - 30	68476-86-8
n-heptane	10 - 20	142-82-5
2-methylpentane	5 - 10	107-83-5
naphtha (petroleum), hydrotreated light	5 - 10	64742-49-0
polydimethylsiloxane	5 - 10	63148-62-9
3-methylhexane	3 - 5	589-34-4

Chemical name

2-methylhexane	1 - 3	591-76-4
methylcyclohexane	1 - 3	108-87-2
n-hexane	1 - 3	110-54-3
solvent naphtha (petroleum), light aliph.	1 - 3	64742-89-8
3-ethylpentane	< 1	617-78-7
3,3-dimethylpentane	< 0.3	562-49-2

SECTION 4 First aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms and health effects	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Expected acute symptoms and delayed symptoms	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Personal protection for first-aid responders	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
Notes to physician	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5 Fire-fighting measures

Extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO ₂).
Extinguishing media to avoid	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
Protection of fire-fighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
General fire hazards	Extremely flammable aerosol.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Clean-up methods and materials and containment measures

Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Prevention of secondary hazards

Not available.

SECTION 7 Handling and storage**Handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Storage

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8 Exposure controls/personal protection**Exposure limits****China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007)**

Components	Type	Value
n-heptane (CAS 142-82-5)	PC-STEL	1000 mg/m ³
	PC-TWA	500 mg/m ³
n-hexane (CAS 110-54-3)	PC-STEL	180 mg/m ³
	PC-TWA	100 mg/m ³

Biological limit values**China. Biological limit values for occupational exposure (WS/T 110 to 115, 239 to 243, and 264 to 267)**

Components	Value	Determinant	Specimen	Sampling Time
n-hexane (CAS 110-54-3)	4 mg/l	2,5-Hexanedione	Urine	*
	35 mmol/l	2,5-Hexanedione	Urine	*

* - For sampling details, please see the source document.

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
n-hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007): Skin designation**

N-HEXANE (CAS 110-54-3)

Can be absorbed through the skin.

Monitoring methods

Follow standard monitoring procedures.

Engineering measures

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Personal protective equipment

Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Hand protection	Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.
Eye protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear appropriate chemical resistant clothing.

Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
-------------------------	---

SECTION 9 Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Aerosol.
Color	Translucent. Opaque.
Odor	Solvent.
pH	Not available.
Melting point/freezing point	-244.7 °F (-153.7 °C) estimated
Boiling point, initial boiling point, and boiling range	118.4 °F (48 °C) estimated
Flash point	< 20 °F (< -6.7 °C) Tag Closed Cup
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	8 % estimated
Explosive limit - lower (%)	1 % estimated
Explosive limit - upper (%)	8 % estimated
Vapor pressure	1528.1 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.66 estimated
Density	Not available.
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	489.2 °F (254 °C) estimated
Decomposition temperature	Not available.
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Other data	
Percent volatile	90.1 %

SECTION 10 Stability and reactivity

Stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong reducing agents. Strong acids. Strong bases. Halogens. Peroxides.
Hazardous decomposition products	Carbon oxides. Hydrocarbons.

SECTION 11 Toxicological information

Acute toxicity	May be fatal if swallowed and enters airways. May be harmful in contact with skin.
-----------------------	--

Components	Species	Test Results
3-methylhexane (CAS 589-34-4)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 2000 mg/kg
methylcyclohexane (CAS 108-87-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 4000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	3000 mg/kg
n-hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 1300 mg/kg
Oral		
LD50	Rat	15840 mg/kg
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg

* Estimates for product may be based on additional component data not shown.

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
Symptoms	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes eye irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Respiratory or skin sensitization	
Skin sensitizer	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not available.
Toxic to reproduction	Suspected of damaging fertility.
Specific target organ toxicity following single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity following repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	May cause damage to organs through prolonged or repeated exposure.

SECTION 12 Ecological information

Ecotoxicological data

Components	Species		Test Results
2-methylpentane (CAS 107-83-5)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1 - 10 mg/l, 48 hours
Fish	LC50	Fish	1 - 10 mg/l, 96 hours
methylcyclohexane (CAS 108-87-2)			
Aquatic			
Fish	LC50	Striped bass (<i>Morone saxatilis</i>)	5.8 mg/l, 96 hours
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1 - 10 mg/l, 48 hours
Fish	LC50	Fish	1 - 10 mg/l, 96 hours
n-heptane (CAS 142-82-5)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1.5 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	2.1 - 2.98 mg/l, 96 hours
n-hexane (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	2.101 - 2.981 mg/l, 96 hours
polydimethylsiloxane (CAS 63148-62-9)			
Aquatic			
Fish	LC50	Channel catfish (<i>Ictalurus punctatus</i>)	2.36 - 4.15 mg/l, 96 hours
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)			
Aquatic			
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
<i>Acute</i>			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1.5 mg/l, 48 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulation	

Bioaccumulative potential

Bioconcentration factor

naphtha (petroleum), hydrotreated light 10 - 25000

Octanol/water partition coefficient log Kow

2-methylpentane 3.74
 methylcyclohexane 3.61
 n-heptane 4.66
 n-hexane 3.9

Mobility in soil	This product is miscible in water.
Other hazardous effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13 Disposal considerations

Residual waste	Dispose of contents/container in accordance with local/regional/national/international regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Local disposal regulations Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

SECTION 14 Transport information

CNDG

UN number UN1950
UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 Label(s) 2.1
Packing group Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1950
UN proper shipping name Aerosols, flammable, Limited Quantity
Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
Packing group Not available.
Environmental hazards No.
ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
 Passenger and cargo aircraft Allowed with restrictions.
 Cargo aircraft only Allowed with restrictions.


IMDG

UN number UN1950
UN proper shipping name AEROSOLS, Limited Quantity
Transport hazard class(es)
 Class 2
 Subsidiary risk -
Packing group Not available.
Environmental hazards
 Marine pollutant No.
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.


CNDG



IATA



IMDG



SECTION 15 Regulatory information

Inventory of Existing Chemical Substances in China

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Applicable regulations

This safety data sheet conforms to the following laws, regulations and standards:
 Regulations on the Control over Safety of Dangerous Chemicals
 Regulations on Labor Protection in Workplaces Where Toxic Products Are Used
 Measures for the Safe Use of Chemicals in Workplaces
 Safety Data Sheet for Chemical Products - Content and Order of Sections (GB/T 16483-2008)
 General Rules for Preparation of Precautionary Labels for Chemicals (GB15258-2009)
 Packing Symbol of Dangerous Goods(GB190-2009)
 Packing - Pictorial Marking for Handling of Goods (GB/T191-2009)

General Rule For Classification and Hazard Communication of Chemicals (GB 13690-2009) and Catalog of Hazardous Chemicals

2-methylhexane (CAS 591-76-4)
 2-methylpentane (CAS 107-83-5)
 3,3-dimethylpentane (CAS 562-49-2)
 3-ethylpentane (CAS 617-78-7)
 3-methylhexane (CAS 589-34-4)
 methylcyclohexane (CAS 108-87-2)
 naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
 n-heptane (CAS 142-82-5)
 n-hexane (CAS 110-54-3)
 solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Occupational exposure limits for hazardous agents in the workplace (GBZ 2.1-2007)

n-heptane (CAS 142-82-5)
 n-hexane (CAS 110-54-3)

Restricted Import/Export Toxic Chemical List (MEP and GCA Announcement No. 2008-66, Dec. 1, 2008, amended through MEP and Customs Notice No. 2013-85, December 30, 2013)

Not regulated.

Identification of Major Hazard Installations for Hazardous Chemicals (GB18218-2009)

n-hexane (CAS 110-54-3)

List Of Priority Management of Hazardous Chemicals

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
 solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Classification and code of dangerous goods (GB 6944-2012)

Regulated.

List of Dangerous Goods (GB 12268-2005)

Regulated.

The Principle of Classification of Transport Packaging Groups of Dangerous Goods (GB/T15098-2008)

Regulated.

General Specifications for Transport Packages of Dangerous Goods (GB 12463-2009)

Regulated.

Regulations on Road Transport of Dangerous Goods

Regulated.

Regulations on Rail Road Transport of Dangerous Goods

Regulated.

UN Recommendations on the Transport of Dangerous Goods (UN RTDG)

Regulated.

SECTION 16 Other information**References**

EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents

Further information

CRC # 438A-B/1002424-1002425

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Trading (Shanghai) Co., Ltd..

Revision Information

Product and Company Identification: Product Codes
SECTION 8 Exposure controls/personal protection: Hand protection
Physical & Chemical Properties: Multiple Properties
SECTION 16 Other information: Further information
GHS: Classification