



CHEMICAL PRODUCT SAFETY DATA SHEET

Prepared in accordance with GB/T 16483 and GB/T 17519.

Product name: 5-56® Multi-Purpose Lubricant

Issue date: 11-03-2014
Revision date: 11-05-2018
Version #: 06
SDS No: -

SECTION 1 Chemical product and company identification

Product name	5-56® Multi-Purpose Lubricant
Product Code	PR05005CR
Manufactured or sold by:	
Company name	CRC Industries Trading (Shanghai) Co., Ltd.
Address	Room 1710, No. 488 South Wuning Road Jingan District - 200042 Shanghai, PR China
General Information	+86 21 6236 6035
24-Hour Emergency	+86 532 83889090
Website	www.crcindustries.cn

Recommended use and Limitations on use

Recommended use	Multi-purpose lubricant
Issue date	11-03-2014
Revision date	11-05-2018
Supersedes date	04-27-2018

SECTION 2 Hazards identification

Emergency overview	Aerosol. CONTENTS UNDER PRESSURE. Pressurized container may rupture when exposed to heat or flame. May be fatal if swallowed and enters airways. May be harmful in contact with skin. May cause genetic defects.
---------------------------	---

Hazard categories

Physical hazards	Aerosols	Category 1
Health hazards	Acute toxicity, dermal	Category 5
	Germ cell mutagenicity	Category 1B
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	

Label elements

Pictograms



Signal word

Danger

Hazard statement

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H340	May cause genetic defects.

Precautionary statement

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor if you feel unwell.

Storage

P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Physical and chemical hazards Extremely flammable aerosol. The product is stable and non-reactive under normal conditions of use, storage and transport.

Health hazards Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May be harmful in contact with skin. Prolonged inhalation may be harmful. Direct contact with eyes may cause temporary irritation.

Environmental hazards The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Supplemental information None.

SECTION 3 Composition/information on ingredients

Substance/mixture	Mixture		
Chemical name		Concentration (%)	CAS Number
distillates (petroleum), hydrotreated light		40 - 50	64742-47-8
liquefied petroleum gas		30 - 40	68476-85-7
white mineral oil		10 - 20	8042-47-5
sorbitan monooleate		1 - 3	1338-43-8

SECTION 4 First aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms and health effects Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhea.

Personal protection for first-aid responders IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Notes to physician Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5 Fire-fighting measures

Extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Extinguishing media to avoid Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Protection of fire-fighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

General fire hazards Extremely flammable aerosol.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Clean-up methods and materials and containment measures Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Prevention of secondary hazards Not available.

SECTION 7 Handling and storage

Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Storage Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8 Exposure controls/personal protection

Exposure limits

China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007)

Components	Type	Value
liquefied petroleum gas (CAS 68476-85-7)	PC-STEL	1500 mg/m ³
	PC-TWA	1000 mg/m ³

Biological limit values No biological exposure limits noted for the ingredient(s).

Monitoring methods Follow standard monitoring procedures.

Engineering measures Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Hand protection Wear protective gloves such as: Nitrile. Neoprene.

Eye protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear appropriate chemical resistant clothing.

Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
-------------------------	---

SECTION 9 Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Amber.
Odor	Mild petroleum.
pH	Not available.
Melting point/freezing point	80.6 °F (27 °C) estimated
Boiling point, initial boiling point, and boiling range	Not available.
Flash point	177 °F (80.6 °C) estimated
Flammability limit - lower (%)	0.5 % estimated
Flammability limit - upper (%)	5.5 % estimated
Explosive limit - lower (%)	0.5 % estimated
Explosive limit - upper (%)	5.5 % estimated
Vapor pressure	1476.8 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.81 - 0.83 (without propellant)
Density	6.75 - 6.94 lbs/gal (without propellant)
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Other data	
Percent volatile	93.6 % estimated

SECTION 10 Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11 Toxicological information

Acute toxicity May be fatal if swallowed and enters airways. May be harmful in contact with skin.

Components	Species	Test Results
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5.2 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg, 2.5 hours

Components	Species	Test Results
sorbitan monooleate (CAS 1338-43-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 hours
Oral		
LD50	Rat	39800 mg/kg
white mineral oil (CAS 8042-47-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5 mg/l, 4 hours
Chronic		
Oral		
LD50	Rat	> 5000 mg/kg
Routes of exposure	Inhalation. Ingestion. Skin contact.	
Symptoms	Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhea.	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitizer	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	May cause genetic defects.	
Carcinogenicity		
IARC Monographs. Overall Evaluation of Carcinogenicity		
white mineral oil (CAS 8042-47-5)	3 Not classifiable as to carcinogenicity to humans.	
Toxic to reproduction	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity following single exposure	Not classified.	
Specific target organ toxicity following repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	

SECTION 12 Ecological information

Ecotoxicological data			
Product	Species		Test Results
5-56® Multi-Purpose Lubricant			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1010.3397 mg/l, 48 hours estimated
Fish	LC50	Fish	6878.3066 ppm, 96 hours estimated
Components	Species		Test Results
distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	> 1000 mg/l, 96 hours

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulation	
Mobility in soil	This product is miscible in water.
Other hazardous effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13 Disposal considerations

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
Local disposal regulations	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14 Transport information

CNDG



UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

CNDG; IMDG**IATA****SECTION 15 Regulatory information****Law of the People's Republic of China on Prevention and Control of Occupational Diseases**

Not regulated.

Regulations on the Control over Safety of Dangerous Chemicals**Catalog of Hazardous Chemicals**

Petroleum gases, liquefied (CAS 68476-85-7)

Petroleum gases, liquefied

Interim Provisions on the Supervision and Management of Major Hazards of Dangerous Chemicals GB 18218-2008**Identification of major hazard installations for dangerous chemicals**

liquefied petroleum gas (CAS 68476-85-7)

List of Priority Management of Hazardous Chemicals

liquefied petroleum gas (CAS 68476-85-7)

Measures for the Environmental Management Registration of Hazardous Chemicals (for Trial Implementation)

Not regulated.

Regulations on Labor Protection in Workplaces Where Toxic Substances Are Used**Regulations for Environmental Management On the First Import of Chemicals and the Import and Export of Toxic Chemicals****Provision on the Environmental Administration of New Chemical Substances****Inventory of Existing Chemical Substances in China**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Other regulations

This safety data sheet conforms to the following laws, regulations and standards:

Regulations on the Control over Safety of Dangerous Chemicals

Regulations on Labor Protection in Workplaces Where Toxic Products Are Used

Measures for the Safe Use of Chemicals in Workplaces

Safety Data Sheet for Chemical Products - Content and Order of Sections (GB/T 16483-2008)

General Rules for Preparation of Precautionary Labels for Chemicals (GB15258-2009)

Packing Symbol of Dangerous Goods(GB190-2009)

Packing - Pictorial Marking for Handling of Goods (GB/T191-2009)

China. National Catalogue of Hazardous Wastes

white mineral oil (CAS 8042-47-5)

List of Priority Management of Hazardous Chemicals

liquefied petroleum gas (CAS 68476-85-7)

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Montreal Protocol

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

SECTION 16 Other information**References**

EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Trading (Shanghai) Co., Ltd..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.