



I. Product Description

Cable Glide™ “All Season” Cable Pulling Lubricant combines the lubricating power of Teflon® with a water-based gel to create a lubricant that goes on smooth, clings firmly and significantly reduces friction. The unique viscosity of the “All Season” gel allows **Cable Glide™** to be applied by hand, cloth or brush without falling off cables before they enter conduit.

II. Applications

Recommended to lubricate high voltage, telecommunication and fiber optic cable or electrical wire during pulls through metal and plastic conduit. Recommended for inside or outside use.

III. Features & Benefits

- **Contains Teflon®.** Friction is minimized for an easier pull.
- **Water-Based Gel.** Product remains soft and will not harden in conduit.
- **Lubricates Without Use of Wax.** Eases addition, removal and re-pull of cables.
- **Does Not Contain Dyes.** Will not stain clothing, fabrics or skin.
- **Water Soluble.** Quick, easy clean-up with soap and water.
- **Exceptional Freeze/Thaw Stability.** Maintains lubricating efficiency in extreme weather conditions.
- **Functions Below 15° F.** Conditions permitting.
- **Wide Temperature Stability.** Performs in both high and low temperature ranges.
- **Non-Conductive After Application.** Increases user safety.
- **Does Not Contain Silicones or Grease.** Non-damaging to insulation or jacketing materials.
- **Versatile.** Safe for use on all cable and conduit materials.

IV. Physical Properties

Flash Point	None
Odor	Slight alcohol
Appearance	Blue Gelatinous Liquid
Vapor Density	Not Determined
VOC Content (Fed)	159 g/L
Sara Title III, Sect. 313 Chemicals	Yes
Prop 65	No

Boiling Point	210°F
Solubility	Soluble in H ₂ O
% Volatile	99
Specific Gravity	1.00
pH	8.0 ± 1
Temperature Range	15°F - 119°F

* Federal VOC content measured in percentage by weight

V. Specifications and Approvals

- Underwriter’s Laboratories Listed - 21C6 Wire Pulling Compound

VI. Performance Characteristics

Brookfield Viscosity (40° F - 100°F)	10% Change
--------------------------------------	------------

VII. Directions

- Always read entire label before using product.
- When possible, pour **Cable Glide™** into conduit or pipe to pre-lubricate surface.
- Apply **Cable Glide™** directly to wire or cable by hand, brush or cloth. Apply liberally to fully coat wire or cable. Remove excess to leave a thin, light film.
- Continue to apply as cable is drawn into conduit.
- Amount of **Cable Glide™** necessary will vary depending upon the length and number of bends in pull.
- Remove excess from electrical contacts to maintain maximum operating efficiency. Do not apply while cables are energized.

VIII. Package Description

Part Number	Container Size
14151	1 Gallon Bottle

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

Teflon® is a registered trademark of DuPont Corporation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260