



I. Product Description

Aviation Quick Dry Precision Cleaner is a unique blend of petroleum distillates and alcohol which provides a suitable precision cleaner for sensitive electronics and electrical equipment. **Aviation Quick Dry Precision Cleaner** is a cost effective alternative to all contact cleaners. **Aviation Quick Dry Precision Cleaner** evaporates quickly, leaves no residue and is safe for use on all plastics. For use where flammable solvents are accepted.

II. Applications

Recommended for effective removal of dirt, dust, light oils and fingerprints from avionics, printed circuit boards, switches, motors, relays, generators, edge connectors, circuit breakers, fusible connecting devices, terminals, rheostats, aircraft instrumentation and communications equipment.

III. Features & Benefits

- **Plastic Safe.** Allows one product to be used in all applications without risk of costly damage to sensitive modern plastics.
- **Lower VOC's.**
- **Fast Evaporation.** Minimizes downtime associated with "clean-in-place" cleaning methods.
- **Leaves No Residue.** No rinsing or wiping required.
- **Contains No Class I or Class II Ozone Depleting Chemicals.** Offers effective performance while complying with the EPA regulations on the use of ozone depleting chemicals.,
- **M.S.D.[L.]™ Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	<0°F TCC	Boiling Point	140°F (initial)
Odor	Alcohol	Solubility	Neg. in H ₂ O
Appearance	Clear liquid	% Volatile	100%
Vapor Density	>1 (air = 1)	Specific Gravity	0.661
VOC Content	495 g/l, 75%	Propellant	HFC-152a
Sara Title III, Sect 313 Chemicals	Yes	Vapor Pressure	164 mmHg @ 68°F
Prop 65	No	Freezing Point	<-76°F

V. Specifications and Approvals

- Passes test requirements for Boeing D6-17487.
- Passes test requirements for ASTM F-484. (Test method for safety on Acrylic plastics).

VI. Performance Characteristics

ASTM D-56 (Flash Point)	<0°F
ASTM D-877 (Dielectric Strength)	36,700 volts
ASTM D-1130 (KB Value)	27

VII. Directions

- Spray liberally on surface to be cleaned and allow to run off.
- Use of an abrasive on heavy carbon deposits or corrosion will accelerate cleaning.
- Do not use on energized equipment.
- Allow to dry thoroughly and vent before reactivating system.
- Follow routine maintenance schedule for prolonged equipment life and increased performance.

VIII. Package Description

Part Number	Container Size
10340	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.