



I. Product Description

CRC Wire Pulling Lubricant with Teflon® is an economical, general purpose, medium viscosity lubricant for pulling electrical cables, fiber optics and Datacom wires through conduit at nominal temperature ranges. Wetting agents, Teflon® and freeze point suppressants combine to ease cable pulling. The Teflon® additive package significantly reduces the force needed to pull cable through tight conduit and around corners.

II. Applications

Recommended for use on all types of cable and jacketing to maintain superior lubricity throughout the entire pull.

III. Features & Benefits

- **Colorless.** Non-staining gel hastens clean-up.
- **Teflon® Additive.** Eases cable installation, leaving a thin coat which, when dry, substantially eases cable removal.
- **Contains No Wax.** Product will not stain, and when dried, will not increase drag during cable removal like wax-based products. It will not harden or crust in storage.
- **Wide Temperature Range.** Excellent freeze – thaw stability.
- **Water Wash-Off.** Easily cleans up with soap and water. Non-staining to skin or clothing.

IV. Physical Properties

Flash Point	None	Boiling Point	210° F
Odor	Mild alcohol	Solubility	Soluble in water
Appearance	Colorless, gelatinous liquid	% Volatile	98.5%
Vapor Density	Not applicable	Specific Gravity	0.996
VOC Content (Fed)	59 g/L	Temperature Range	23° F to 210° F
Sara Title III, Sect. 313 Chemicals	Methanol	Freeze Point	Approximately 23°F
Prop 65	No	pH	8.0=/.5

V. Specifications and Approvals

- Underwriters Laboratories (UL) Listed.

VI. Performance Characteristics

Type of Film	Non-hardening
Coefficient of Friction	0.067

VII. Directions

- Apply directly to the cable by hand or brush.
- Can also be used to lubricate conduit.
- Soap and water cleanup, non-staining.

VIII. Package Description

Part Number	Container Size
02099	1 Gallon Bottle
02100	5 Gallon Pail

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Do not take internally. If product comes in contact with eyes or mouth, flush with water. Wash hands thoroughly after handling. Keep container closed.

TEFLON® is a registered trademark of DuPont Corporation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260