



I. Product Description

CRC Rust Proof Enamel Spray Paint is a premium grade spray paint formulated for industrial applications where maximum indoor/ outdoor coating performance is required. **CRC Rust Proof Enamel** fights weathering, salt spray and the most severe and demanding conditions. Hides well, dries fast and resists chipping and peeling.

II. Applications

Recommended for use on iron, steel, wood and aluminum. For best results and highest durability, use **CRC Rust Proof Enamel Spray Paint** in conjunction with **CRC Rust Proof Enamel Primer**.

III. Features & Benefits

- **Will Not Fade.** Hard, durable finish is long-lasting, premium quality.
- **Excellent Resistance to Abrasion, Corrosion, and Solvents.** Lengthens time between repainting.
- **Enamel Formulation.** Offers gloss, durability, and flexibility superior to lacquer.
- **Fast Drying.** Reduces down time associated with slower-drying coatings.
- **S.D.[L.][®]-Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**
- **20 oz. aerosol** can size.
- **Inhibits rust** and resists heat and gasoline.

IV. Physical Properties with propellant

Resin System	Chain Stopped Alkyd	Heat Resistance	300°F
Flash Point	-2°F(-19°C)	Propellant	Hydrocarbon
Odor and Appearance	Aromatic	Solids Content	18%
Vapor Density	>1 (air=1)	VOC Content (Fed) (Wt.)	65% maximum
Sara Title III, Sect. 313 Chemicals	Yes	% Volatile	45-48
Prop 65	Yes		

V. Performance Characteristics

Dry Time, Tack Free	30 minutes
Dry Time, Fully Dry	2 hours
Recoat	Before 1 hour or after 48 hours
Square Foot Coverage	25 to 40 square feet

VI. Directions

- Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants
- Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.
- For best results, spray at 50°F to 90°F.
- Mask areas not to be sprayed to protect from overspray.
- Hold can 8 to 10 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
- For best results several light thin coats are recommended rather than one heavy coat. Recoat within 1 hour or after 48 hours. This time varies with curing temperature, humidity, and film thickness.
- To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.

VII. Package Description

The Occupational Safety and Health Act (OSHA) stipulates that industrial plants provide color coded safety equipment in the workplace. OSHA also requires that hazardous areas be identified with certain colors. CRC provides a wide range of OSHA colors for the correct application and safety.

Rust Proof Enamel Spray Paint

18100	OSHA Red	18106	OSHA White
18101	OSHA Yellow	18109	Flat Black
18102	OSHA Blue	18114	Machinery Light Gray
18105	OSHA Black		

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn.

Some state and local agencies may require that aerosol paints be sold from locked cages or other specialized displays in order to conform to local anti-graffiti regulations. Check with local authorities to ensure compliance with existing regulations. CRC can provide locked cages to aid in conformance to anti-graffiti legislation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.