



I. Product Description

CRC Striping and Traffic Spray Paints are designed to provide the high hide and durability required for high traffic striping jobs. These superior striping paints are formulated with a high solids formula to give you thick, even coverage.

II. Applications

Recommended for surfaces such as concrete, metal, asphalt, gravel, and wood for the striping and marking of parking lots, road surfaces, warehouse areas, factory floors, underground utilities, construction and excavation sites, apartment complexes and fairgrounds.

III. Features & Benefits

- **High Solids Formula.** Provides the highest durability and best hide available.
- **Bright Vivid Lines.** High quality for improved visibility; won't wash away.
- **Long Lasting.** Excellent resistance to weather, abrasion, ultraviolet rays, water, oil, gasoline, and most in-plant cleaning solvents.
- **Fast Drying.** Tack free in 2 to 5 minutes.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**
- Available in **20 oz. aerosol** can size.

IV. Physical Properties with propellant

Resin System	Alkyd enamel	Boiling Point	134°F to 289°F
Flash Point	-100°F	% Volatile (by Wt.)	72
Odor and Appearance	Typical Ketone odor	Specific Gravity	>1
Vapor Density	Heavier than air	Propellant	Hydrocarbon
VOC Content (Fed) (Wt.)	66% maximum		
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	Yes		

V. Performance Characteristics

Dry Time, Tack Free	2 to 5 minutes
Linear Coverage	Up to 300 linear feet of 3.5 inch line width

VI. Directions

- Shake can well. After you hear the rattle of mixing ball, continue to shake the can for one minute.
- Turn can upside down and place in the can holder of the CRC 4-Way Portable Paint Striper, or the Economy Portable Striping Machine.
- Adjust for proper line width (2-5") by raising or lowering the handle of the 4-Way Portable Paint Striper.
- If striping is interrupted, shake the can again for 10 seconds before resuming striping.
- After use, to prevent sprayhead from clogging, hold can upright, away from face and eyes, and depress nozzle.
- Not recommended for use below 35°F.

VII. Package Description

Striping and Traffic Spray Paint	
18300	White
18301	Yellow

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn.

Some state and local agencies may require that aerosol paints be sold from locked cages or other specialized displays in order to conform to local anti-graffiti regulations. Check with local authorities to ensure compliance with existing regulations. CRC can provide locked cages to aid in conformance to anti-graffiti legislation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.