



I. Product Description

CRC Lecithin Mold Release is suitable for most applications where post-mold parts will be painted, stenciled, glued, bonded, laminated, hot-stamped or metalized. This product is a food-approved, vegetable based, non-silicone mold release. The rapid dry, anti-stick formula is suitable for cold and hot molds. **CRC Lecithin Mold Release** prevents sticking, which increases the life of dies and molds, improves product surface finishes and reduces production times.

II. Applications

Excellent for use in injection and compression molding of ABS, acetal, acrylic, nylon, polycarbonate, polyethylene, polypropylene, polystyrene, polysulfone, and rubber. Also for use on plastic wrap equipment, gaskets and seals.

III. Features & Benefits

- **Prevents Sticking** to increase the life of dies and molds, improve product surface finishes and reduce production times.
- **Rapid Dry**, anti-stick mold release agent suitable for cold and hot molds.
- **Vegetable-Based Lecithin** is a non-silicone, food approved release.
- **Completely Compatible** with secondary operations where parts must be painted, stenciled, glued, bonded, laminated, hot stamped or metalized. (No special cleaning required before part decoration.)
- **3.5% Solids** provide excellent general purpose lubrication up to 500°F .
- **Colorless, Odorless**, non-staining and non-corrosive.
- **Meets FDA Regulation 21 CFR 175.300** (release agent).
- **Meets 1998 USDA Guidelines** for use in meat and poultry plants.

IV. Physical Properties

Flash Point	ND	Boiling Point	ND
Odor	Mild	Freezing Point	ND
Appearance	Colorless liquid	Solubility	Neg. in water
Vapor Density	ND	% Volatile	97%
Vapor Pressure	ND	Specific Gravity	.95 @ 70°F
VOC Content (Fed)	335 g/L	Propellant	DME
Sara Title III, Sect. 313 Chemicals	Yes*		
Prop 65	No		

*1,1-Dichloro-1-Fluoroethane

V. Specifications and Approvals

- Meets 1998 USDA Guidelines for use in meat and poultry plants.
- Meets FDA Regulation 21 CFR 175.300 (release agent).

VI. Performance Characteristics

Evaporation Rate	Very fast
------------------	-----------

VII. Directions

- For best results do not over-spray.
- Apply a light, even film to mold surface as needed when sticking occurs.
- To avoid marked parts, do not over apply.
- Hold can 10" to 12" from mold surface.

VIII. Package Description

Part Number	Container Size
03306	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260