



I. Product Description

CRC Spinnerette Lubricant provides optimal lubrication to prevent clogged spinnerette heads without damaging fibers. This low odor silicone-based fluid exhibits high stability with very little change in velocity and flow. When dry, **Spinnerette Lubricant** will not boil, flash or gel up to 600° F. Prolonged release of lubricant permits longer intervals between scrape and wipe without jeopardizing fibers. **Spinnerette Lubricant's** optimum silicone level does not prevent finished fibers from accepting coloring agents. The unique trigger and bent straw combination adjust to spray any spinnerette configuration: horizontal, vertical, and 45°.

II. Applications

Recommended for the coating of metal spinnerette heads to prevent the adhesion of molten synthetic fibers. Safe on plastic and neoprene surfaces.

III. Features & Benefits

- **Improves Performance and Operating Efficiency.** Prevents clogged spinnerette heads which can lead to costly down-time for scraping and wiping.
- **Adjustable Application Method.** The trigger and bent straw combination effectively reaches spinnerettes in all positions to enhance convenience and eliminate costly multiple SKUs.
- **Precise Silicone Formulation.** Will not affect the acceptance of dyes by the finished fiber.
- **Corrosion Inhibiting and Water Displacing.** Helps prolong equipment life.
- **No Flash or Fire Point.** Significantly reduces the risk of fire caused by incidental contact with energized equipment.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	None	Boiling Point	90°F
Odor	Minimal	Solubility	Slight in water
Appearance	Light amber liquid	% Volatile	90%
Vapor Density	4.1 (air = 1)	Specific Gravity	1.19 @ 70°F
VOC Content (Fed)	Exempt	Propellant	134a
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	No		

V. Specifications and Approvals

- Not Applicable.

VI. Performance Characteristics

Type of Film	Dry
--------------	-----

VII. Directions

- Shake well before use.
- For vertical application, insert tube with long end into valve and short end pointed up. For horizontal application, do not use tube.
- Press firmly while inserting tube. Tube will seat tightly in valve.
- Hold can 10 to 12 inches from spinnerette and spray with a thin, light coat.
- Repeat application as necessary.
- Do not use on energized equipment.

VIII. Package Description

Part Number	Container Size
03170	16 oz Aerosol w/ Trigger

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

Restrictions

Contains HCFC (141b) which has use restrictions and may only be sold to professional users for applications consistent with the regulation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260