



I. Product Description

CRC Heavy Duty Mold Cleaner is a safety-solvent designed to quickly dissolve and remove silicone, grease, oil and residue on mold surfaces. **CRC Heavy Duty Mold Cleaner's** fast evaporating formulation is ideal for cleaning cold molds. It is non-flammable, non-conductive and non-abrasive.

II. Applications

Excellent for use on metal molds, pins, machinery and mechanical equipment.

III. Features & Benefits

- **Safety Solvent** designed to quickly dissolve and remove silicone, grease, oil and residue on mold surfaces.
- **Evaporates Rapidly** without leaving a residue.
- **Non-Flammable**, chemically stable, non-conductive and non-corrosive.
- **VOC Exempt** and does not contain known Ozone Depleting Substances.
- **Meets 1998 USDA Guidelines (K2)** for use in meat and poultry plants.

IV. Physical Properties without propellant

Flash Point	None	Boiling Point	189°F
Odor	Mild	Freezing Point	Not Determined
Appearance	Colorless liquid	Solubility	Neg. in water
Vapor Density	4.55	% Volatile	100%
Vapor Pressure	60 m @20° C	Specific Gravity	1.46 @ 70° F
VOC Content (Fed)	1400 g/L	Propellant	CO ₂
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	Yes		

V. Specifications and Approvals

- Meets 1998 USDA Guidelines (K2) for use in meat and poultry plants.

VI. Performance Characteristics

ASTM D-1130 (KB Value)	129
ASTM D-877 (Dielectric Strength)	36,700 volts
ASTM D-56 (Flash Point)	None
Evaporation Rate	Very fast

VII. Directions

- Protect all rubber parts, plastic parts and painted surfaces from over-spray. Do not spray directly on painted surfaces.
- Spray until clean. Begin at the top of the mold. Use extension tube for hard to reach areas.
- Air-dry or wipe with a dry, absorbent cloth. Use CRC Duster™ to accelerate drying time.
- Do not use on plastics – especially modern plastics such as LEXAN®, ABS and Noryl®. If uncertain, check with equipment manufacturer.

VIII. Package Description

Part Number	Container Size
03315	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.