



## ***I. Product Description***

**CRC Long Term Mold Saver** is a one-step rust preventative that contains both neutralizer and rust preventative. It provides positive protection by displacing moisture from metal surfaces and adhering tightly to the surface. **CRC Long Term Mold Saver** is ideal for mold and die protection.

## ***II. Applications***

Excellent for use on all metal molds and dies including plastic, rubber, drawing, stamping, die-casting, fine blanking, stripper plates, jigs and fixtures.

## ***III. Features & Benefits***

- **Long Term Corrosion Inhibitor** protects all metal molds with a light amber, transparent film.
- **Seals Out Moisture** and corrosive contaminants. Halts rust.
- **Dry, Self Healing Film** is highly resistant to humidity and salt spray.
- **Protects** up to 5 years under normal indoor storage conditions or up to 2 years outdoors.
- **Meets MIL-C-16173** Grade 4, Class 1.

## ***IV. Physical Properties without propellant***

<b>Flash Point</b>	104°F (TCC)	<b>Boiling Point</b>	141°F (initial)
<b>Odor</b>	Petroleum-like	<b>% Volatile</b>	74%
<b>Appearance</b>	Dark amber, viscous liquid	<b>Specific Gravity</b>	0.6939
<b>VOC Content (Fed)</b>	547 g/L	<b>Propellant</b>	Hydrocarbon
<b>Sara Title III, Sect. 313 Chemicals</b>	Yes		
<b>Prop 65</b>	Yes		

## ***V. Specifications and Approvals***

- Meets requirements for MIL-C-16173, Grade 4.

## VI. Performance Characteristics

Type of Film	Drying time = 1 hour
Film Thickness	2 mils dry
Coverage	1,000 sq. ft. per gal. @ 1 mil
Corrosion Resistance	Up to 2 years outdoors

## VII. Directions

- Shake can well before using this product.
- Best results are obtained when used above 60°F.
- Mask area not to be sprayed.
- Spray from a distance of 12 to 15 inches in light, even coats.
- Allow each coat to dry before applying next coat.
- For storage, clean valve by turning can upside down and pressing actuator until only propellant escapes.
- Remove with CRC Heavy Duty Mold Cleaner.
- **Do not apply while equipment is energized.**

## VIII. Package Description

Part Number	Container Size
03319	16 oz Aerosol

## IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

## X. Special Use Warnings

### Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.