



## ***I. Product Description***

**CRC Coil Cleaner** is a versatile, chlorinated solvent-based cleaner/degreaser that is extremely effective in removing grease and dirt on air conditioning and refrigeration coils. It aggressively dissolves grease, oil and sludge for more efficient operation of mechanical equipment. **Coil Cleaner** evaporates quickly, and is non-conductive, non-corrosive, and non-staining. **Coil Cleaner** dries residue free and does not require rinsing.

## ***II. Applications***

Recommended for the effective removal of grease, oil, dirt, lint and other contaminants from air conditioning and refrigeration condensers.

## ***III. Features & Benefits***

- **High Pressure.** Cuts through grease, dirt lint, and other debris.
- **No Flash or Fire Point.** Significantly reduces the risk of fire caused by incidental contact with live electrical equipment or solvents trapped by insulating materials.
- **Fast Evaporation.** Minimizes downtime associated with “clean-in-place” cleaning methods.
- **No Rinsing Required.**
- **No Class I or II Ozone Depleting Chemicals.** Alternative to 1,1,1 Trichloroethane products while complying with the EPA regulations on the use of ozone depleting chemicals.
- **S.D.[L.]<sup>®</sup> Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

## ***IV. Physical Properties without propellant***

<b>Flash Point</b>	None	<b>Boiling Point</b>	120°F
<b>Odor</b>	Irritating	<b>Solubility</b>	Slight in water
<b>Appearance</b>	Colorless liquid	<b>% Volatile</b>	98%
<b>Vapor Density</b>	4.53 (air = 1)	<b>Specific Gravity</b>	1.58 @ 70° F
<b>Vapor Pressure</b>	1315 hPa	<b>Propellant</b>	CO <sub>2</sub>
<b>VOC Content (Fed)</b>	7.8%		
<b>Sara Title III, Sect. 313 Chemicals</b>	Yes		
<b>Prop 65</b>	Yes		

## V. Performance Characteristics

ASTM D-1130 (KB Value)	105
ASTM D-877 (Dielectric Strength)	39,200 volts
ASTM D-56 (Flash Point)	None
Evaporation Rate	Very fast

## VI. Directions

- **For personal safety, do not use while equipment is energized.**
- Turn off fans on unit to be cleaned.
- Spray until clean.
- Use extension tube for hard-to-reach areas.
- Allow equipment to fully dry and vent before using.
- Drying time can be accelerated by using a dry, absorbent cloth or **CRC Duster™**.
- Do not use on plastics such as acrylic, ABS and polycarbonate. If uncertain, check with the manufacturer or test on a small area before using.

## VII. Package Description

Part Number	Container Size
03195	20 oz Aerosol

## VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

## IX. Special Use Warnings

### Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.