



I. Product Description

Econo Wash is a unique blend of petroleum-distillates and alcohol which provides a suitable precision cleaner for sensitive electronics and electrical equipment. **Econo Wash** is a cost effective alternative to all contact cleaners. **Econo Wash** evaporates quickly, leaves no residue and is safe to use on all plastics.

II. Applications

Recommended for the cleaning of printed circuit boards, telephones, motors, relays, generators, edge connectors, tape heads, buss bars and circuits. Effectively removes dirt, dust, light oils and fingerprints from contacts, switches and breakers.

III. Features & Benefits

- **Plastic Safe.** Allows one product to be used in all applications without risk of costly damage to sensitive modern plastics.
- **Leaves No Residue.** Prevents harmful build-up on equipment and eliminates wiping and rinsing.
- **Fast Evaporation.** Minimizes downtime.
- **No Class I or Class II Ozone Depleting Chemicals.** Offers effective performance while complying with EPA regulations on the use of ozone depleting chemicals.

IV. Physical Properties without propellant

Flash Point	<0°F	Boiling Point (initial)	141°F
Odor	Petroleum	Solubility	Neg. in water
Appearance	Clear	% Volatile	100%
Vapor Density	>1 (air = 1)	Specific Gravity	0.6699
VOC Content (Fed)	649 g/L	Vapor Pressure	Not Determined
Sara Title III, Sect. 313 Chemicals	Yes	Freezing Point	<0°F
Prop 65	No	Propellant	CO ₂

V. Specifications and Approvals

- N/A

VI. Performance Characteristics

ASTM D-1130 (KB Value)	27
ASTM D-877 (Dielectric Strength)	22,600 volts/mil
Belcore Test (Plastic Compatibility)	Passed

VII. Directions

- * Spray until clean and allow cleaner to run-off.
- * Use an abrasive on heavy carbon deposits or corrosion to accelerate cleaning.
- * Do not use on energized equipment.
- * Allow to dry thoroughly and vent before reactivating system.
- * Follow routine maintenance schedule for prolonged equipment life and increased performance.

VIII. Package Description

Part Number	Container Size
04010	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260