



## ***I. Product Description***

**CRC General Purpose Silicone Lube** is a multi-purpose silicone spray. It forms a colorless, odorless, non-staining film that lubricates and protects in most metal and non-metal applications. **General Purpose Silicone Lube's** dry film eliminates binding and sticking, while protecting most surfaces. **General Purpose Silicone Lube** is a non-hardening lubricant that minimizes corrosion. In addition, it may be used as a release agent for many applications.

## ***II. Applications***

Recommended for lubricating coin mechanisms, linkages, locks, motor bearings, parking meters, projectors, pulleys, timers, rubber seals, tools, vending machines and ceramic insulators. Also recommended for metal-to-non-metal and plastic-to-plastic lubrication applications. Protects electronic and electrical contact and connector surfaces from corrosion.

## ***III. Features & Benefits***

- **Wide Temperature Range.** Effective from -40°F to 400°.
- **Low Surface Tension.** Allows for better coverage and deeper penetration.
- **Non-Hardening Film.** Minimizes corrosion and provides excellent lubricity.
- **Reduces Galling and Friction on Metal-to-Non-Metal Contact Areas.** Reduces wear on parts to promote extended equipment life.
- **Harmless to Most Rubbers and Plastics.**
- **Waterproofs.**
- **360° Valve.** Product can be sprayed from any position – even upside down.

## ***IV. Physical Properties without propellant***

<b>Flash Point</b>	20°F		<b>Boiling Point</b>	141°F (initial)
<b>Odor</b>	Solvent		<b>Solubility</b>	Negligible in H <sub>2</sub> O
<b>Appearance</b>	Clear, water-white liquid		<b>% Volatile</b>	97
<b>Vapor Density</b>	>air		<b>Specific Gravity (bulk)</b>	0.700
<b>VOC Content (Fed)</b>	<u>Aerosol</u> 641 g/L	<u>Bulk</u> 675 g/L	<b>Dielectric Strength</b>	350 volts/mil
<b>Sara Title III, Sect. 313 Chemicals</b>	Yes		<b>Propellant</b>	Hydrocarbon
<b>Prop 65</b>	No		<b>% Solvent</b>	3.0%

## ***V. Specifications and Approvals***

- N/A

**VI. Performance Characteristics**

Type of Film	Dry, clear, non-hardening
Temperature Range	-40°F to 400°F

**VII. Directions**

- Spray a light, even film on areas requiring lubrication or protection.
- Use extension tube for hard-to-reach areas.
- Repeat application if necessary.
- Do not use on energized equipment.

**VIII. Package Description**

Part Number	Container Size
04080	16 oz Aerosol

**IX. Disposal**

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

**IX. Special Use Warnings****Aerosol Cans**

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**General**

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.