



I. Product Description

CRC Layout Fluid Remover is specifically formulated to remove layout fluids quickly and effectively.

II. Applications

Recommended for use by tool and die makers, machinists, pattern makers and maintenance mechanics.

III. Features & Benefits

- Super strength formula removes layout fluids
- Leaves no residue
- Non-Chlorinated

IV. Physical Properties without propellant

Flash Point	<0°F TCC	Boiling Point	131°F (initial)
Odor	Aromatic	Solubility	Slight in H ₂ O
Appearance	Clear, colorless liquid	VOC %	45%
Vapor Density	Heavier than air	Specific Gravity	0.815
Vapor Pressure	Not Determined	Freezing Point	Not Determined
VOC Content (Fed)	366 g/L	pH	N/A
Sara Title III, Sect. 313 Chemicals	Yes	Propellant	Carbon Dioxide
Prop 65	Yes		

V. Specifications and Approvals

Not applicable.

VI. Directions

1. Use Layout Fluid Remover in a well ventilated area. For best results, container should be used and stored at room temperature.
2. Hold can upright and depress actuator holding can 8" to 10" from surface to be cleaned.
3. Spray Layout fluid Remover evenly across surface to be cleaned.
4. Wipe surface off with a clean cloth.

VII. Package Description

Part Number	Container Size
03069	16 oz Aerosol

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Vapors will accumulate readily and may ignite. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260