



I. Product Description

CRC Clear Penetrating Grease is a heavy-duty clear penetrating gel that provides superior lubrication and withstands high temperatures and pressures. **Clear Penetrating Grease** has tremendous adhesive strength and penetrates deep to form a tenacious, long-lasting film. It is waterproof and resistant to acids, alkalis, salt, oxidation, weather and steam. **Clear Penetrating Grease** can extend the operating service life of equipment and reduce wear, galling and scarring.

II. Applications

Recommended to lubricate door hinges, latches, open gears , wire ropes, sprockets, conveyors, roller chains, pulleys and cables

III. Features & Benefits

- **Contains PTFE.** PTFE enhances lubrication performance and reduces friction.
- **Heavy Duty Formula.** High tack, clear lubricating gel extends operating service life of equipment.
- **Withstands High Temperature and Pressure.** Will not break down, harden or separate at extreme pressures or temperatures (up to 500°F).
- **Waterproofs and Prevents Corrosion.** Resistant to acids, alkalis, salt, oxidation, weather and steam.
- **Penetrates to Form a Thick Film.** Deep penetrating formula quickly thickens to form a long-lasting grease.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	25°F TCC	Boiling Point	175°F (initial)
Odor	Minimal	Solubility	Slight
Appearance	Clear grease	Specific Gravity	0.80
VOC Content (Fed) %	45%	Propellant	Hydrocarbon
Sara Title III, Sect. 313 Chemicals	No		
Prop 65	No		
Vapor Density	>1 (air=1)		

V. Specifications and Approvals

- Not Applicable

VI. Performance Characteristics

Working Temperature	-30°F to 500°F
Type of Film	Non drying
Base Type	Petroleum

VII. Directions

- For personal safety, do not apply while equipment is energized.
- For best results, prepare surface by cleaning with a CRC Cleaner.
- Shake can well before use.
- Hold can 8" to 12" away from surface to be sprayed
- Spray in light, even coats.
- Wipe off excess with a clean cloth
- Use extension tube for hard-to-reach areas.
- Repeat application if necessary.

VIII. Package Description

Part Number	Container Size
03056	20 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well-ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800) 521-3168

Industrial Products Division
Customer Service: (800) 272-4620

Warminster, PA 18974
CRC On-Line: (215) 442-6260