



## ***I. Product Description***

**CRC TAC 2™** is an exceptional lubricant, with a tough adhesive quality, which will bond to chain/wear surfaces to keep them in peak operating condition by reducing friction and wear that cause metal fatigue. **CRC TAC 2™** contains a tackifier that enables the lubricant to cling tenaciously to metal surfaces without increasing the viscosity. Regular use of **CRC TAC 2™** will help inhibit corrosion, reduce load stress and help increase chain life.

## ***II. Applications***

Recommended for use as a lubricant and corrosion inhibitor on all types of drive chains, open gears, hoists, winches, pulleys, fork lifts, rollers, garage doors, bushings, seals, o-rings, and wire ropes.

## ***III. Features & Benefits***

- **Low Viscosity.** Provides the ability to penetrate and thoroughly coat vital chain pin and bushing areas.
- **Contains Molybdenum.** Provides cling ability to avoid sling-off or excess dripping.
- **High Temperature Stability.** Operates effectively in temperatures up to 350° F continuous, equivalent to many grease products. Covers wide range of applications.
- **Blue Color** allows easy identification of lubricated parts and equipment.
- **No Known Ozone Depleting Chemicals.** Offers effective performance while complying with the EPA regulations on the use of ozone depleting chemicals.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

## ***IV. Physical Properties without propellant***

<b>Flash Point</b>	<0°F TCC	<b>Boiling Point</b>	140°F
<b>Odor</b>	Mild petroleum	<b>Solubility</b>	Negligible in water
<b>Appearance</b>	Blue liquid	<b>% Volatile</b>	81.3%
<b>Vapor Density</b>	>1 (air=1)	<b>Specific Gravity</b>	0.710
<b>VOC Content (Fed)</b>	577.2 g/L	<b>Temperature Range</b>	350°F (Continuous)
<b>Shelf Life</b>	2 years	<b>Propellant</b>	Hydrocarbon
<b>Sara Title III, Sect. 313 Chemicals</b>	Yes		
<b>Prop 65</b>	No		

## ***V. Specifications and Approvals***

- NSF Registration # 144243, Category Code (H2) for use in federally inspected meat and poultry plants.

## VI. Performance Characteristics

Type of Film	Non-drying
Base Type	Organic Molybdenum
ASTM D-3233 (Falex Load Test)	1,500 lbs.

## VII. Directions

1. Do not apply while equipment is energized.
2. Shake well before use.
3. Spray upper edges of overlapping chain side plates and allow lubricant to set up before re-energizing.

## VIII. Package Description

Part Number	Container Size
03076	16 oz Aerosol

## IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

## X. Special Use Warnings

### Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### Bulk

Product is extremely flammable and should be kept from all flames and other ignition sources. Vapors are heavier than air and can collect in low-lying areas.

### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.