



I. Product Description

CRC Fire Ant Killer is a fast-acting, high strength insecticide that kills fire ants on contact. **Fire Ant Killer** contains no chlorinated solvents and is harmless to most plastics. It features a high dielectric strength of 47,600 volts. Fire Ant Killer can be used to kill ants in their mounds by using the injector rod attachment or it can be used to kill visible ants on the surface.

II. Applications

Recommended for any outdoor worker around electric and power utilities, telecommunications equipment and installation sites, cable and wire installation sites, and industrial plant grounds.

III. Features & Benefits

- **Kills on contact.**
- **Non-chlorinated formulation.** Replaces chlorinated solvent-based fire ant killers.
- **Safe on most plastics.** Test first on a small area.
- **Reaches Over 20 Feet.** Provides a dense accurate spray to drench harmful insects and their nests.
- The only Fire Ant Killer in the industry with its own **Material Safety Data Sheet** right on the label. Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	205°F (TCC)	Freezing Point	Not determined
Odor	Petroleum	Boiling Point	435°F (initial)
Appearance	Clear liquid	Solubility	Neg. in H ₂ O
Vapor Density	>2 (air = 1)	VOC %	1.4%
Vapor Pressure	<0.1 mm Hg	Specific Gravity	0.79
Sara Title III, Sect. 313 Chemicals	Yes	Propellant	CO ₂
VOC Content (Fed)	11.06 g/L		
Prop 65	No		

V. Specifications and Approvals

- EPA Reg. No. 55809-3
- This product is registered for sale in the following states: AL, AR, AZ, CA, FL, GA, KY, LA, MS, NC, NM, OK, SC, TN, TX, and VA. Sale in any other state or outside of the United States is prohibited.

VI. Performance Characteristics

ASTM D-877 (Dielectric Strength)	47,600 volts
----------------------------------	--------------

VII. Directions

- **To kill Fire Ants in their mounds:** DO NOT DISTURB MOUND PRIOR TO TREATMENT.
- Attach injector rod to can by threading the rod onto the spray nozzle.
- Slowly drive rod into the mound while spraying and continue until reaching the bottom of the nest. Spray at a rate of 5-10 seconds per injection.
- Inject the mound 3-6 places depending on the size of the mound.
- Space injection sites in a circular pattern on the mound surface with one site in the center.
- For best results, treatment should be made in early morning or late evening when ants are least active.
- **To kill Fire Ants on the surface:** Without using the injector rod sweep surface with spray from a distance of 18 inches. Do not apply when windy.

VIII. Package Description

Part Number	Container Size
14037	20 oz Aerosol w/ Trigger

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260